

Commercial/Industrial Floodplain Development Permit

Doddridge County, WV Floodplain Management

This permit has been issued to EQT Production Company, and is for the approved commercial and/or industrial development project associated with this permit that impacts the FEMA-designated floodplain and/or floodway of Doddridge County, WV, pursuant to the rules and regulations established by all applicable Federal, State and local laws and ordinances, including the Doddridge County Floodplain Ordinance. This permit must be posted at the site of work as to be clearly visible, and must remain posted during entirety of development.

Permit: #15-375

Date Approved: 08/26/2015 Expires: Not in FloodPlain

Issued to: EQT Production Co POC:

Company Address:120 Professional Place, Bridgeport, WV 26330

Project Address: Co. Rt. 4/Broad Run

Firm: #54017C0045C Lat/Long: 39.411532, -80.661258

Purpose of development: Well Pad

Issued by: George C. Eidel, Doddridge County FPM (or designee)

For additional information regarding this permit, please contact Doddridge County Floodplain Manager at 304.873.2631, or via email at doddridgecountyfpm@gmail.com

/26/2015

118 East Court Street; West Union, WV 26456



August 20, 2015

2015 AUG 21 PM 2: 55



Mr. George Eidel
Floodplain Coordinator
Doddridge County Commission
118 East Court Street
West Union, WV 26456

Re: Doddridge County Floodplain Development Permit Application (Outside Floodplain)

CPT-10 Well Pad Project
Doddridge County, West Virginia
EQT Production Company

Dear Mr. Eidel:

EQT Production Company (EQT) proposes to construct the proposed CPT-10 Well Pad (Project) in Doddridge County, West Virginia (Figure 1). The proposed Project will support EQT's natural gas development of state permitted wells and will be accessible from County Route 4 at 39.411532°, -80.661258°. Kleinfelder, Inc. (Kleinfelder), on behalf of EQT, has enclosed a Doddridge County Floodplain Development Permit Application for your review and approval.

A list of property owners located within the proposed Project is included as Attachment A. Figures 1 and 2 present the project on USGS Topographic and Aerial Maps, respectively and depicts the proposed area-of-interest (AOI) and limit-of-disturbance associated with the well pad construction activities.

Kleinfelder biologists conducted stream and wetland investigations and habitat assessments on October 30 – 31, 2013, August 19, 2014, and February 2, 2015 to identify streams and wetlands within a 110.0-acre AOI surrounding the proposed Project. During the site review, seven (7) jurisdictional features were observed within the AOI and included five (5) ephemeral streams, one (1) intermittent stream, and one (1) palustrine emergent wetland.

Based on the engineered design plans (Attachment B), construction activities will permanently impact one (1) intermittent stream.

Construction of the proposed Project will not take place within a designated Federal Emergency Management Administration regulated flood zone according to FIRM Map #54017C0045C within Doddridge County (Attachment C). There will be no fill deposited and no impacts to the floodplain as a result of construction acitivities.

<u>Directions to the Site from Center Point, WV:</u> Head north on WV-23 W toward Hill Street. Make a slight right onto County Route 4/Broad Run and continue for 0.9 mile. The entrance to the Project will be on your left.

We appreciate your timely review of this request. Please contact Matt Albright (724-831-5101) of Kleinfelder or Lacoa Corder (304-848-0066) of EQT with any questions.

Respectfully submitted,

Matthew J. Albright Project Manager

matthing. curlt

c: Lacoa Corder, EQT

Enclosures (6)

Doddridge County Floodplain Development Permit Application
Figure 1 -- Project Location Map
Figure 2 -- Delineation Map
Attachment A -- Property Owner Table
Attachment B -- Engineered Design Plans
Attachment C -- Floodplain Map

Josh Farley, PE Senior Engineer

M



DODDRIDGE COUNTY FLOODPLAIN DEVELOPMENT PERMIT APPLICATION

SECTION 1: GENERAL PROVISIONS (APPLICANT TO REAL AND SIGN)

- 1. No work may start until a permit is issued.
- 2. The permit may be revoked if any false statements are made herein.
- 3. If revoked, all work must cease until permit is re-issued.
- 4. Development shall not be used or occupied until a Certificate of Compliance is issued.
- 5. The permit will expire if no work is commenced within six months of issuance.
- 6. Applicant is hereby informed that other permits may be required to fulfill local, state, and federal requirements.
- 7. Applicant hereby gives consent to the Floodplain Administrator/Manager or his/her representative to make inspections to verify compliance.
- 8. I, THE APPLICANT CERTIFY THAT ALL STATEMENTS HEREIN AND IN ATTACHMENTS TO THIS APPLICATION ARE, TO THE BEST OF MY KNOWLEDGE, TRUE AND ACCURATE.

DATE 8/19/15

SECTION 2: PROPOSE DEVELOPMENT (TO BE COMPLETED BY APPLICANT).

IF THE APPLICANT IS NOT A NATURAL PERSON, THE NAME, ADDRESS, AND TELEPHONE NUMBER OF A NATURAL PERSON WHO SHALL BE APPOINTED BY THE APPLICANT TO RECEIVE NOTICE PURSUANT TO ANY PROVISION OF THE CURRENT DODDRIDGE COUNTY FLOODPLAIN ORDINANCE.

APPLICANT'S NAME: EQT Production Company c/o Lacoa Corder

ADDRESS: 120 Professional Place, Bridgeport, WV 26330

TELEPHONE NUMBER: <u>304-848-0066</u>

BUILDER'S NAME: EQT Production Company

ADDRESS: 120 Professional Place, Bridgeport, WV 26330

TELEPHONE NUMBER: 304-848-0066

ENGINEER'S NAME: Josh Farley, P.E.

ADDRESS: 230 Executive Drive, Suite 122, Cranberry Township, PA 16066

TELEPHONE NUMBER: 724-831-5108

PROJECT LOCATION:

NAME AND ADDRESSES FOR SURFACE OWNER/OWNERS (IF NOT THE APPLICANT) See Attachment A

DISTRICT: McClellan

DATE/FROM WHOM PROPERTY PURCHASED: N/A

LAND BOOK DESCRIPTION: <u>See Attachment A</u>

DEED BOOK REFERENCE: <u>See Attachment A</u>

TAX MAP REFERENCE: <u>See Attachment A</u>

EXISTING BUILDINGS/USES OF PROPERTY: N/A

NAME OF AT LEAST ONE ADULT RESIDING IN EACH RESIDENCE LOCATED UPON THE SUBJECT PROPERTY See Attachment A

ADDRESS OF AT LEAST ONE ADULT RESIDING IN EACH RESIDENCE LOCATED UPON THE SUBJECT PROPERTY See Attachment A

To avoid delay in processing the application, please provide enough information to easily identify the project location.

DESCRIPTION OF WORK (CHECK ALL APPLICABLE BOXES)

A. STRUCTURAL DEVELOPMENT

ACTIVITY

STRUCTURAL TYPE

	New Structure Addition Alteration Relocation Demolition Manufactured/Mobil Home		Residential (1—4 Family) Residential (more than 4 Family) Non-residential (floodproofing) Combined Use (res. & com.) Replacement
В.	OTHER DEVEOPLMENT ACTIVITIES:		
	Fill Mining Grading Excavation (except for STRUCTURAL D Watercourse Altercation (including dred Drainage Improvements (including culve Road, Street, or Bridge Construction Subdivision (including new expansion) Individual Water or Sewer System Other (please specify)	ging and cha	ENT checked above)

C. STANDARD SITE PLAN OR SKETCH

- 1. SUBMIT ALL STANDARD SITE PLANS, IF ANY HAVE BEEN PREPARED.
- 2. IF STANDARD SITE PLANS HAVE NOT BEEN PREPARED:

SKETCH ON A SEPARATE 8 1/2 X 11 INCH SHEET OF PAPER THE SHAPE AND LOCATION OF THE LOT. SHOW THE LOCATION OF THE INTENDED CONSTRUCTION OR LAND USE INDICATING BUILDING SETBACKS, SIZE & HEIGHT. IDENTIFY EXISTING BUILDINGS, STRUCTURES OR LAND USES ON THE PROPERTY.

3. SIGN AND DATE THE SKETCH.

ACTUAL TOTAL CONSTRUCTION COSTS OF THE COMPLETE DEVELOPMENT IRRESPECTIVE OF WHETHER ALL OR ANY PART OF THE SUBJECT PROPOSED CONSTRUCTION PROJECT IS WITHIN THE FLOODPLAIN Not Applicable.

D. ADJACENT AND/OR AFFECTED LANDOWNERS:

1. NAME AND ADDRESS OF ALL OWNERS OF SURFACE TRACTS ADJACENT TO THE AREA OF THE SURFACE TRACT (UP & DOWN STREAM) UPON WHICH THE PROPOSED ACTIVITY WILL OCCUR AND ALL OTHER SURFACE OWNERS UP & DOWN STREAM) WHO OWN PROPERTY THAT MAY BE AFFECTED BY FLOODING AS IS DEMONSTRATED BY A FLOODPLAIN STUDY OR SURVEY (IF ONE HAS BEEN COMPLETED).

See Attachment A

1. NAME AND ADDRESS OF AT LEAST ONE ADULT RESIDING IN EACH RESIDENCE LOCATED UPON ANY ADJACENT PROPERTY AT THE TIME THE FLOODPLAIN PERMIT APPLICATION IS FILED AND THE NAME AND ADDRESS OF AT LEAST ONE ADULT RESIDING IN ANY HOME ON ANY PROPERTY THAT MAY BE AFFECTED BY FLOODING AS IS DEMONSTRATED BY A FLOODPLAIN STUDY OR SURVEY.

NAME: See Attachment A	NAME:
ADDRESS:	_ ADDRESS:

E. CONFIRMATION FORM

THE APPLICANT ACKNOWLEDGES, AGREES, AND CONFIRMS THAT HE/IT WILL PAY WITHIN 30 DAYS OF RECEIPT OF INVOICE BY THE COUNTY FOR ALL EXPENSES RELATIVE TO THE PERMIT APPLICATION PROCESS GREATER THAN THE REQUIRED DEPOSIT FOR EXPENSES INCLUDING:

- (A) PERSONAL SERVICE OF PROCESS BY THE DODDRIDGE COUNTY SHERIFF AT THE RATES PERMITTED BY LAW FOR SUCH SERVICE.
- (B) SERVICE BY CERTIFIED MAIL RETURN RECEIPT REQUESTED.
- (C) PUBLICATION.
- (D) COURT REPORTING SERVICES AT ANY HEARINGS REQUESTED BY THE APPLICANT.
- (E) CONSULTANTS AND/OR HEARING EXPERTS UTILIZED BY DODDRIDGE COUNTY FLOODPLAIN ADMINISTRATOR/MANAGER OR FLOODPLAIN APPEALS BOARD FOR REVIEW OF MATERIALS AND/OR TESTIMONY REGARDING THE EFFICACY OF GRANTING OR DENYING THE APPLICANT'S FLOODPLAIN PERMIT.

NAME (PRINT): <u>Lacoa</u> Corder			
SIGNATURE:	Jacoa	Corder	DATE: 8	119/15

After completing SECTION 2, APPLICANT should submit form to Floodplain Administrator/Manager or his/her representative for review.

SECTION 3: FLOODPLAIN DETERMINATION (to be completed by Floodplain Administrator/Manager or his/her representative)

THE F	ROPOSED DEVELOPMENT:
THE F	PROPOSED DEVELOPMENT IS LOCATED ON:
FIRM Dated	Panel: :
•	Is NOT located in a Specific Flood Hazard Area (Notify applicant that oplication review is complete and NO FLOOPLAIN DEVELOPMENT IIT IS REQUIRED).
[]	Is located in Special Flood Hazard Area. FIRM zone designation 100-Year flood elevation is: NGVD (MSL)
[]	Unavailable
0	The proposed development is located in a floodway. FBFM Panel No Dated

See section 4 for additional instructions.

[]

e=	ст і	ON 4: ADDITIONAL INCORMATION REQUIRED (To be consulated by				
	SECTION 4: ADDITIONAL INFORMATION REQUIRED (To be completed by Floodplain Administrator/Manager or his/her representative)					
		oplicant must submit the documents checked below before the application can be sed.				
		A plan showing the location of all existing structures, water bodies, adjacent roads, lot sions and proposed development.				
bas floc	ails sem od p	Development plans, drawn to scale, and specifications, including where applicable: for anchoring structures, storage tanks, proposed elevation of lowest floor, (including ent or crawl space), types of water resistant materials used below the first floor, details of roofing of utilities located below the first floor and details of enclosures below the first floor				
[]		Subdivision or other development plans (If the subdivision or development exceeds 50				
		5 acres, whichever is the lesser, the applicant must provide 100-year flood elevations if e not otherwise available).				
[]		Plans showing the extent of watercourse relocation and/or landform alterations.				
[]		Top of new fill elevation Ft. NGVD (MSL). For flood proofing structures applicant must attach certification from registered engineer or architect.				
[]	•	Certification from a registered engineer that the proposed activity in a regulatory floodway will not result in any increase in the height of the 100-year flood. A copy of all data and calculations supporting this finding must also be submitted.				

_____ DATE

SIGNED _

[]

Contractor's License and a Manufactured Home Installation License as required by the

Manufactured homes located in a floodplain area must have a West Virginia

Federal Emergency Management Agency (FEMA).

Aummstrat	<u>or/Manager or his/her represe</u>	entative)
conformand County Cor	nmission of Doddridge Cour	ctivity (type is or is not) in odplain Ordinance adopted by the aty on May 21, 2013. The permit is ed to and made part of this permit.
SIGNED		DATE
conformand Ordinance	e with the provisions of the	er found that the above was not in Doddridge County Floodplain on, the applicant may complete an
APPEALS:	Appealed to the County Co	ommission of Doddridge County?
[] Yes {} No	Hearing Date:	

SECTION 6: AS-BUILT ELEVATIONS (To be submitted by APPLICANT before Certificate of Compliance is issued).

The following information must be provided for project structures. This section must be completed by a registered professional engineer or a licensed land surveyor (or attach a certification to this application).

COMPLETE 1 OR 2 BELOW:

1	Actual (As-Built) Elevation of the top of the lowest floor (including basement or
	crawl space is FT. NGVD (MSL)
2	Actual (As Built) elevation of floodproofing is FT. NGVD (MSL)
Note	e: Any work performed prior to submittal of the above information is at risk of
	applicant.
SEC	TION 7: COMPLIANCE ACTION (To be completed by the Floodplain
<u>Adn</u>	ninistrator/Manager or his/her representative).
	Floodplain Administrator/Manager or his/her representative will complete this section
	pplicable based on inspection of the project to ensure compliance with the Doddridge
Cou	nty Floodplain Ordinance.
I	INSPECTIONS:
	DATE: BY:
	DEFICIENCIES ? Y/N
	COMMENTS
SEC	TION 8: CERTIFICATE OF COMPLIANCE (To be completed by Floodplain
Adn	ninistrator/Manager or his/her representative).
Cort	difference of Compliance issued: DATE: PV:

CERTIFICATE OF COMPLIANCE FOR DEVELOPMENT IN SPECIAL FLOOD HAZARD AREA (OWNER MUST RETAIN)

	RMIT NUMBER:	
, L.		
PURPOSE	-	
CONSTRUCTION LOCATION:		
OWNER'S ADDRESS:		
	•	
THE FOLLOWING MUST BE CO	MPLETED BY THE FLOODPLAIN	
ADMINISTRATOR/MANAGER O	R HIS/HER AGENT.	
COMPLIANCE IS HEDER	BY CERTIFIED WITH THE REQUIREMENT OF THE	
	PTED BY THE COUNTY COMMISSION OF	
DODDRIDGE COUNTY ON MAY		
SIGNED	DATE	

FIGURES

Proposed AOI Access Point 39.411532 -80.661258

FIGURE 1 PROJECT LOCATION MAP

CPT-10 Well Pad **EQT Production Company** Doddridge County, WV



Legend

AOI (110.0 ac) Proposed LOD (40.5 ac)

Proposed Well Pad

Proposed Access Road

Proposed Completion Pit

Proposed Flow Back Pit

---- NHD Stream

NWI Wetland (N/A)

USFWS Aquatic Buffer

USFWS Terrestrial Buffer

FEMA 100 Year Flood Zone

--- Existing Road

PROJECT #: 00137355.000A

DRAWN: 7/15/2014

PRINTED: 8/10/2015

DRAWN BY: GHB

CHECKED BY: MA

FILE NAME:

G:\GIS\PROJECTS\EQT\Production\CPT-10-137355\MXD\WDSIR\CPT-10_Fig1.mxd



2,000






STREAM 5 STREAM 2 CHECKED BY: MA STREAM 3 STREAM 4

FIGURE 2 **DELINEATION MAP**

CPT-10 Well Pad **EQT Production Company** Doddridge County, WV



AOI (110.0 ac) Proposed LOD (40.5 ac) Proposed Well Pad

Proposed Access Road - - Delineated Intermittent Stream

Delineated Ephemeral Stream Delineated PEM Wetland

--- Existing Culvert

Proposed Completion Pit

Proposed Flow Back Pit

Existing Road

USFWS Aquatic Buffer (N/A) USFWS Terrestrial Bufferr (N/A)

PROJECT #: 00137355.000A

DRAWN: 7/15/2014


PRINTED: 8/10/2015

DRAWN BY: GHB

FILE NAME:

G:\G\S\PROJECTS\EQT\Production\CPT-10-137355\MXD\WDS\R\CPT-10_Fig2_Delineation.mxd










ATTACHMENT A PROPERTY OWNER TABLE

Property Owner Table - Doddridge County EQT Production Company - CPT-10 Well Pad Project

Property Owner Name	Mailing Address	Parcel ID	Deed Book Reference	Land Book Description		
HOST PROPERTIES - OUTSIDE FLOODPLAIN						
HAYES SHIRLEY JAMES & MA	81 Broad Run Rd. Center point, WV 26339	7-10-2	Deed Book 203	Page 183-184		
ASH SAMUEL G ET UX	Route 4 Center Point, WV 26339	5-12-2.3	Deed Book 201	Page 350		
COASTAL FOREST RESOURCES	Off Route 4/Broad Run Road	5-6-27	Deed Book 78	Page 313		

ATTACHMENT B ENGINEERED DESIGN PLANS



CPT-10 WELL PAD SITE DESIGN & CONSTRUCTION PLAN, **EROSION & SEDIMENT CONTROL PLANS**

EQT PRODUCTION COMPANY

Where energy meets innovation.

PROJECT CONTACTS

PROJECT OWNER

EQT PRODUCTION COMPANY CONTACT: CHRIS METZGAR 115 PROFESSIONAL PLACE BRIDGEPORT, WV 26330 304.848.0075 OFFICE

LOCATION SURVEYOR

ENCOMPASS ENERGY SERVICES, LLC CONTACT: TYLER HASTINGS 1370 WASHINGTON PIKE, SUITE 308 BRIDGEVILLE, PA 15017 412.564.5215 OFFICE

ENVIRONMENTAL/ **DELINEATION BOUNDARY**

KLEINFELDER CONTACT: MATTHEW ALBRIGHT 230 EXECUTIVE DRIVE, SUITE 122 CRANBERRY TOWNSHIP, PA 16066 724.772.7079 FAX

ENGINEER OF RECORD

KLEINFELDER
CONTACT: JOSH FARLEY, PE
WV PE #020711
230 EXECUTIVE DRIVE, SUITE 122
CRANBERRY TOWNSHIP, PA 16066
724.772.7072 OFFICE
724.772.7079 FAX

TOPO SURVEYOR

BLUE MOUNTAIN AERIAL MAPPING CONTACT: CRAIG FRY 11023 MASON DIXON HIGHWAY BURTON, WV 26562 304.662.2626 OFFICE 304.815.4890 CELL

SITE LOCATION						
DESCRIPTION	NAD 83	(DEGREES)	UTM ZONE 17N NAD 83 (M)			
DESCRIPTION	LATITUDE (N)	LONGITUDE (W)	NORTHING	EASTING		
CENTER OF WELL PAD	39.413493° N	80.660501° W	4362718.95	529225.97		
CENTER OF COMPLETION PIT	39.417796° N	80.664784° W	4363195.12	528855.49		
CENTER OF FLOWBACK PIT	39.415813° N	80.660713° W	4362976.36	529206.76		
MAIN ACCESS ROAD ENTRANCE	39.411547° N	80.661251° W	4362502.75	529162.22		
WELL PAD ACCESS ROAD ENTRANCE	39.413638° N	80.659453° W	4362735.39	529316.13		

FLOOD CONDITIONS	
DO SITE CONSTRUCTION ACTIVITIES TAKE PLACE IN FLOODPLAIN	NO
PERMIT NEEDED FROM COUNTY FLOODPLAIN COORDINATOR:	NO
HEC-RAS STUDY COMPLETED:	N/A
FLOODPLAIN SHOWN ON DRAWINGS:	NO
FIRM MAP NUMBER FOR SITE:	54017C0045C
ACREAGE OF CONSTRUCTION IN FLOODPLAIN:	N/A

211	
Hann valuets heldett. Call before yourdy.	
THREE DAYS BEFORE	

YOU DIG

CALL PA ONE CALL SYSTEM TOLL FREE 811 1-800-242-1776

DESCRIPTION FEET MAIN ACCESS ROAD 3,100 PAD ACCESS ROAD

ACCESS ROAD

LENGTH (FEET)

DESIGN CERTIFICATION

THE DRAWINGS, CONSTRUCTION NOTES, AND REFERENCE DIAGRAMS ATTACHED HERETO HAVE BEEN PREPARED IN ACCORDANCE WITH THE WEST VIRGINIA CODE OF STATE RULES, DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS §35-4-21 AND §35-8.

MM-109 PERMIT

EQT PRODUCTION COMPANY WILL OBTAIN AN ENCROACHMENT PERMIT (MM-109) FROM THE WEST VIRGINIA DEPARTMENT OF TRANSPORTATION, DIVISION OF HIGHWAYS, PRIOR TO THE COMMENCEMENT OF CONSTRUCTION ACTIVITIES

PROPOSED COMPLETION PIT	PROPOSED TOPSOIL STOCKPILE 3
	PROPOSED FLOWBACK PIT
PROPOSED SPOIL STOCKPILE 2	
PROPOSED TOPSOIL STOCKPILE 2	PROPOSED SPOIL STOCKPILE 1
PROPOSED TOPSOIL STOCKPILE 1	
PROPOSED SPOIL STOCKPILE 3	BM / W
PROPOSED TOPSOIL STOCKPILE 4	#ana/
PROPOSED WELL PAD ACCESS ROAD	
	PROPOSED MAIN ACCESS ROAD
PROPOSED WELL DAD	Contraction (1)

NORTH MERIDIAN	
REFERENCED TO NAD83	
WEST VIRGINIA STATE	
DI ANE NODTU ZONE	

BOARD AND SHOW WITH A PARTY OF THE PARTY OF

AFFECTED TAX PARCELS: SEE SHEET 2

CENTER POINT QUAD

BRIDGISH TO TA

	PROPOSED TOPSOIL STOCKPILE 3
PROPOSED COMPLETION PIT PROPOSED SPOIL STOCKPILE 2 PROPOSED TOPSOIL STOCKPILE 2 PROPOSED SPOIL STOCKPILE 3	PROPOSED FLOWBACK PIT PROPOSED SPOIL STOCKPILE 1 PROPOSED TOPSOIL STOCKPILE 1
PROPOSED TOPSOIL STOCKPILE 4	PROPOSED TOPSOIL STOCKPILE TO PROPOSED MAIN ACCESS ROAD 2.5
McFirmy SCALE	NTS

	WELL HEAD LAYOUT			
WELL	WV STATE PL	WV STATE PLANE NAD 83 (FT)		DEGREES)
HEAD	NORTHING	EASTING	LATITUDE (N)	LONGITUDE (W)
H1-513513	334850.57	1640597.50	39,413529° N	80.660625° W
H2-513514	334850.57	1640612.50	39.413530° N	80.660572° W
H3-513515	334850.57	1640627.50	39.413530° N	80.660519° W
H4-513516	334850.57	1640642.50	39.413531° N	80,660466° W
H5-513517	334850.57	1640657.50	39.413531° N	80.660413° W
H6-513518	334850.57	1640672.50	39.413532° N	80.660359° W
H7-514143	334850,57	1640687.50	39,413532° N	80.660306° W
H8-514144	334850.57	1640702.50	39.413533° N	80.660253° W

PLAN REPRODUCTION WARNING

FOR REDUCTIONS, REFER TO GRAPHIC SCALE

GRAY SCALE PLOTTING

THE PLANS HAVE BEEN CREATED ON ANSI D (22" x 34") SHEETS.

THE PLANS HAVE BEEN CREATED FOR FULL COLOR PLOTTING

ANY SET OF THE PLANS THAT IS NOT PLOTTED IN FULL COLOR SHALL NOT BE CONSIDERED ADEQUATE FOR CONSTRUCTION

WARNING: INFORMATION MAY BE LOST IN COPYING AND/OR

		WELL HEAD LAY	YOUT	
WELL	WV STATE PL	ANE NAD 27 (FT)	UTM ZONE 1	7N NAD 83 (M)
HEAD	NORTHING	EASTING	NORTHING	EASTING
H1-513513	334814.30	1672038.29	4362723.13	529215.29
H2-513514	334814.30	1672053.29	4362723.15	529219.86
H3-513515	334814.30	1672068.29	4362723.17	529224.43
H4-513516	334814.30	1672083.29	4362723.18	529229.00
H5-513517	334814.30	1672098.29	4362723.20	529233.57
H6-513518	334814.30	1672113.29	4362723.22	529238.14
H7-514143	334814.30	1672128.29	4362723.46	529242.71
H8-514144	334814.30	1672143.29	4362723.47	529247.28

	SHEET INDEX
PAGE NO.	DESCRIPTION
1	COVER PAGE & LOCATION MAP
2	SCHEDULE OF QUANTITIES
3	NOTES
4	EXISTING CONDITIONS
5	OVERALL PLAN
6-8	SITE PLAN
9	WELL PAD CROSS SECTIONS AND PROFILE
10	FLOWBACK PIT CROSS SECTIONS AND PROFILE
11-12	COMPLETION PIT CROSS SECTIONS AND PROFILE
13-15	MAIN ACCESS ROAD CROSS SECTIONS AND PROFILE
16	CULVERT PROFILES
17-22	DETAILS
23-25	RECLAMATION PLAN




230 Executive Drive, Suite 122 Cranbarry Township, PA 16066 Phone: 724-772-7072 www.kleinfelder.com



Signed By: JOSHUA M. FARLEY, W.V. P.E. # 20711

	REVISIONS			
REV	DESCRIPTION	DSN	снк	DATE
REV	DESCRIPTION	DWN	APP	DATE
\perp				
			ш	
		\perp		
			Ш	
		-		

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION



SCALE IN FEET ORIGINAL DRAWING SIZE IS 22 x 34

COVER PAGE & LOCATION MAP

CPT-10 WELL PAD **DODDRIDGE COUNTY**



PERMITTING

	LICIVII	111110
PROJECT NO.	137355	
ISSUE DATE	07/01/2015	
CURRENT REVIS	ION -]
DESIGNED BY	AER	
DRAWN BY	AER	
CHECKED BY	JMF	
APPROVED BY	JMF	SHEET

WELL LOCATION RESTRICTIONS

WELL PAD IS TO COMPLY WITH WELL LOCATION RESTRICTIONS OF WV CODE 22-6A-12. THE PADS COMPLY WITH THE FOLLOWING RESTRICTIONS:

250' FROM AN EXISTING WELL OR DEVELOPED SPRING USED FOR HUMAN OR DOMESTIC ANIMALS TO WELL BEING DRILLED

625' FROM AN OCCUPIED DWELLING OR BARN GREATER THAN 2500 SF USED FOR POULTRY OR DAIRY MEASURED FROM THE CENTER OF

100' FROM EDGE OF DISTURBANCE TO WETLANDS, PERENNIAL STREAMS, NATURAL OR ARTIFICIAL LAKE, POND OR RESERVOIR

300' FROM EDGE OF DISTURBANCE TO NATURALLY REPRODUCING TROUT STREAMS

1000' FROM EDGE OF DISTURBANCE TO ANY SURFACE OR GROUND WATER INTAKE TO A PUBLIC WATER SUPPLY

	SCHEDULE OF QUANTITIES CPT-10 WELL PAD		
	ITEM DESCRIPTION	QUANTITY	UNIT
.1 - MOBILIZATION	TEM DESORAL FIOR	1	LS
.1 - CLEARING			
	A - CLEAR & GRUB (TREES, STUMPS, BRUSH)	41	AC
	.B - CLEAR FELLED TIMBER & GRUB	31	AC
3.1 - EROSION & SEDI	MENT CONTROL		
3.1	A - 12" COMPOST FILTER SOCK	1,005	LF
3.1.	.B - 18" COMPOST FILTER SOCK	1,205	LF
3.1.	.C - 24" COMPOST FILTER SOCK	575	LF
	D - 32" COMPOST FILTER SOCK	615	ŁF
	D - SUPER SILT FENCE	3,780	LF
	E - ROCK CONSTRUCTION ENTRANCE	1	EA
	F - R-3 RIP RAP (ROCK FILTER OUTLETS)	10	TONS
	.G - AASHTO #57 STONE (ROCK FILTER OUTLETS)	5	TONS
	H - R-3 RIP RAP (ROCK CHECK DAMS)	27	TONS
	L -EROSION CONTROL MATTING - NAG C125BN	30,781	SY
	L -EROSION CONTROL MATTING -NAG C350	30,875	SY
.1 - DITCH LINING	A - NORTH AMERICAN GREEN C125BN	1,589	SY
_	A - R-3	1,787	SY
	A-R-3	676	SY
.1 - AGGREGATE SUF		, 5,5	
	A.1 - WELL PAD #3 - #6 LIMESTONE (8" THICK)	6,485	TONS
	A.2 - WELL PAD 0.75" OR 1.5" CRUSHER RUN LIMESTON (2" THICK)	2,671	TONS
	A.3 - WELL PAD GEOTEXTILE FABRIC (US 200)	25,431	SY
	B.1 - ACCESS ROADS #3 - #6 LIMESTONE (8" THICK)	5,424	TONS
5.1.	B.2 - ACCESS ROADS 0.75" OR 1.5" CRUSHER RUN LIMESTON (2" THICK)	2,234	TONS
5.1.	8.3 - ACCESS ROADS GEOTEXTILE FABRIC (US 200)	21,269	SY
5.1.	.C.1 - TRUCK QUEUES #3 - #6 LIMESTONE (8" THICK)	627	TONS
5.1.	.C.2 - TRUCK QUEUES 0.75" OR 1.5" CRUSHER RUN LIMESTON (2" THICK)	259	TONS
5.1.	.C.3 - TRUCK QUEUES GEOTEXTILE FABRIC (US 200)	2,458	SY
3.1 - SEED & MULCH			
_	A - SITE SEEDING (LIME, FERTILIZER, SEEDING, AND HYDRO-MULCH w/TACK (HYC-2 OR EQUAL))	30.2	AC
	B - RECLAMATION SEEDING (LIME, FERTILIZER, SEEDING, AND HYDRO-MULCH w/TACK (HYC-2 OR EQUAL))	1.9	AC
.1 - EXCAVATION		1 1	
	A - TOPSOIL (ESTIMATED AT 1' DEEP)	30,402	CY
	.B -WELL PAD EXCAVATION (CUT TO FILL)	32,642	CY
	.CWELL PAD EXCAVATION (EXPORT TO SPOIL AREA)	41,490	CY
. —	D - COMPLETION PIT & TRUCK QUEUE EXCAVATION (CUT TO FILL)	67,537 18,337	CY
_	E - COMPLETION PIT & TRUCK QUEUE EXCAVATION (IMPORT FROM SPOIL AREA)	1,023	CY
_	.F - FLOWBACK PIT & TRUCK QUEUE EXCAVATION (CUT TO FILL) .G - FLOWBACK PIT & TRUCK QUEUE EXCAVATION (EXPORT TO SPOIL AREA)	35,779	CY
	H - ACCESS ROADS EXCAVATION (CUT TO FILL)	17,240	CY
_	.1 - ACCESS ROADS EXCAVATION (GOT TO THE)	2,742	CY
.1 - PAD	· · · · · · · · · · · · · · · · · · ·	,	
	A - CONTAINMENT BERM	7,050	CY
_	B - SUMPS - (SEE "SUMP SYSTEM DETAIL")	8	EA
	.C - 4" PVC SUMP DRAIN PIPE - (SEE "SUMP SYSTEM DETAIL")	100	LF
	D - PVC PIPE OUTLET PROTECTION - R-3 RIP RAP	88	TONS
.1 - CROSS DRAIN CL	JLVERTS		
	A - 18" HDPE	370	ĻF
9.1	.B - FLARED END SECTION	5	EΑ
9.1	.C - R-3 RIP RAP (INLETS/OUTLETS)	20	TONS
	E - R-4 RIP RAP (INLETS/OUTLETS)	41	TONS
	.G - R-6 RIP RAP (INLETS/OUTLETS)	51	TONS
	.D - AASHTO #57 STONE (INLETS)	91	TONS
0.1 - PIT		, ,	
	1.A - PRIMARY LINER (60 MIL)	9,122	SY
	1.B - NON-WOVEN GEOTEXTILE FABRIC CUSHION (160Z FELT)	9,122	SY
1.1 FRENCH DRAIN			
	11.1.A - 4" PERFORATED PIPE 11.1.B - GEOTEXTILE FABRIC	1,248 7,488	LF SY

LIMITS OF DISTURBANCE				
DESCRIPTION	AREA	AFFECTED TAX		
DESCRIPTION	(ACRES)	PARCELS		
COMPLETION PIT	2.14	COASTAL FOREST RESOURCES		
MAIN ACCESS ROAD	7.75			
WELL PAD	7.47			
FLOWBACK PIT & TURN AROUND	2.31			
COMPLETION PIT & TURN AROUND	4.51			
SPOIL STOCKPILE 1	3.84			
SPOIL STOCKPILE 2	2.67	HAYES SHIRLEY		
SPOIL STOCKPILE 3	0.22	JAMES & MA		
SPOIL STOCKPILE 4	0.11			
TOPSOIL STOCKPILE 1	3.51			
TOPSOIL STOCKPILE 2	1.56			
TOPSOIL STOCKPILE 3	0.71			
COMPLETION PIT	3.66	ASH SAMUEL G ET UX		
TOTAL	40.46			
TOTAL WOODED ACRES DISTURBED	30.88			
TOTAL LINEAR FOOTAGE OF MAIN	2400			
ACCESS ROAD	3,100			
TOTAL LINEAR FOOTAGE OF WELL PAD	24			
ACCESS ROAD	24			

GRADING	
CUT SLOPE	2:1 *
FILL SLOPE	2:1 *
SPOIL SWELL FACTOR	20%
WELL PAD ELEVATION	969'
FLOWBACK PIT BERM ELEVATION	1099'
COMPLETION PIT BERM ELEVATION	1179'
*UNLESS OTHERWISE NOTE!)

PAD/ROAD CUT/ FILL SLOPES	Z:1
EQUIPMENT PAD & ACCESS ROADS	2
COMPLETION & FLOWBACK PIT INTERIOR SLOPES	3
COMPLETION & FLOWBACK PIT EXTERIOR SLOPES	2
SPOIL STOCKPILES	2
TOPSOIL STOCKPILES	3

COMPLETION PIT VOLUMES							
Elevation	Barrels	Gallons	Acre-Ft	Unincised Acre-Ft	Incised Acre-Ft		
1160 (Bottom)	0	0	0.000	0.000	0.000		
1161	3,136	131,717	0.404	0.000	0.404		
1162	6,769	284,290	0.872	0.000	0.872		
1163	10,910	458,230	1.406	0.000	1.406		
1164	15,573	654,048	2.007	0.000	2.007		
1165	20,768	872,251	2.677	0.000	2.677		
1166	26,508	1,113,352	3.417	0.000	3.417		
1167	32,806	1,377,863	4.229	0.000	4.229		
1168	39,674	1,666,293	5.114	0.000	5.114		
1169	47,123	1,979,151	6.074	0.000	6.074		
1170	55,165	2,316,949	7.110	1.037	6.074		
1171	63,814	2,680,199	8.225	2.151	6.074		
1172	73,081	3,069,411	9.420	3.346	6.074		
1173	82,978	3,485,092	10.695	4.622	6.074		
1174	93,518	3,927,759	12.054	5.980	6.074		
1175	104,712	4,397,921	13.497	7.423	6.074		
1176	116,573	4,896,086	15.026	8.952	6.074		
1177 (Pit Capacity)	129,114	5,422,767	16.642	10.568	6.074		
1178	142,345	5,978,473	18.347	12.273	6.074		
1179 (Top Berm)	156,279		20.143	14.069	6.074		
* 1 Barrel [US Petroleum] = 42 gallons [US liquid]							

FLOWBACK PIT VOLUMES

Elevation

1081 (Bottom)

1082

1083

1084

1085

1086 1087

1088

1089

1090

1091

1092 1093 1094

1095

1098

Barrels Gallons Acre-Ft Unincised Incised Acre-Ft Acre-Ft

0.419

8,419 269,579 0.827 0.000 0.827 8,339 350,219 1.075 0.000 1.075 10,501 441,036 1.353 0.000 1.353

18,571 779,968 2.394 0.000 2.394 21,831 916,917 2.814 0.000 2.814 25,399 1,066,756 3.274 0.000 3.274

3.775

4,907

5.542

48,293 2,028,302 6.225 1.317 4.907

903 37,908 0.116 1,983 83,277 0.256

3,254 136,650 0.419 4,728 198,570 0.609

12,918 542,573 1.665 15,604 655,368 2.011

33,506 1,407,273 4.319

* 1 Barrel [US Petroleum] = 42 gallons [US liquid]

29,286 1,230,026

1096 38,072 1,599,040 1097 (Pit Capacity) 42,997 1,805,869

1099 (Top Berm) 53,973 2,266,882 6.957

0.000 0.000 0.000

0.000

0.000

0.000

0.000

0.000

0.635

0.000 0.256

0.000 0.419

0.000 1.665

0.000 4.319

2.050 4.907

0.116

0.609

2.011

3.775

4.907

4.907

	QUANTITIES								
DESCRIPTION	CUT (CY)	FILL (CY)	BASE (CY)	TOPSOIL (CY)	SPOIL (CY)	BORROW (CY)	MAX. SLOPE	LENGTH OF SLOPE	
WELL PAD	74132	32642	4021	8477	37034	N/A	N/A	N/A	
FLOWBACK PIT	36802	1023	716	2819	33675	NA	N/A	N/A	
COMPLETION PIT	67537	85874	1429	6949	N/A	23858	N/A	N/A	
PRIMARY ACCESS ROAD	13410	19982	1906	7079	N/A	11745	16.99%	1520'	
WELL PAD ACCESS ROAD	3870	0	15	11	3874	N/A	N/A	N/A	
TOPSOIL STOCKPILE 1	0	21689	0	0	N/A	21689	N/A	N/A	
TOPSOIL STOCKPILE 2	0	2926	0	0	N/A	2926	N/A	N/A	
TOPSOIL STOCKPILE 3	0	1103	0	0	N/A	1103	N/A	N/A	
SPOIL STOCKPILE 1	0	31093	0	0	N/A	31093	N/A	N/A	
SPOIL STOCKPILE 2	0	1738	0	0	N/A	1738	N/A	NA	
SPOIL STOCKPILE 3*	0	3570	0	0	N/A	3570	N/A	NA	
SPOIL STOCKPILE 4*	0	1560	0	0	N/A	1560	N/A	N/A	
TOTALS	196751	203200	8087	25335	74584	99281	N/A	N/A	
	AL EXPOR	T (CY)	637	,					

"SPOIL STOCKPILES 3 & 4 WILL BE BUILT PRIOR TO CONSTRUCTION OF TOPSOIL STOCKPILE 1. CONSTRUCTION SEQUENCING MUST BE EVALUATED

WEST VIRGINIA 811 UTILITY RESPONSE STATUS
TICKET #1421253047 THRU SEPTEMBER 4, 2014

ı	Utility Code	Utility Owner	Utility Contact/Responder Information			Utility	Utility Type	Utility Specifications	Notes
1	Utility Code		Name	Number	E-Mail	Response	Othity type	(diameter, pole number(s), etc.)	
	AC	Frontier Communications (Formerly Verizon)			•	Clear	Phone		
1	CGS	Columbia Gas Transmission - Clarksburg		1-800-835-7191	irthnetapp@nisource.com	Clear	Gas		
	EQW560	EQT Gathering	•	•	-	No Response	Gas	•	-
	MPC	Firstenergy Corp		-		Clear	Electric		-



230 Executive Drive, Suite 122 Cranberry Township, PA 16066 Phone: 724-772-7072 www.kleinfelder.com



Signed By: JOSHUA M. FARLEY, W.V. P.E. # 20711

	REVISION	S		
	T. T	DSN	СНК	
REV	DESCRIPTION	DWN		DATE
	REVISED SCHEDULE OF	MDV		
1	QUANTITIES (11.1.C)	MDV	JMF	7/21/2015
				1
		\perp		1
		-		
			-	
			_	
		\vdash	\vdash	-
			_	
		-		1
				<u> </u>
				1

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

1 INCH

ADJUST SCALE ACCORDINGLY IF DISTANCE PLOTS DIFFERENTLY

ORIGINAL DRAWING SIZE IS 22 x 34

SCHEDULE OF QUANTITIES

CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA



Where energy meets innovation.

PERMITTING

PROJECT NO.	. 1	37355	
ISSUE DATE	07/0	1/2015	
CURRENT REVIS	ION	-	
DESIGNED BY		AER	
DRAWN BY		AER	
CHECKED BY		JMF .	
APPROVED BY		JMF	s

2 of 25

GENERAL NOTES

- EQT PRODUCTION COMPANY WILL OBTAIN AN ENCROACHMENT PERMIT (FORM MM-109) FROM THE WEST VIRGINIA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS, PRIOR TO COMMENCEMENT OF CONSTRUCTION ACTIVITIES.
- ANY DISCREPANCIES FOUND BETWEEN THE DRAWINGS AND SPECIFICATIONS AND SITE CONDITIONS OR ANY INCONSISTENCIES OR AMBIGUITIES IN DRAWINGS OR SPECIFICATIONS SHALL BE IMMEDIATELY REPORTED TO THE ENGINEER, IN WRITING, WHO SHALL PROMPLY A DODRESS SUCH PROBLEMS, WORK DONE BY THE CONTRACTOR AFTER THE DISCOVERY OF SUCH DISCREPANCIES, INCONSISTENCIES, OR AMBIGUITIES SHALL BE DONE AT THE CONTRACTOR'S RISK.
- WORK ON THIS PROJECT SHALL CONFORM TO THE LATEST EDITIONS OF THE WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION (WYDOP) PROSION AND SEDIMENT CONTROL BEST MANAGEMENT PRACTICE HANDBOOK. IN THE EVENT OF CONFLICT BETWEEN THE DESIGN, SPECIFICATIONS, OR PLANS, THE MOST STRINGENT WILL GOVERN.
- THE CONTRACTOR IS RESPONSIBLE FOR LOCATING ALL PUBLIC OR PRIVATE UTILITIES WHICH LIE IN OR ADJACENT TO THE CONSTRUCTION SITE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE REPAIR, AT HIS OR HER EXPENSE, OF ALL EXISTING UTILITIES DAMAGED DURING CONSTRUCTION. FORTY-EIGHT HOURS PRIOR TO ANY EXCAVATION THE CONTRACTOR SHALL CALL MISS UTILITY AT
- INSTALLATION OF STORM PIPE SHALL BE IN CONFORMANCE WITH THESE DRAWINGS.
- ALL MATERIALS USED FOR FILL OR BACK FILL SHALL BE FREE OF WOOD, ROOTS, ROCKS, BOULDERS OR ANY OTHER NON-COMPACTABLE SOIL TYPE MATERIALS, UNSATISFACTORY MATERIALS ALSO INCLUDE MAN MADE FILLS AND REFUSE DEBRIS DERIVED FROM ANY SOURCE.
- MATERIALS USED TO FILL AROUND DRAINAGE STRUCTURES IN UTILITY TRENCHES OR ANY OTHER DEPRESSION REQUIRING FILL OR BACK FILL SHALL BE COMPACTED TO 95% OF MAXIMUM DENSITY AS DETERMINED BY THE STANDARD PROCTOR TEST AS SET FORTH IN ASTM STANDARD D-98. THE MOISTURE CONTENT WILL BE CONTROLLED IN ACCORDANCE WITH THE LIMITS OF THE STANDARD PROCTOR AT PLUS OR MINUS 4% MOISTURE CONTENT. THE CONTRACTOR SHALL PRIOR TO ANY OPERATIONS INVOLVING FILLING OR BACK FILLING, SUBMITTHE RESULTS OF THE PROCIECT REST TO EST TOGETHER WITH A CERTIFICATION THAT THE SOIL TESTED IS RESENSATATIVE OF THE MATERIALS TO BE USED ON THE PROJECT. THE TESTS SHALL BE CONDUCTED BY A CERTIFICATION SMODE BY A LICENSED PROFESSIONAL ENGINEER PREFESSINITIES THE LABORATORY AND THE CERTIFICATIONS MADE BY A LICENSED PROFESSIONAL ENGINEER REPRESENTING THE LABORATORY. THE CONTRACTOR IS RESPONSIBLE FOR ALL COSTS ASSOCIATED WITH THESE TESTS AND THEIR SUBMITTALS.
- FILL SHALL BE PLACED IN LIFTS AT A MAXIMUM UNCOMPACTED DEPTH OF 12" WITH SOIL FREE FROM AGGREGATES EXCEEDING 6".
- ALL TEST RESULTS SHALL BE SUBMITTED TO THE ENGINEER. FAILURE TO CONDUCT DENSITY TESTS SHALL BE CAUSE FOR NON-ACCEPTANCE OF THE FACILITY. TESTS SHALL BE CONDUCTED AT THE SOLE COST OF THE CONTRACTOR OR HIS AGENT.
- 0. A PRE-CONSTRUCTION CONFERENCE SHALL BE HELD PRIOR TO THE START OF CONSTRUCTION.
- 1 SATISFACTORY MATERIALS FOR USE AS FILL FOR PAD AREAS INCLUDE MATERIALS CLASSIFIED IN ASTM D-2487 AS GW. GP. GM. GC. SW. SALISH CART MERCULE FOR MISSESSIFIED IN AS IN MISSESSIFIED IN AS IN AS THE OPTIMUM TO FACILITATE COMPACTION. GENERALLY, UNSATINE OF MATCH SHALL BE MATERIALS INCLUDE MATERIALS CLASSIFIED IN AST MO-249 A 5 TY, CH, MH. OL, CH AND ANY SOIL TOO WET TO FACILITATE COMPACTION. CH AND MH SOILS MAY BE USED SUBJECT TO APPROVA OF THE NEER. SOILS SHALL HAVE A MINIMUM DRY DENSITY OF 92 LB/CF PER ASTM D-698 AND SHALL HAVE A PLASTICITY INDEX LESS THAN
- 2. CONTRACTOR SHALL DEVELOP A GENERIC GROUNDWATER PROTECTION PLAN (GPP), SUBMITTAL TO WYDEP IS NOT REQUIRED. THE
- 3 NO ROCK FILL LIETS SHALL BE GREATER THAN 36"

EROSION & SEDIMENT CONTROL NARRATIVE

- PROJECT DESCRIPTION: THE PURPOSE OF THIS PROJECT IS TO GRADE AND INSTALL EROSION AND SEDIMENT CONTROL MEASURES, IN PREPARATION FOR THE CONSTRUCTION OF A NATURAL GAS WELL PAD COUNTY ROUTE 4, IN DODDRIDGE COUNTY, WEST VIRIGINIA. THE CONSTRUCTION INCLUDES TWO ACCESS ROADS, ONE WELL PAD, ONE FLOWBACK PIT, ONE COMPLETION PIT, STORM WATER
- EXISTING SITE CONDITIONS: THE EXISTING SITE IS PREDOMINATELY WOODS, NO EROSION IS NOTICED ON SITE, OR IN ANY NATURAL
- ADJACENT PROPERTY: THE SITE IS BORDERED BY WOODS.
- I. SOILS: NO SOIL STUDIES OR SUBSURFACE INVESTIGATIONS WERE PERFORMED FOR THIS PROJECT
- 5. OFF SITE AREAS: THERE SHALL BE NO BORROW AREA OUTSIDE OF THE PROPOSED GRADING AND CONSTRUCTION AREA
- CLEARING OF VEGETATION SHOULD BE KEPT TO THE MINIMUM NECESSARY FOR CONSTRUCTION PLUS THE INSTALLATION OF SEDIMENT CONTROLS.
- CRITICAL EROSION AREAS MAINTENANCE: ALL 3:1 SLOPES AND SYEEPER, DITCHES AND OTHER CONTROLS SHALL BE CONSIDERED CRITICAL EROSION AREAS. THESE AREAS SHALL BE MONITORED & MAINTAINED DAILY AND AFTER EACH RAIN FALL OF 0.5 INCH OR GREATER. THE LOCAL GOVERNING AUTHORITY WILL WAYE THE AUTHORITY TO RECOMMEND THE PLACEMENT OF ADDITIONAL EROSION CONTROL MEASURES IN THESE AREAS IF IT BECOMES EVIDENT DURING CONSTRUCTION THAT THE ONES IN PLACE ARE NOT
- EROSION AND SEDIMENT CONTROL MEASURES: UNLESS OTHERWISE INDICATED, ALL VEGETATIVE AND STRUCTURAL EROSION AND SEDIMENT CONTROL PRACTICES SHALL BE CONSTRUCTED AND MAINTAINED ACCORDING TO MINIMUM STANDARDS AND SPECIFICATIONS OF THE CURRENT WEST VIRGINIA EROSION AND SEDIMENT CONTROL BEST MANAGEMENT PRACTICE MANUAL. THE CONTRACTOR SHALL OBTAIN A COPY OF THIS MANUAL FROM THE WYDEP WEBSITE AND CONSTRUCT ALL DEVICES BASED ON THIS MANUAL OR A HANDBOOK THAT IS COMPARABLE OR EXCEEDS THE SPECIFICATIONS OF THE WEST VIRGINIA MANUAL. THE MINIMUM STANDARDS OF THIS MANUAL SHALL BE ADHERED TO UNLESS OTHERWISE WAIVED OR APPROVED BY A VARIANCE, SEE PLANS FOR ALL PROPOSED EROSION AND SEDIMENT CONTROL MEASURES.

- STRUCTURAL PRACTICES:

 DIVERSION DITCHES: WILL BE CONSTRUCTED AS SHOWN ON THE PLANS.

 OUTLET PROTECTION: WILL BE CONSTRUCTED AS SHOWN ON THE PLANS.

 FILTER SOCK/SUPER SILT FENCE: WILL BE CONSTRUCTED AS SHOWN ON THE PLANS.
- VEGETATIVE PRACTICE TOPSOILING: TOPSOIL WILL BE STRIPPED FROM THE SITE AND STOCKPILED AS SHOWN ON THE PLANS. UPON THE COMPLETION OF THE PROJECT, TOPSOIL WILL BE PLACED ON ALL DISTURBED AREAS AT A MINIMUM DEPTH OF 4 INCHES. TEMPORARY SEEDING: ALL DENUDED AREAS LEFT DORMANT FOR MORE THAN 21 DAYS SHALL BE SEEDED WITH A FAST GERMINATING SEED. THE TIME OF YEAR WILL BE TESSED SHESSED OF SEED MIXTURE. PERMANENT SEEDING: ALL SEEDED AREAS WILL BE RESEDED. MULCHED AND FERTILIZED AS NEEDED TO OBTAIN AN ADEQUATE STAND OF GRASS. PERMANENT SEEDING SHALL BE PLACED WITHIN SEVEN DAYS UPON ACHIEVING FINAL GRADE. WATER, MULCH, AND RESEED AS NECESSARY TO OBTAIN AN ADEQUATE STAND OF VEGETATION.
- MANAGEMENT STRATEGIES: CONSTRUCTION WILL BE SEQUENCED SO THAT GRADING OPERATIONS WILL BEGIN AND END AS SOON AS POSSIBLE. THE JOB SUPERINTENDENT SHALL BE RESPONSIBLE FOR THE INSTALLATION AND MAINTENANCE OF ALL EROSION AND SEDIMENT CONTROL MEASURES. AFTER ACHIEVING ADEQUATE STABILIZATION THE TEMPORARY EROSION AND SEDIMENT CONTROLS SHALL BE REMOVED AND ANY AREAS DISTURBED DURING THIS PROCESS SHALL BE STABILIZED.
- PERMANENT STABILIZATION: ALL AREAS LEFT UNCOVERED BY EITHER BUILDINGS OR PAVEMENT SHALL BE STABILIZED WITH PERMANENT SEEDING IMMEDIATELY FOLLOWING FINISH GRADING AND WITHIN 7 DAYS. AT NO TIME SHALL LAND LAY DORMANT FOR LONGER THAN 21 DAYS.
- S. MAINTENANCE AND OTHER CONSIDERATIONS AND GROUND WATER PROTECTION: ALL EROSION AND SEDIMENT CONTROL MEASURES WILL BE CHECKED DAILY AND AFTER EACH RAINFALL OF 0.5 INCH OR MORE. THEY WILL BE INSPECTED FOR UNDERMINING, DETERIORATION, EROSION AND EXCESS DEPOSITED MATERIAL. ALL DEFICIENCIES WILL BE CORRECTED IMMEDIATELY, EXCESS MATERIAL WILL BE SCHEAD ON THE SITE IN A MANNER WHERE IT IS, NOT LIKELY TO ERODE IN THE FUTURE. CLEANING PROCEDURES WILL BE COMPLETED AT REGULAR INTERVALS AND AT LEAST WHEN SEDIMENT REACHES 33% OF CAPACITY, OR AS SHOWN ON APPLICABLE OFTAILS, RECORDS OF CLEANING AND CORRECTIONS WILL BE MAINTAINED BY THE GOTRACTOR. THE "GENERIC GROUNDWATER PROTECTION PLAN FOR CONSTRUCTION SITES" (GPP) WILL BE USED AND AVAILABLE ON SITE AT ALL TIMES, AN ARE WILL BE PROVIDED FOR VEHICLE AND COURMENT MAINTENANCE, MOBILE FUEL TRUCKS WITH APPROVED TANKS WILL BE USED ON THE SITE. PORTABLE SANITARY FACILITIES WILL BE AVAILABLE FOR EMPLOYEES, IF CONCRETE IS USED, EXCESS CONCRETE WILL BE USED ON THE SITE. PORTABLE SANITARY FACILITIES WILL BE AVAILABLE FOR EMPLOYEES, IF CONCRETE IS USED, EXCESS CONCRETE WILL BE USED ON THE SITE. MOST OF PROPERTY AND NOT ALLOWED TO REMAIN ON THIS SITE. MACHINERY WILL NOT BLUCKED WILL BE CLEANED AND TAKEN OFF SITE TO A PROPER FACILITY. SOLID OR HAZARDOUS WASTES WILL BE USED. BE WILL BE CLEANED AND TAKEN OFF SITE TO A PROPER FACILITY. SOLID OR HAZARDOUS WASTES WILL BE USED. SED IN ACCORDANCE WITH APPROPRIATE STATE AND FEDERAL REACILITY. SOLID OR HAZARDOUS WASTES WILL BE DISPOSED IN ACCORDANCE WITH APPROPRIATE STATE AND FEDERAL REACILITY. SOLID OR HAZARDOUS WASTES WILL BE DESPOSED IN ACCORDANCE WITH APPROPRIATE STATE AND FEDERAL REACILITY. SOLID OR HAZARDOUS WASTES WILL BE DESPOSED IN ACCORDANCE WITH APPROPRIATE STATE AND FEDERAL REACILITY. SOLID OR HAZARDOUS WASTES WILL BE DISPOSED IN ACCORDANCE WITH APPROPRIATE STATE AND FEDERAL REACILITY. SOLID OR HAZARDOUS WASTES WILL BE DESPOSED IN ACCORDANCE WITH APPROPRIATE STATE AND FEDERAL REACILITY. SOLID OR HAZARDOUS WASTES WILL BE DESPOSED IN A

GENERAL EROSION & SEDIMENT CONTROL NOTES

- THE CONTRACTOR SHALL ARRANGE FOR A PRE-CONSTRUCTION CONFERENCE WITH THE APPROPRIATE EROSION AND SEDIMENT CONTROL INSPECTOR 48 HOURS PRIOR TO BEGINNING WORK.
- ALL EROSION CONTROL DEVICES AS SHOWN OR AS REQUIRED, ARE TO BE CONSTRUCTED TO THE CURRENT STANDARDS AND SPECIFICATIONS OF THE WEST VIRGINIA EROSION AND SECIMENT CONTROL BEST MANAGEMENT PRACTICE MANUAL AND ARE TO BE IN PLACE PRIOR TO ALL CONSTRUCTION.
- EROSION AND SEDIMENT CONTROL MEASURES SHALL BE MAINTAINED CONTINUOUSLY, RELOCATED WHEN AND AS NECESSARY AND SHALL BE CHECKED AFTER EVERY RAINFALL. SEEDED AREAS SHALL BE CHECKED REGULARLY AND SHALL BE WATERED, FERTILIZED, RESEEDED AND MULCHED AS NECESSARY TO OBTAIN A DENSE STAND OF GRASS.
- DRAIN INLETS SHALL BE PROTECTED FROM SILTATION, INEFFECTIVE PROTECTION DEVICES SHALL BE IMMEDIATELY REPLACED AND
- PERMANENT OR TEMPORARY SOIL STABILIZATION SHALL BE APPLIED TO DENUDED AREAS WITHIN SEVEN DAYS AFTER FINAL GRADE IS REACHED ON ANY PORTION OF THE SITE. TEMPORARY SOIL STABILIZATION SHALL BE APPLIED WITHIN EVEN DAYS TO DENUDED AREAS THAT MAY NOT BE AT FINAL GRADE BUT WILL REMAIN DORMANT (UNDISTURBED) FOR LONGER THAN 21 DAYS, PERMANENT, STABILIZATION SHALL BE APPLIED TO AREAS THAT ARE TO BE LEFT DORMANT FOR MORE THAN ONE YEAR.
- 6. DURING CONSTRUCTION OF THE PROJECT. SOIL STOCKPILES SHALL BE STABILIZED OR PROTECTED WITH SEDIMENT TRAPPING
- SEDIMENT BASINS AND TRAPS. PERIMETER DIKES, SEDIMENT BARRIERS AND OTHER MEASURES INTENDED TO TRAP SEDIMENT SHALL E CONSTRUCTED AS A FIRST STEP IN ANY LAND DISTURBING ACTIVITY AND SHALL BE MADE FUNCTIONAL BEFORE UPSLOPE LAND
- 8. STABILIZATION MEASURES SHALL BE APPLIED TO EARTHEN STRUCTURES SUCH AS IMPOUNDMENTS, DIKES AND DIVERSIONS
- 9. ALL TEMPORARY EROSION AND SEDIMENT CONTROL MEASURES SHALL BE REMOVED WITHIN 30 DAYS AFTER THE TEMPORARY MEASURES ARE NO LONGER NEEDED, UNLESS OTHERWISE AUTHORIZED BY THE ENGINEER. TRAPPED SEDIMENT AND THE DISTURBED SOIL AREAS RESULTING FROM THE DISPOSITION OF TEMPORARY MEASURES SHALL BE PERMANENTLY STABILIZED TO PREVENT
- 10. NO SEDIMENT TRACKING ON THE ROADWAY IS ALLOWED. IN THE EVENT THAT SEDIMENT IS INADVERTENTLY TRACKED ONTO THE ROAD. THE ROAD SHALL BE CLEANED THOROUGHLY BY THE END OF EACH DAY, SEDIMENT SHALL BE REMOVED FROM ROADS BY SHOVELING OR PICKUP SWEEPING AND SHALL BE TRANSPORTED TO A CONTROLLED SEDIMENT DISPOSAL AREA, STREET WASHING OF SEDIMENTS TO THE STORM DRAIN SYSTEM IS NOT ALLOWED. IF STREET WASH WASTEWATER CAN BE CONTROLLED FROM ENTERING THE STORM NAGE SYSTEM. THEN IT SHALL BE PUMPED BACK ONTO THE SITE, CONTAINED AND DISPOSED OF PROPERLY
- 11. ALL DISTURBED AREAS NOT PAVED OR BUILT UPON SHALL BE HYDRO-SEEDED AND FERTILIZED, PERFORM PERMANENT TOP SOILING. SEEDING AND FERTILIZING AS SOON AFTER FINISH GRADING AS POSSIBLE. SEEDING SHALL COMPLY WITH THE FOLLOWIN
- TOPSOIL 4 INCH MINIMUM FOR PERMANENT TURE.
- FERTILIZER 500 LBS. PER ACRE OF 10-20-20 FERTILIZER OR EQUIVALENT POUNDAGE OF DIFFERENT ANALYSIS. WORK INTO SOIL
- . LIME (PERMANENT SEEDING) AGRICULTURAL LIME SPREAD AT RATE OF 4 TONS PER ACRE. WORK INTO SOIL PRIOR TO SEEDING.
- MULCH OR EROSION CONTROL BLANKET (ECB) WOOD FIBER OR CHOPPED STRAW AT RATE OF 2 TONS PER ACRE. HYDRO-MULCH AT RATE OF 30 BALES PER ACRE. ECB SHALL BE PER PLANS.
- SEED 45 LBS. PER ACRE TALL FESCUE AND 20 LBS. PER ACRE PERENNIAL RYE GRASS. TO BE SEEDED WITH HYDRO-SEEDER

SEQUENCE OF BMP INSTALLATION AND REMOVAL

CONSTRUCTION MUST BE IN ACCORDANCE WITH THE FOLLOWING SEQUENCE. THIS SEQUENCE IS DESIGNED TO MINIMIZE SOIL EROSION AND SEDIMENTATION. THE CONTRACTOR MAY DEVIATE SHORTLY FROM THE STAGING OF PERMANENT SITE IMPROVED. DEVIATION FROM THE RELATIVE ORDER OF EROSION AND SEDIMENTATION CONTROL MEASURES WILL BE ALLOWED.

THE STAGING OF EARTHMOVING ACTIVITIES FOR THIS PROJECT IS A GENERAL DESCRIPTION OF THE WORK REQUIRED. ALL WORK SHALL BE COMPLETED IN ACCORDANCE WITH COMPANY STANDARDS, THE WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION REGULATIONS AND ALL OTHER APPLICABLE FEDERAL, STATE OR LOCAL REQUIREMENTS.

THE APPROVED EROSION AND SEDIMENTATION CONTROL PLAN INCLUDING THE SOIL EROSION CONTROL DRAWINGS SHALL BE AVAILABLE ON SITE AT ALL TIMES DURING EARTH DISTURBANCE.

ALL BMPs SHALL BE INSPECTED AFTER EACH MEASURABLE RAINFALL RUNOFF EVENT. ANY NECESSARY REPAIRS MUST BE MADE IMMEDIATELY TO ENSURE EFFECTIVE AND EFFICIENT OPERATION.

- A PRE-CONSTRUCTION CONFERENCE WILL BE HELD ON SITE WITH CONTRACTOR TO REVIEW THE CONSTRUCTION DRAWINGS AND
- 2. STAKE/FLAG DISTURBED WORK AREA, CLEARLY IDENTIFYING WETLAND AND STREAM EDGES AND BUFFERS. INSTALL SIGNS TO DESIGNATE THE AREA AND ORANGE SAFETY FENCE TO IDENTIFY IMPORTANT PROJECT ATTRIBUTES SUCH AS APPROVED ACCESS ROADS, NO REFUELING ZONES, WETLAND/STREAM BOUNDS, ETC.
- 3 CONSTRUCT THE CONSTRUCTION ENTRANCE.
- 4. CONSTRUCT ALL PROPOSED SEDIMENT CONTROL DEVICES AS SOON AS CLEARING AND GRUBBING OPERATIONS ALLOW.
- 5. PRIOR TO GRADING OR OTHER EARTH DISTURBANCE ON THE PARCEL, PERMANENT DOWN SLOPE BMPs ARE TO BE INSTALLED.
- 6. CLEAR AND GRUB, REMOVE TOPSOIL AND PLACE AS SHOWN ON THE PLANS. TOPSOIL STOCKPILE TO BE SEEDED AND MULCHED. E&S BMPs SHALL BE CONSTRUCTED AROUND TOPSOIL STOCKPILES AS SHOWN.
- 7. GRADING OPERATIONS AS REQUIRED, CUT SLOPES AND ALL SLOPES SHALL BE TOPSOILED AS NEEDED. DITCH LINES SHALL BE CLEANED. ALL DITCHES WILL HAVE AT LEAST GRASS LINING PROTECTION OR AS SPECIFIED IN DETAIL ON SHEET 16.
- 8. THE ACCESS ROAD SHALL BE CONSTRUCTED UP TO THE PROPOSED PADS, THE ACCESS ROAD SHALL RECEIVE A STONE SURFACE.
- 9. INSTALL PROPOSED EQUIPMENT PAD AND EQUIPMENT PAD BERMS.
- 10. CULVERT INLET AND OUTLET PROTECTION SHALL BE CONSTRUCTED IMMEDIATELY UPON PLACEMENT OF INLETS AND CULVERTS. INSTALLATION OF MATTING AND/OR RIP RAP TO OCCUR ONCE DITCHES ARE CONSTRUCTED.
- 11. SIDE SLOPE STABILIZATION MATTING AND STABILIZATION SHALL OCCUR AS SOON AS POSSIBLE
- 12. AT THE END OF EACH WORK DAY, WHERE THE PARCEL HAS BEEN GRADED, INCLUDING ANY STRIPPING, STUMPING, LEVELING, 2:1 ON SIDE SLOPES, ETC. BMPs ARE TO BE INSTALLED. IN NO CASE IS THE CONTRACTOR TO LEAVE THE JOB SITE AT THE END OF THE WOR DAY WITHOUT TEMPORARY OR PERMANENT BMPS BEING INSTALLED. THE CONTRACTOR IS NOT REQUIRED TO MAINTAIN WATERBAR DURING THE WORK DAY UNLESS THE ENVIRONMENTAL INSPECTOR DETERMINES THAT THERE IS A RISK OF A RAIN EVENT THAT WARRANTS THEIR IMMEDIATE INSTALLATION.
- 13. WHEN FINAL GRADE IS ACHIEVED, TOPSOIL TO BE PLACED ON ALL DISTURBED AREAS NOT LINED. SEED ALL DISTURBED AREAS AS REQUIRED. A SOIL SAMPLE SHOULD BE TAKEN AND TESTED TO DETERMINE RECOMMENDED RATES. IF NO SOILS SAMPLE IS TAKEN T FOLLOWING RATES SHOULD BE APPLIED AS A MINIMUM: LIME AT A RATE OF 4 TONS PER ACRE, EFITILIZE AT A RATE OF 500 LBS. OF 10-20-0 PER ACRE. SEED WITH 45 LBS. PER ACRE OF TALL FESCUE AND 20 LBS. PER ACRE OF PERENNIAL RYE GRASS.
- LIME, FERTILIZER, AND SEED WILL BE APPLIED. HYDRO-MULCH PRODUCTS SHALL BE MIXED AND INSTALLED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS, OR EROSION CONTROL BLANKET SHALL BE INSTALLED PER PLANS & SPECIFICATIONS.
- 15. FINAL SEEDING MUST OCCUR WITHIN 7 DAYS OF FINAL GRADING.
- WHEN SITE IS STABILIZED, ALL EROSION AND SEDIMENT CONTROL MEASURES CAN BE REMOVED AND REPAIR/STABILIZE THOSE AREAS IN ACCORDANCE WITH STATE STANDARDS.
- 17. FINAL SITE INSPECTION, A NOTICE OF TERMINATION SHOULD BE FILED WITH DEP UPON FINAL STABILIZATION.

GENERAL CONSTRUCTION NOTES

- 1. THE WELL PAD AND FRESHWATER IMPOUDMENTS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE CONSTRUCTION DOCUMENTS. HE SCOPE OF WORK AND SHALL CONFORM GENERALLY WITH THE GRADES, BERMS, AND DIMENSIONS SHOW
- 2. THE CONSTRUCTION DOCUMENTS SHOW THE EXISTING AND PROPOSED GRADES AND BERMS, ETC. THAT ALL CUT AND FILL ESTIMATES ARE BASED UPON THE ENGINEER'S ESTIMATES OF THE QUANTITIES ARE ONLY ESTIMATES AND MAY CHANGE BASED ON ACTUAL FIELD
- 3. THE GRADES BERMS DEPTHS AND DIMENSIONS MAY CHANGE BASED ON ACTUAL FIFED CONDITIONS. THE ENGINEER RESERVES THE RIGHT TO CHANGE GRADES, BERMS, DEPTHS AND DIMENSIONS AS NECESSARY TO MEET FIELD CONDITIONS
- 4. THE CONTRACTOR SHALL PROVIDE THE ENGINEER ALL REASONABLE FACILITIES AND PROVIDE INFORMATION AND SAMPLES AS RED BY THE ENGINEER FOR PROPER MONITORING AND TESTING OF MATERIAL WORKMANSHIP
- THE CONTRACTOR SHALL HAVE ON SITE AT ALL TIMES WHEN CONSTRUCTION IS IN PROGRESS A COMPETENT SUPERINTENDENT THOROUGHLY FAMILIAR WITH THE CONSTRUCTION OF EARTH BERMS AND EMBANKMENTS, THE COMPACTION OF SOILS AND PLACEMENTS OF LINERS.
- 6. THE CONTRACTOR SHALL INSTALL FILTER SOCK AND SUPER SILT FENCE PRIOR TO CLEARING AND GRUBBING AS SHOWN ON THE DRAWINGS IN ACCORDANCE WITH WYDEP BEST MANAGEMENT PRACTICES MANUAL CHAPTER 3. SURFACE WATER SHALL BE DIVERTED AWAY FROM ALL EXCAVATIONS AND THE FACE OF ALL FILLS TO PREVENT FLOODING AND SOFTENING OF THE SUBGRADE OR
- 7. CLEARING AND GRUBBING SHALL REMOVE ALL BRUSH, TREES, ROOTS, STUMPS, FENCES, SIGNS OR ANY OTHER MATERIAL THAT IS NOT TO BE REUSED FOR THE CONSTRUCTION. SOME STUMPS MAY REMAIN AT THE APPROVAL OF THE ENGINEER, NO CLEARING DEBRIS SHALL BE BURIED ON-SITE. FOR CLEARING WITHIN PERMITTED LOD, STUMPS AND ROOTS LARGER THAN 2 INCHES IN DIAMETER SHALL BE COMPLETELY GRUBBED AND PROPERLY DISPOSED OF OFF-SITE. ALL TIMBER, TREETOPS, BRANCHES, STUMPS LESS THAN 2 INCHES IN DIAMETER, ETC., WILL BE CHIPPED, GROUND, AND/OR MULCHED AND USED AS SITE BMPS WITH THE REMAINDER BEING PROPERLY DISPOSED OF OFF-SITE. CLEARING TO BE COMPLETED ONLY AS NEEDED WITHIN THE LOD TO CONSTRUCT THE FACILITY AS DEPICTED.
- 8. TOP SOIL SHALL BE STRIPPED AND STOCKPILED WITH APPROPRIATE STABILIZATION TO PREVENT EROSION. THE TOP SOIL SHALL BE REUSED DURING THE RECLAMATION PROCESS AS NEEDED.
- PRIOR TO PLACING ANY FILL, THE EXPOSED SUBGRADE SHALL BE COMPACTED AND PROOF ROLLED TO PRODUCE A STABLE AND
- 10. RIPRAP USED AS OUTLET PROTECTION MUST BE HARD, ANGULAR AND OF A QUALITY RESISTANT TO WEATHERING AND DISINTEGRATION AP SHOULD BE GROUTED ON STEEP OR LENGTHY FILL SLOPES WITH A MINIMUM THICKNESS TWO TIMES THE MAXIMUM STONE DIAMETER, BUT NOT LESS THAN SIX INCHES.
- 11. ALL FILL SHALL BE PLACED IN LOOSE LIFTS OF UP TO 12" AND SHALL BE COMPACTED TO AT LEAST 95% OF THE LABORATORY MAXIMUM DRY DENSITY AS DETERMINED BY THE STANDARD PROCTOR TEST METHOD (ASTM D 698). THE MOISTURE CONTENT WILL BE CONTROLLED IN ACCORDANCE WITH THE LIMITS OF THE STANDARD PROCTOR TEST RESULTS. SOME SOILS CANNOT BE COMPACTED TO 95% OF THE STANDARD PROCTOR AT PLUS OR MINUS 4% MOISTURE CONTENT. CONTRACTOR IS RESPONSIBLE FOR THE CRIGINAL SOIL TEST AND PROVIDING A COPY OF THE RESULTS WITH MOISTUREDENSITY CURVE TO THE ENGINEER. THE CONTRACTOR SHALL DO IN-PLACE DENSITY TESTS EVERY THIRD LIFT OF SOIL, FIELD DENSITY TESTS FOR COMPACTION SHALL BE PERFORMED IN ACCORDANCE WITH ASTM D 2922 (NUCLEAR METHOD), RECORD SHALL BE MAINTAINED OF TEST LOCATION AND RESULTS AND PROVIDED TO THE ENGINEER ON REQUEST, AREAS THAT FAIL FOR COMPACTION SHALL BE REMOVED, RE-COMPACTED AND RETESTED FOR COMPLIANCE. IN LIEU OF STANDARD PROCTOR TESTING, THE CONTRACTOR MAY PROOF-ROLL THE SOIL EVERY 2"OF SOIL LIFT WITH A LOADED 15 TON TANDEM DUMP TRUCK, SOIL THAT DEFLECTS UNDER THE REAR WHEELS GREATER THAN 12"S SHALL BE REMOVED, RE-COMPACTED AND RETESTED FOR CEMPACTED AND RETESTED.
- 12. ON-SITE FILL SHALL BE USED TO THE MAXIMUM EXTENT POSSIBLE, ANY IMPORTED FILL SHALL BE CERTIFIED BY THE CONTRACTOR TO BE CLEAR OF ALL HAZARDOUS SUBSTANCES OR MATERIALS. IF MATERIAL IS ENCOUNTERED THAT CANNOT BE RIPPED BY A CAT D6 WITH A SINGLE TOOTH RIPPER, THEN THE CONTRACTOR SHALL CONTACT THE ENGINEER WHO WILL VISIT THE SITE AND DETERMINE IF THE MATERIAL MAY BE USED AS IS OR MUST BE REMOVED BY OTHER MEANS. IF UNSUITABLE SOLIS IN THE SUBGRADE ARE FOUND THEY SHALL BE REMOVED AND REPLACED WITH APPROPRIATE FILL AT THE CONTRACTOR'S EXPENSE AND THE ENGINEER'S DIRECTION.
- 13. IF SPRINGS OR SEEPS ARE ENCOUNTERED, SUBSURFACE DRAINAGE FEATURES SHALL BE INSTALLED PRIOR TO FILL PLACEMENT. CONTACT ENGINEER FOR EVALUATION AND RECOMMENDATION OF CORRECTIVE MEASURES.
- THE FILL TOE FOR ALL EMBANKMENTS SHALL BE BENCHED OR KEYED INTO THE NATURAL SOIL, ALL FILL TOES SHALL BE SUPPORTED BY COMPETENT BEDROCK OR SOIL MATERIAL.
- 15. FILL PLACED AGAINST EXISTING SLOPES SHALL BE BENCHED INTO THE EXISTING MATERIAL DURING ALL PLACEMENT TO REDUCE THE POTENTIAL FOR DEVELOPMENT OF A SMOOTH INTERFACE BETWEEN THE FILL AND EXISTING SLOPE.
- 16. ANY SOFT AREAS SHALL BE OVER-EXCAVATED TO A FIRM MATERIAL AND BACKFILLED WITH A WELL COMPACTED STRUCTURAL FILL
- 17. FILL REQUIRED TO OBTAIN DESIGN GRADES SHALL BE PLACED AS CONTROLLED, COMPACTED. ALL THE FILL SHALL BE FREE OF TRASH, WOOD, TOPSOIL, ORGANICS, COAL, COAL MINE REFUSE, FROZEN MATERIAL AND PIECES OF ROCK GREATER THAN 6" IN ANY DIMENSION
- 18. DURING PLACEMENT OF MATERIAL, MOISTEN OR AERATE EACH LAYER OF FILL, AS NECESSARY, TO OBTAIN THE REQUIRED COMPACTION. FILL SHOULD NOT BE PLACED ON SURFACES THAT ARE MUDDY OR FROZEN, OR HAVE NOT BEEN APPROVED BY PRIOR PROOF-ROLLING. FREE WATER SHALL BE PREVENTED FROM APPEARING ON THE SURFACE DURING OR SUBSEQUENT TO COMPACTION OPERATIONS.
- 19. SOIL MATERIAL WHICH IS REMOVED BECAUSE IT IS TOO WET TO PERMIT PROPER COMPACTION MAY BE SPREAD AND ALLOWED TO DRY. DRYING CAN BE FACILITATED BY DISKING OR HARROWING UNTIL THE MODITURE CONTENT IS REDUCED TO AN ACCEPTABLE LEVEL. WHEN THE SOIL IS TOO DRY, WATER MAY BE UNIFORMLY APPLIED TO THE LAVER TO BE COMPACTED.
- 20. THE FILL OUTSLOPES SHALL BE OVERBUILT AND TRIMMED BACK TO DESIGN CONFIGURATIONS TO VERIFY PROPER COMPACTION
- 21, GRANULAR MATERIALS, SUCH AS AASHTO NO. 57 STONE SHALL BE COMPACTED TO 85% OF ITS RELATIVE DENSITY, AS DETERMINED BY ASTM 0 4253 AND D 4254 TEST METHODS.
- 22. PHOTOGRAPHIC DOCUMENTATION SHALL BE TAKEN BY THE CONTRACTOR AND PROVIDED TO THE ENGINEER OF THE FOLLOWING

 - SITE AFTER CLEARING AND GRUBBING;
 THE SITE AFTER TOPSOIL REMOVAL;
 TOE KEY AND INSPECTION TRENCH CONSTRUCTION;
 DAILY PHOTOS OF CUT AND FILL OPERATIONS;
 PROOF-ROLLING TESTS.
- 23. THE CONTRACTOR SHALL PROVIDE THE ENGINEER WITH A COMPLETE BINDER THAT INCLUDES ALL PHOTO DOCUMENTATION, ALL COMPACTION TEST REPORTS, RESULTS AND MAPS, AND A REPORT OF ALL CUT AND FILL VOLUMES IN CUBIC YARDS.



230 Executive Drive, Suito 122 Cranberry Township, PA 1606 Phone: 724-772-7072 www.kleinfelder.com



Signed By: JOSHUA M, FARLEY, W.V. P.E. # 20711 DEVISIONS

	REVISION	3		
REV	DESCRIPTION	DSN	CHK	DATE
	DESCRIPTION	DWN	APP	
1 1				
		ļ		
				
		_		
 				
\vdash		_		
		<u> </u>		
1				

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

IF DISTANCE BELOW PLOTS ACCORDINGLY 1 INCH


ORIGINAL DRAWING SIZE IS 22 x 34


NOTES

CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA

Where energy meets innovation. PERMITTING

PROJECT NO. 137355 SSUE DATE 07/01/2015 CURRENT REVISION ESIGNED BY AER RAWN BY CHECKED BY JME APPROVED BY JMF SHEET






KLEINFELDER

001/1	DESCRIPTION			DATE
REV	DESCRIPTION	DWN	APP	DATE
		_		

SCALE VERIFICATION








230 Executive Drive, Suite 122 Cranborry Township, PA 16066 Phone: 724-772-7072



Signed By: JOSHUA M, FARLEY, W.V. P.E. # 20711

	REVISION	IS		
REV	DESCRIPTION	DSN	СНК	DATE
REV	DESCRIPTION	OWN	APP	DATE
			\Box	
		1		

ISSUED FOR PERMITTING
NOT RELEASED FOR CONSTRUCTION





INAL DRAWING SIZE IS 22 x 34


SITE PLAN

CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA




PERMITTING

		I LI CIVI	111110	
	PROJECT NO.	137355)	
	ISSUE DATE	07/01/2015	}	
	CURRENT REVISI	ON -]	6
i	DESIGNED BY	AER		O
	DRAWN BY	AER		
i	CHECKED BY	JMF		
	APPROVED BY	JMF	SHEET	





v	DESCRIPTION		CHK	DATE
. •	DESCRIPTION	DWN	APP	DATE
_				•
-				
	<u> </u>			
1		_		





230 Executive Drive, Suite 122 Cranberry Township, PA 16066 Phone: 724-772-7072



Signed By: JOSHUA M. FARLEY, W.V. P.E. # 20711

	REVISIONS								
	REV	DESCRIPTION	DSN CHK						
	REV	DESCRIPTION	DWN	APP	DATE				
\neg									
					Ì				
Ì									
1									
1									
Ì									
					ľ				

ISSUED FOR PERMITTING
NOT RELEASED FOR CONSTRUCTION



SCALE VERIFICATION

ADJUST SCALE ACCORDINGLY IF DISTANCE PLOTS DIFFERENTLY

60 120 18

ORIGINAL DRAWING SIZE IS 22 x 34

SITE PLAN

CPT-10 WELL PAD
DODDRIDGE COUNTY
WEST VIRGINIA



Where energy meets innovation.

PERMITTING

PROJECT NO. 137355
ISSUE DATE 07/01/2015

CURRENT REVISION DESIGNED BY AER


DRAWN BY AER

CHECKED BY JMF

APPROVED BY JMF

APPROVED BY JMF


SHEET





	REVISIONS			
REV	DESCRIPTION	DSN	CHK	0475
REV	DESCRIPTION		APP	DATE
				,
	-			
	·	_		
		_		





KLEINFELDER Bright People. Right Solutions.

230 Executive Drive, Sulte 122 Cranberry Township, PA 16066 Phone: 724-772-7072 www.kleinfelder.com



Signed	By: JOSHÚA M. FARLEY,	W.V. P.E. #	20711	
	REVISION	1 S		
REV	· DESCRIPTION	DSN	снк	DATE
REV	DESCRIPTION	DWN	APP	DATE
	•			
.				
			1	
			, , , , , , , , , , , , , , , , , , ,	
	**			

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

1 INCH

ADJUST SCALE ACCORDINGLY IF DISTANCE PLOTS DIFFERENTLY

FLOWBACK PIT CROSS SECTIONS &

PROFILE

CPT-10 WELL PAD DODDRIDGE COUNTY



Where energy meets innovation.

PERMITTING

PROJECT NO.	137355
ISSUE DATE	07/01/2015
CURRENT REVISIO	ON -
DESIGNED BY	AER
DRAWN BY	AER
CHECKED BY	JMF
APPROVED BY	. JMF

SHEET

10

FLOWBACK PIT SECTIONS

-250

1100

1075

1125

1100

1125

1100

1100

1075

1501060

150¹1080

TOP OF 1125 SLOPE

150¹080

150

0+50.00

1+00.00

0

1+50.00

0

2+00.00

-50

-50

FLOWBACK PIT TRUCK QUEUE

50

FLOWBACK PIT TRUCK QUEUE

50

- FLOWBACK PIT TRUCK QUEUE

TOP OF SLOPE

-100

TOP OF SLOPE -

1125

1100

1080

1125

1100

1080

BERM -

-100

1125

1100

1075


1060

1125

1100

1075

1060 50





230 Executive Drive, Suite 122 Cranberry Township, PA 16066 Phone: 724-772-7072 www.kleinfelder.com



Signed By: JOSHUA M, FARLEY, W.V. P.E. # 20711

	REVISIONS			
REV	DESCRIPTION	DSN	СНК	DATE
KEV	DESCRIPTION	DWN	APP	DATE
	,			
		L		
	·			
		L		
1	•			
]

ISSUED FOR PERMITTING
NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

1 INCH

ADJUST SCALE ACCORDINGLY IF DISTANCE PLOTS DIFFERENTLY

ORIGINAL DRAWING SIZE IS 22 x 34

COMPLETION PIT CROSS SECTIONS & PROFILE

CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA




PERMITTING


PROJECT NO.	137355	
ISSUE DATE	07/01/2015	
CURRENT REVISI	ON -	
DESIGNED BY	AER	
DRAWN BY	AER	
CHECKED BY	JMF	
APPROVED BY	JMF	SHEET


11

11 o



-200





LEGEND

AREA IN FILL

AREA IN CUT

EXISTING GRADE

PROPOSED COMPLETION PIT (UNLESS STATED OTHERWISE)

1. REFER TO SITE PLAN SHEET FOR ADDITIONAL COMPLETION PIT INFORMATION INCLUDING STORMWATER AND EROSION CONTROL MEASURES KLEINFELDER Bright People. Right Solutions

230 Executive Drive, Suite 122 Cranberry Township, PA 18056 Phone: 724-772-7072 www.kleinfelder.com



Signed By: JOSHUA M. FARLEY, W.V. P.E. # 20711

	REVISION	NS		
REV	DECCRIPTION.	DSN	снк	DATE
REV	DESCRIPTION	DWN	APP	DATE
	·			
1				

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

1 INCH

ADJUST SCALE ACCORDINGLY IF DISTANCE PLOTS DIFFERENTLY

ORIGINAL DRAWING SIZE IS 22 x 34

COMPLETION PIT CROSS SECTIONS


CPT-10 WELL PAD DODDRIDGE COUNTY




Where energy meets innovation.

PERMITTING

PROJECT NO.	137355	
ISSUE DATE	07/01/2015	
CURRENT REVIS	SION -]
DESIGNED BY	AER	
DRAWN BY	AER	
CHECKED BY	JMF	
APPROVED BY	JMF	SHEET







230 Executive Drive, Suite 122 Cranberry Township, PA 16066 Phone: 724-772-7072 www.kleinfekter.com



Signed	By: JOSHUA M. FARLEY,	W.V. P.E. #	20711	
	REVISION	is		
REV	DESCRIPTION	DSN	СНК	0.475
REV		DWN	APP	DATE
	•			[
	·			ľ
	•			ľ
		_	ļ	
		-		ļ
	***	_		
-		•		
		-	<u> </u>	
	•			
		1	1	1

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

1 INCH

ADJUST SCALE
ACCORDINGLY IF DISTANCE
PLOTS DIFFERENTLY

MAIN ACCESS ROAD CROSS SECTIONS & PROFILE

> CPT-10 WELL PAD DODDRIDGE COUNTY




Where energy meets innovation.


SHEET


PERMITTING

PROJECT NO.	137355
ISSUE DATE	07/01/2015
CURRENT REVISIO	ν -
DESIGNED BY	AER
DRAWN BY	AER
CHECKED BY	JMF
APPROVED BY	JMF

14











Signed By: JOSHUA M. FARLEY, W.V. P.E. # 20711

	REVISION	S			
REV	DEGODIOTION.	П	DSN	СНК	
KEV	DESCRIPTION	Ī	DWN	APP	DATE
		[_	
		·T			
	<u></u>				
		· · [
		L			
		L			
		Ĺ			
		L			
		Г			

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

1 INCH ADJUST SCALE ACCORDINGLY IF DISTANCE PLOTS DIFFERENTLY

ORIGINAL DRAWING SIZE IS 22 x 34

MAIN ACCESS ROAD CROSS SECTIONS & PROFILE

> CPT-10 WELL PAD DODDRIDGE COUNTY




PERMITTING


PROJECT NO.	137355
ISSUE DATE	07/01/2015
CURRENT REVIS	ION -
DESIGNED BY	AER
DRAWN BY	AER
CHECKED BY	JMF

APPROVED BY

15

JMF SHEET





KLEINFELDER Bright People. Right Solution

230 Executive Drive, Suite 122 Cranberry Township, PA 16066 Phone: 724-772-7072 www.kleinfelder.com



Signed By: JOSHUA M. FARLEY, W.V. P.E. # 20711

	REVISIONS			
REV	DESCRIPTION	DSN	CHK.	DATE
11.	DESCRIPTION		APP	DAIL
	. *			
		<u></u> .		
	•			

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

1 INCH

ADJUST SCALE
ACCORDINGLY IF DISTANCE
PLOTS DIFFERENTLY

ORIGINAL DRAWING SIZE IS 22 x 34

CULVERT PROFILES


CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA




PERMITTING


ROJECT NO.	137355	
SUE DATE	07/01/2015	
URRENT REVISI	ON -	
ESIGNED BY	AER	
RAWN BY	AER	
LIEGUES SV	10.477	1

16







2 TYPICAL PAD CROSS-SECTION DETAIL
14 NTS







3 MOUNTABLE BERM DETAIL




COMSTRUCTION PRECISCALIDAS

LOLVERTE WITH COLLEGE ON TO LEMOTHY FILL SLOPES MAY REQUIRE SLOPE DRAWS WITH OUTLES PROTECTION DEPENDEND ON THE STEEPHESS OF THE OUTSLOPE.

REPRAIP LIEGED AS QUILLE PROTECTION MIST SE HARD, ANDLURA MAD OF A QUALITY RESISTANT TO WRATHERING AND DISITRADISTING PRIPAP SHOULD BE GROUTED ON STEEP OF LEARNING THE AUXILIARY THAT LOLVER WITH A REMINIARY INCHEORES THY OTHER STEEP AND LANGE WITHOUT PASS THAT OF THE AUXILIARY STORE DAMAGE WITHOUT LESS THAT OF THE AUXILIARY STORE DAMAGE WITHOUT LIGHT STORE THE AUXILIARY STORE DAMAGE WITHOUT LIGHT STORE AUXILIARY STORE DAMAGE WITHOUT STORE AUXILIARY AU

6 DITCH RELIEF CULVERT DETAIL
17 NTS



ROAD-SIDE DITCH & CHANNEL DESIGN AND LINING												
ROAD-SIDE DITCH / CHANNEL NAME	TOTAL RUNOFF, Q (cfs)*	UPPER STATION	LOWER STATION	LENGTH (ft)	CHANNEL SECTION	BOTTOM WENTH (ft)	LEFT SIDE SLOPE, Z:1 (ft)	RIGHT SIDE SLOPE, Z:1 (ft)	CHANNEL DEPTH (ft)	CHANNEL SLOPE (ft/ft)	TEMPORARY LINER	PERMANENT LINER
ROAD-SIDE DITCH 1	0.23	AR1 01+95	AR1 00+32	163.00	TRIANGULAR	-	2.00	2.00	1.50	0.04	C125BN	C125BN
ROAD-SIDE DITCH 2	4.45	AR1 02+40	AR1 00+00	240.00	TRIANGULAR		2.00	2.00	1.50	0.03	C125BN	C125BN
ROAD-SIDE DITCH 3	0.04	AR1 07+75	AR1 07+18	57.00	TRIANGULAR		2.00	2.00	1.50	0.03	C125BN	C125BN
ROAD-SIDE DITCH 4	0.40	AR1 07+02	AR1 06+50	52.00	TRIANGULAR		2.00	2.00	1.50	0.10	C125BN	C125BN
ROAD-SIDE DITCH 5	0.95	AR1 09+50	AR1 07+02	248.00	TRIANGULAR		2.00	2.00	1.50	0.02	C125BN	C125BN
ROAD-SIDE DITCH 6	1.42	AR1 12+72	AR1 11+60	112.00	TRIANGULAR		2.00	2.00	1.50	0.02	C125BN	C125BN
ROAD-SIDE DITCH 7	0.45	AR1 17+85	AR1 16+08	177.00	TRIANGULAR		2.00	2.00	1.50	0.05	C125BN	C125BN
ROAD-SIDE DITCH 8	0.50	AR1 21+50	AR1 20+05	145.00	TRIANGULAR		2.00	2.00	1.50	0.13	C125BN	C125BN
ROAD-SIDE DITCH 9	3,56	AR2 31+00	AR1 26+25	475.00	TRIANGULAR	-	2.00	2.00	1.50	0.05	C125BN	C125BN
ROAD-SIDE DITCH 10	0.49	AR2 30+60	AR1 27+00	360.00	TRIANGULAR	-	2.00	2.00	1.50	0.10	C125BN	C125BN
ROAD-SIDE DITCH 11	10.78	CORT 4	CORD 4	98.50	TRIANGULAR		2.00	2.00	1.25	0.10	C125BN	C125BN
CHANNEL 1	0.08	N/A	N/A	530.00	TRIANGULAR	-	1.00	1.00	3.00	0.01	R-3	R-3
CHANNEL 2	1.38	N/A	N/A	322.00	TRIANGULAR		1.00	1.00 '	3.00	0.01	R-4	R-4
CHANNEL 3	11.01	N/A	N/A	500.00	TRIANGULAR	-	1.00	1.00	3.00	0.01	R-3	R-3
CHANNEL 4	1.96	N/A	N∕A	321.00	TRIANGULAR		1.00	1.00	3.00	0.01	R-3	R-3
TOTAL RUNOFF FOR CHANNEL 1 IS THE AREA & FLOW OF ROAD-SIDE DITCH 28 AND CHANNEL 1												
TOTAL RUNOFF FOR CH	ANNEL 2 IS THE A	AREA & FLOW OF RO	AD-SIDE DITC	H 29 30 &	31 AND CHANNE	1 2						

7 TYPICAL DRAINAGE ROAD-SIDE DITCH AND CHANNEL DETAIL 17



230 Executivo Drive, Suite 122 Cranberry Townshlp, PA 16066 Phone: 724-772-7072 www.kleinfelder.com



Signed By: JOSHUA M. FARLEY, W.V. P.E. # 20711

	REVISIONS						
	-		2011	СНК			
	REV	DESCRIPTION	DWN		DATE		
	-		51111	-			
	_			_			
İ							
				_			
			<u> </u>	-			
				_			
			<u> </u>				

ISSUED FOR PERMITTING
NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

IF DISTANCE BELOW PLOTS DIFFERENTLY, SCALE ACCORDINGLY

1 INCH

ORIGINAL DRAWING SIZE IS 22 x 34

DETAILS

CPT-10 WELL PAD
DODDRIDGE COUNTY
WEST VIRGINIA



PERMITTING

	137355	
]	7/01/2015	07/0
1		ISION
}	AER	
	AER	
1	INC	

JMF SHEET

PROJECT NO. ISSUE DATE

DESIGNED BY DRAWN BY


CHECKED BY


APPROVED BY

17

17


17 of 25







OUTLET	Do.	3Do	ما	w	RIP RAP	4
FES 1	18"	4.5"	8.	12.5	R-J RIPRAP	18
FES 2	18"	4,5'	18"	12,5"	R4 RIPRAP	18
FES 3	18"	4.5	18"	12.5	R-4 RIPRAP	18
FES 4	18"	4.5	18"	12.5	R4 RIPRAP	18
FES 5	18*	4.5	36	12,5"	R-6 RIPRAP	18
FES 6	18"	4.5'	36"	12.5'	R-6 RIPRAP	18

9 RIP RAP OUTLET PROTECTION DETAIL







Signed By: JOSHUA M. FARLEY, W.V. P.E. # 20711 REVISIONS

KLEINFELDER

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

IF DISTANCE BELOW PLOTS DIFFERENTLY, SCALE ACCORDINGLY

1 INCH

ORIGINAL DRAWING SIZE IS 22 x 34

DETAILS

CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA



Where energy meets innovation.

PERMITTING

PROJECT NO.	137355
ISSUE DATE	07/01/2015
CURRENT REVI	ISION -
DESIGNED BY	AER
DRAWN BY	AER
CHECKED BY	JMF
APPROVED BY	JMF

18

12 BROAD-BASED DIP DETAIL 18 NTS

SECTION VIEW

JUD BE IT WITH TAKE SALE AND AVERTOPPING. THE TOP OF THE STONE SHOULD BE A MANUFACTURE OF THE SELEN GRADE.

PRESIDES OF HIGH FLOYS.

A SHOULD BE EXCHAIGE UNSTRUCK OF THE ROOC PIPE BLE FROTECTION, WITH A MINISTUM DEPTH OF 1.0 BELON GRADE.


AS HOUSED BE EXCHAIGE UNSTRUCK WITH BE SHOULD SEE BUILT UP HIGHER ON EACH END WHERE IT THES INTO THE EMBANGMENT, ADJUST CREST AND BOTTOR

SHOULDER OF THE EMBANGENT OF DIVERSIONS.

SHOULDER OF THE EMBANGENT OF DIVERSIONS. M WITH AS NECESSARY TO FACILITATE PLACEMENT WITHIN THE DITCHICHANNEL. THE MINIMUM HEIGHT SHOULD BE 1.0°,

13 ROCK PIPE INLET DETAIL
18 NTS

11 TURN OUT DETAIL
18 NTS




							_	2'X 2' WOODEN STAKES PLACED 10' O.C.
	COMPO	ST SOCK FABRIC	HENDAUM SPECIF	CATIONS		1		
MATERIAL TYPE	3 mil HDPE	5 mt HQPE	5 mil HDPE	MUS-Fibrarit POLYPROPYLENE (MEPP)	HEAVY DUTY Multi-Flament Polypropylane (HOMFPP)		Ц/	COMPOST FILTER SOCK
MATERIAL CHARACTERISTICS	PHOTO- DEGRADABLE	PHOTO- DEGRADABLE	DEGRADABLE	PHOTO- DEGRADABLE	PHOTO- DEGRADABLE	BLOWN / PLACED -		
SOCK DIAWETERS	12" 18"	12 18 24 32	12 18 24 32	12" 16" 24" 32"	12" 18" 24" 32"	FILTER MEDIA /	\	
MESH OPENING	38	35	3/8	28.	3/8") \/	1	
TENSALE STRENGTH		26 ppi	25 psi	40	202 pel	1 /(1	UNDISTURBED AREA
ULTRA VIQUET STABILITY % ORIGINAL STRENGTH (ASSIM G-155)	23% at 1000 Nr.	23% at 1000 hr.		100% at 1000 hr.	100% at 1000 hr.	DISTURBED AREA		Adde
MINIMUM PUNCTIONAL LONGEVITY	6 MONTHS	9 WONTHS	6 MONTHS	1 YEAR	2 YEARS			
		THYO-PLY	Y SYSTEMS]	1 112	
				HOPE]	()	
NNE3 CC	WTANAJENT NET	TING	CONTINUOUSLY WOUND FUSION-HIELDED AINCTURES			1	V	
						EXISTING CONTOURS	CEODON 145W	
				K 3M" MAX, APERTURE LYPROPYLENE FABRIC		_ \	SECTION_VIEW	/ -
OUTER	FILTRATION ME	5H		N PLEEECE MECHANIA NEEDLE PUNCHI		l (a) \	DISTURBED	102
				16" MAX. APERTURE S	75	1 1 1 1 \	AREA	
SOCK FARRICS	COMPOSED OF	RUEL AP MAY RE		TS LASTING & MONTH		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
						' ' ` ` ` ` ` ` ` ` `	_ \	
	co	MPOST STAND	DARDS		7	18(/ 34		_1 / /]8
ORGANIC M	ATTER CONTE	NT 6	100% (DRY	WEIGHT BASIS)	1	8 4 -	` ~ _	新 / // 丿
ORGAN	IC PORTION		FIBROUS AND	ELONGATED	7	\-\ \ \	_	₹ / 8/
	pH		5.5-8.0		7	/8		8/
MOISTU	RE CONTENT		35%-55%		7	 •	2 B 8	8 8
PART	ICLE SIZE	9	8% PASS THRO	UGH 1" SCREEN	7 27	2 WOODEN STAKES	7	
SOLUBLE SAL	CONCENTRA	TION	5,0 dS/m (mmho	s/cm) MAXIMUM]	PLACED 10' O.C.	UNDISTURBED AREA	
						COMPOST FILTER SOCK		
NOTES							PLAN_VIEW	
1. SOOK FABRIC SHAE 2. COMPOST FILTER S DOWNSLOPK OF TH 3. TRAFFIC SHAEL NO	OCK SHALL BE PA E SOCK IF SO SP F BE PERMITTED	ACED AT EXISTING COPIED BY THE ME NO CROSS PILITER	G LEVEL GRADE B WARFACTURER. SOCKS.		DK SHALL BE EXT	ENDED AT LEAST 6 FEET UP SLOPE AT 45 DECREE		STANCES WAY BE INSTALLED MOREDIATELY
4. ACCUMULATED SED 5. SOCIOS SHALL BE I	NENT DALL BE REPECTED WEEKL	renoved riven i I and after eac	T REACHES HALF T ON RUNOFF EYENT.	DANAGED SOOKS SHA	ONT OF THE SOOT LL BE REPARED	C AMO DISPOSED IN THE WANNER DESCRIBED ELSE ACCORDING TO MANUFACTURER'S SPECIFICATIONS (encoz in ing plan. De reducado hithen 24 hours of	NOTES N.


NOT REPORTED TO COSSITUED SCOOL.

THE STATE OF THE SCOOL THE SCOOL THE SCOOL AND THE SCOOL AND DESCRIPT IN MAKEND SCOOLING DESCRIPT IN THE PLAN.

THE SCOOL THAN ARE SCOOLING ON IT THE SCOOL AND THE SCOOL AND DESCRIPT IN THE SCOOL AND THE SC


15 COMPOST FILTER SOCK DETAIL 19 NTS







KLEINFELDER

DATE









/	$\overline{}$	\				
/	17)	ROCK	CHECK	DAM	DETAIL
	19		NTS			
_		/				

ID#	CFS	DIAMETER
# טו	(LF)	(IN)
1	100	18
2	95	18
3	50	18
4	100	24
5	100	32
6	110	32
7	120	32
8	140	18
9	105	32
10	90	32
11	90	32
12	115	18
13	120	18
14	70	24
15	150	24
16	240	18
17	70	18
18	125	12
19	165	12
20	65	12
21	255	24
22	40	12
23	115	12
24	225	12
25	110	18
26	200	12
27	165	18
28	70	12


ID#	SSF	
# טו	(LF)	
29	55	
30	100	
31	80	
32	50	
33	125	
34	45	
35	165	
36	200	
37	135	
38	75	
39	90	
40	180	
41	140	
42	40	
43	60	
44	160	
45	105	
46	95	
47	100	
48	110	
49	110	
50	460	
51	75	
52	65	
53	250	
54	220	
55	90	
56	400	



19 SLOPE PROTECTION INSTALLATION DETAIL 19 NTS



ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION



20 BRUSH PILE SEDIMENT BARRIER DETAIL
19 NTS

ORIGINAL DRAWING SIZE IS 22 x 34

DETAILS

CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA



Where energy meets innovation.


PERMITTING

PROJECT NO.	137355	Г
ISSUE DATE	07/01/2015	
CURRENT REVISI	ON -	
DESIGNED BY	AER	1
DRAWN BY	AER	1
CHECKED BY	JMF	
APPROVED BY	JMF	١.

19

19 of 25

18 SUPER SILT FENCE & FILTER SOCK TABLES
19 NTS



26 TYPICAL PIT EMBANKMENT DETAIL 20 NTS

KLEINFELDER

230 Executive Drive, Suite 122 Cranberry Township, PA 16066 Phone: 724-772-7072 www.klainfelder.com



gned By: JOSHUA M. FARLEY, W	.V. P.E. #	20711	
REVISIONS	6		
DESCRIPTION	D\$N	СНК	DAT
DESCRIPTION	DWN	APP	UAI

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

IF DISTANCE BELOW PLOTS DIFFERENTLY, SCALE ACCORDINGLY

1 INCH

ORIGINAL DRAWING SIZE IS 22 x 34

DETAILS


CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA




Where energy meets innovation.

	137355	ROJECT NO.
	07/01/2015	SUE DATE
	ION -	URRENT REVI
	AER	ESIGNED BY
	AER	RAWN BY
	JMF	HÉCKED BY
SHI	JMF	PPROVED BY

20







230 Executive Drive, Suite 122 Cranberry Township, PA 16066 Phone: 724-772-7072 www.kleinfelder.com



у:	JOSHUA M.	FARLEY, W.V. P.E.	1
		REVISIONS	

Oil	gned By: JOSHUA M. FARLEY, W.V	, P.E. #	20711	
	REVISIONS			
REV	DESCRIPTION	D\$N	снк	DATE
REV	DESCRIPTION	DWN	APP	DATE
		<u> </u>		
_				
			ļ	
-				
1		-		
-				
		-	-	
-		+	_	
		-		
		T		

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

IF DISTANCE BELOW PLOTS DIFFERENTLY, SCALE ACCORDINGLY

1 INCH

ORIGINAL DRAWING SIZE IS 22 x 34

DETAILS

CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA



Where energy meets innovation.

PERMITTING

PROJECT NO.	137355
ISSUE DATE	07/01/2015
CURRENT REVIS	ION -
DESIGNED BY	AER
DRAWN BY	AER
CHECKED BY	JMF
APPROVED BY	JMF

TYPICAL BERM BREACH
21 NTS

8" RIP-RAP OUTLET PROTECTION

BREAK IN BERM -

Specification Sheet - BioNet* C125BN™ Erosion Control Blanket

The long-term double net erosion control blanket shall be a machine-produced mat of 100% coconut filber with a functional longevity of up to 24 months. (NOTE: functional longevity may vory depending upon climatic conditions. Soil geographical location. and elevation! The blanket shall be of consistent thickness with the coconut evenly distributed over the or consistent transforms with the cutoust evenly distinctive over the entire area of the mat. The blanket shall be covered on the top and bottom sides with 100% biodegradable woven natural organic fiber netting. The netting shall consist of machine directional strands formed from two intertwined yarns with cross directional strands interwoven through the the twisted machine strands (commonly referred to as Leno weave) to form an approximate 0.50 x 1.0 in (1.27 x 2.54 cm) mesh. The thread stitched along both outer edges (approximately 2-5 Inches [5-12.5 cm] from the edge) as an overlap guide for adjacent mats

The C125BN shall meet Type 4 specification requirements established by the Erosion Control Technology Council (ECTC) and Federal Highway Administration's (FHWA) FP-03 Section 713.17

	MaterialConte	邱
Matrix	100% Coconut Fiber	0.5 lbs/sq yd (0.27 kg/sm)
	Leng Woven 100%	9.3 lbs/1000 sq f
	blodegradable jute	(4.5 kg/100 sm)
Netting		
	100% Blodegradable lute	7.7 lb/1880 sq ft
	iou a dioucgisadore jate	(3.76 kg/100 sm
Thread	Black polypropytene	

	Standard Roll (3 1763
Width	6.67 (2.03 m)	8.0 ft (2.4 m)
Length	108 ft (32.92 m)	112 ft (34.14 m)
Weight ± 10%	52.22 lbs (23.69 kg)	65.25 lbs (29.61 kg)
Area	80 sq yd (66.9 sm)	180 sq yd (83.61 sm)
	Lene weave top only	Leng weave top and botto

Tensar NORTH AMERICAN GREEN*

ASTM 06525 ECTC Guidelines ASTM D1117 ASTM 6475 ECTC Guidelines **ECTC** Guidelines 16.2% 206.4 lbs/ft (3.06 kN/m) 15.3% 145.2 lbs/ft ASTM 06567 ASTM 06818 ASTM D6818 Tensile Strength - TD (2.15 kN/m) Elongation - TD ASTM DERIR ASTM 7322 Design Permissible Shear Stress Unvegetated Shear Stress 2.35 psf (112 Pa) 10.0 fps (3.05 m/s)

TestMethod Typical

	Slop	e Gradients (S)	
Slope Length (L)	s 3:1	3:1 - 2.1	≥ 2:1
≤ 20 ft (6 m)	0.0001	0.018	0.050
20-50 ft	0.003	0.040	0.060
2 50 ft (15.2 m)	0.007	0.070	0.070

CoughnessCosfficients−Unves				
Flow Depth	Manning's n			
s 0.50 ft (0.15 m)	0.022			
0.50 - 2.0 ft	0.022-0.014			
≥ 2.0 ft (0.60 m)	0.014			

EC_RMX_MP05_0C125814_5.13

ROLLMAX**
ROLLED EROSION CONTROL Specification Sheet - VMax® C350® Turf Reinforcement Mat DESCRIPTION Ugited DESCRIPTION

The composite turf reinforcement mat (C-TRM) shall be a machine-produced mat of 100% coconut fiber matrix incorporated into permanent timee-dimensional turf reinforcement matting. The matrix shall be evenly distributed a cross the entitie which of the matting and stitich bonded between super heavy duty UV-stabilized nettings with 0.5 to 0.5 to, (1.7 x 1.27 cm) openings, an ultra heavy duty UV-stabilized, dramatically corrugated (crimped) intermedial enterling with 0.5 to, 15. in. (1.27 x 1.27 cm) openings. The middle corrugated netting shall form prominent closely spaced ridges across the entire width of the mat. The three mettings shall be stitched together on 150 in. (1.27 s. 1.27 cm) TestMethod (Index(Rogerty 0.73 in. (18.54 mm) ASTM D6525 ASTM D6524 90% 0.917 g/cm¹ 18.36 oz/sy (624 g/sm) 86% ECTC Guidelines 99% three nettings shall be stitched together on 1.50 in, (3.81 cm) centers with UV-stabilized polypropylene thread to form permanent three-dimensional turf reinforcement matting. All mass shall be manufactured with colored thread stitched ASEM D1388 0.24 in.-ib (275990 mg-cm) 7.2% 585.8 lbs/ft (8.70 kN/m) ASTM DS818 along both outer edges as an overlap guide for adjacent mats. The C350 shall meet Type SA, B and C specification requirements established by the Erosion Control Technology Council (ECTC) and Federal Highway Administration's (FHWA) FP-03 Section 713.18. ASTM D6818 45.3% 687.6 lbs/ft (10.20 kH/m) ASTM 06818 ASTM DERIS 19.5% Anticological and a state of the state of th 380% 8 lb/1000 sf {3.91 kg/100 sm} 24 lb/1000 sf (11.7 kg/100 sm) - Crypropylene
Middle, Corrugated UV-Stabilized
Polypropylene 0ක්ලා දිනායික්ට්ට්ටේකන් නියන Long Duration Phase 1 Unvegetated 3.2 psf (153 Pa) 3.0 psf (144 Pa) Phase 2 Partially Veg. 10.0 psf (480 Pa) 10.0 psf (480 Pa) Phase 3 Fully Veg. 12.0 psf (576 Pa) 10.0 psf (480 Pa) Standard Roll Stress Invegetated Velocity 10.5 fps (3.2 m/s) 6.5 ft (2.0 m) Vegetated Velocity 20 fps (6.0 m/s) 55.5 ft (16.9 m) 37 lbs (16.8 kg) Weight ± 10% 40 sv (33.4 sm)

29 NORTH AMERICAN GREEN C125BN TURE REINFORCEMENT MATTING (OR EQUIVALENT)
22 NTS

NORTH AMERICAN GREEN C350 TURF REINFORCEMENT MATTING (OR EQUIVALENT)



230 Executive Drive, Suite 122 Cranberry Township, PA 16066 Phone; 724-772-7072 www.kleinfelder.com



Signed By: JOSHUA M. FARLEY, W.V. P.E. # 20711

	REVISIONS			
REV	DESCRIPTION	DSN	DATE	
KEV	DESCRIPTION	DWN	APP	DATE
		[
	•			
			П	
	·			

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION

IF DISTANCE BELOW PLOTS DIFFERENTLY, SCALE ACCORDINGLY

1 INCH

ORIGINAL DRAWING SIZE IS 22 x 34

DETAILS

CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA




Where energy meets innovation.

PERMITTING

PROJECT NO.	137355	Г
ISSUE DATE 01	7/01/2015	
CURRENT REVISION	-	
DESIGNED BY	AER	
DRAWN BY	AER	
CHECKED BY	JMF	
APPROVED BY	JMF	:

22 of 25






230 Executive Drive, Suite 122 Cranberry Township, PA 16066 Phone: 724-772-7072 www.klninfolder.com



Signed By: JOSHUA M. FARLEY, W.V. P.E. # 20711

	REVISIONS			
REV	DESCRIPTION	D\$N	СНК	DATE
NE¥	DESCRIPTION	DWN	APP	DATE

ISSUED FOR PERMITTING
NOT RELEASED FOR CONSTRUCTION



ALE: 1" = 60' SCALE IN

RIGINAL DRAWING SIZE IS 22 x 34

RECLAMATION PLAN

CPT-10 WELL PAD
DODDRIDGE COUNTY




Where energy meets innovation.


PERMITTING

PROJECT NO.	137355	
ISSUE DATE	07/01/2015	
CURRENT REVISIO	N -	
DESIGNED BY	AER	ĺ
DRAWN BY	AER	
CHECKED BY	JMF	
APPROVED BY	JMF	9


رے "

23 of 2





ATTACHMENT C FLOODPLAIN MAP



CPT-10 Well Pad FEMA FIRM 54017C0045C **EQT Production Company Doddridge County, WV**



Legend

Proposed LOD (40.5 ac)

— Existing Road

FEMA 100 Year Flood Zone

PROJECT #: 00137355.000A

DRAWN: 8/14/2015

PRINTED: 8/17/2015

DRAWN BY: AL

CHECKED BY: MA

FILE PATH:









The Doddridge Independent **PUBLISHER'S CERTIFICATE**

I, Michael D. Zorn, Publisher of The Doddridge Independent, A newspaper of general circulation published in the town of West Union, Doddridge County, West Virginia, do hereby certify that:

Floodplain Permit Application # 15-375

Please take notice that on the 17th day of August, 2015

EQT Production Company

filed an application for a Floodplain Permit to develop land located at or about:

15-375- EQT Production Company CPT-10 Well Pad Project Location: County Route 4 Coordinates: 39.411532, -80.661258

was published in The Doddridge Independent 2 times commencing on Friday, August 28, 2015 and Ending on Friday, September 4, 2015 at the request of:

George Eidel, Doddridge County Floodplain **Manager & Doddridge County Commission**

Given under my hand this Tuesday, September 8, 2015

The publisher's fee for said publication is:

\$ 25.27 1st Run/\$ 18.95 Subsequent Runs This Legal Ad Total: \$ 44.22

Publisher of The Doddridge Independent

Subscribed to and sworn to before me on

Notary Public in and for Doddridge County

My Commission expires on

Public Notice • Legal Notice

Floodplain:PermitApplication#15-375 Please take nouce that on the With day of August, 2015

EQT Production Company

EQT Production Company filed an application for a Floodplain Permit to develop land located at or about:

15-375 EQT Production Company CPT-10 Well Pad Project Location: County Route 4

Coordinates: 39.411532, 801661258 Received: 08/21/2015

To Be Announced: 09/01/2015

Publication Date: Week of 09/24/2015

20-Day, Comment Period Window (from Commission Meeting) 09/20/2015 - NOT IN FEOODPLAIN

The Application is on file with the Glerk of the County Court and may be inspected or copied during regular business hours. As this project is outside the FEMA identified floodplain of Doddridge County.

Doddridge County Floodplain Management has no regulatory authority. Any interested persons who desire to comment shall present the same in writing by August 28, 2015, delivered to

Clerk of the County Court 118 E. Court Street, West Union, WV 26456 Beth A Rogers; Döddridge County Clerk George Eidel. Doddridge County Flood Plain Manager



NON-REPORTING NATIONWIDE PERMIT 14 CPT-10 WELL PAD PROJECT

DODDRIDGE COUNTY, WEST VIRGINIA





Where energy meets innovation.

EQT PRODUCTION COMPANY 120 PROFESSIONAL PLACE BRIDGEPORT, WV 26330

PREPARED BY:



KLEINFELDER, INC. 230 EXECUTIVE DRIVE, SUITE 122 CRANBERRY TOWNSHIP, PA 16066

AUGUST 2015

TABLE OF CONTENTS

Exec	utive Summary	. 1
1.0	Introduction	. 2
1.1 1.2 1.3 1.4 1.5	Project Description	. 2 . 2 . 2
2.0	Methods	. 3
2.1 2.2 2.3 2.4	Desktop Analysis	. 3 . 3 . 4 . 4
3.0	Jurisdictional Findings	. 4
4.0	Impacts	. 7
5.0	Permitting Requirements	. 9
Table Table Table	OF TABLES 1 – Land Owner Information 2 – Potentially Jurisdictional Features Identified in the AOI 3 – Impacts to Potentially Jurisdictional Waters in the Project LOD (Fill Only)	6 8
LIST	OF FIGURES	
Figur	re 1 – Project Location Map re 2 – Delineation Map re 3 – Soils Map	
APPE	ENDICES	
Appe Appe	endix A – Delineation Data Sheets endix B – Photos of Jurisdictional Features endix C – Design Drawings endix D – Agency Correspondence Letters	

Executive Summary

EQT Production Company (EQT) is proposing to construct a well pad, completion pit, flowback pit, and associated access roads, known as the CPT-10 Well Pad (Project), in Doddridge County, West Virginia (WV) (Figure 1). Site location maps are provided as Figure 1 (Project Location Map) and Figure 2 (Aerial Imagery Map). The proposed Project will have a limit of disturbance (LOD) of 40.5 acres and will support EQT's natural gas development of state-permitted wells within the region. As described in this report, the project meets all of the terms and conditions of a non-reporting Nationwide Permit (NWP) 14 for linear transportation projects.

Kleinfelder, Inc. (Kleinfelder) biologists conducted stream and wetland investigations and habitat assessments on October 30 – 31, 2013, August 19, 2014, and February 2, 2015 within the 100-acre Area of Interest (AOI) surrounding the project. Seven (7) potentially jurisdictional features were observed within the AOI and included five (5) ephemeral streams, one (1) intermittent stream and one (1) palustrine emergent (PEM) wetland.

Field data collected during stream and wetland delineations provided the basis for adjusting the Project location in a manner that minimized and avoided impacts to aquatic habitats and biological features. The proposed Project will permanently impact one (1) intermittent stream (Stream 6). This impact will be associated with placement of rip-rap for a drainage ditch along County Route 4. Temporary disturbances related to construction (non-fill) will occur to one (1) intermittent stream (Stream 6). Table 3 summarizes the proposed fill related impacts to potential jurisdictional features. Table 4 summarizes the proposed non-fill related construction disturbances to potentially jurisdictional features and the associated avoidance and minimization measures.

A Pre-Construction Notification to the U.S. Army Corps of Engineers (ACOE) is not required since each proposed stream impact is under 100 linear feet, and therefore the contents of this report represents a "No Impact Project". Information contained herein records EQT's due diligence in a thorough environmental site investigation.

1.0 Introduction

This report represents a non-reporting Nationwide Permit (NWP). Information contained in this report records EQT Production Company's (EQT) due diligence in a thorough environmental site investigation. This project is within the constraints of a non-reporting NWP 14 (linear transportation projects). Therefore, the project does not require District Engineer notification.

1.1 Project Description

EQT is proposing to construct a well pad, completion pit, flowback pit, and associated access roads, known as the CPT-10 Well Pad (Project), in Doddridge County, West Virginia (WV) (Figure 1) to support EQT's natural gas development of state-permitted wells within the region. Site location maps are provided as Figure 1 (Project Location Map) and Figure 2 (Delineation Map). The proposed area of interest (AOI) is approximately 110 acres. However, only 40.5 acres will be associated with the limit-of-disturbance (LOD). In order to construct the proposed Project, site access will be obtained through the use of one (1) access road. During site reviews, seven (7) potentially jurisdictional features were identified. None of the features are listed in the National Hydrography Dataset (NHD) or in the National Wetland Inventory (NWI) (Figures 1 and 2).

1.2 Land Owner Information

Property owner information is included in Table 1.

	Table 1. Land Owner Information
Property ID	Property Owner Name
05-12-3	HAYES, SHIRLEY, JAMES & MARJORIE
05-6-27	COASTAL FOREST RESOURCES CO
05-12-2.3	ASH, SAMUEL G. ET UX

1.3 Location

The Project is located in Doddridge County, WV as shown on the Project Location Map (Figure 1) and will be accessed via County Route 4 at 39.411532°, -80.661258°. Directions to the site from Center Point, WV are provided below:

- Head north on WV-23 W toward Hill Street.
- Make a slight right onto County Route 4/Broad Run and continue for 0.9 miles.
- · The entrance to the access road will be on your left.

1.4 Site Description

Figure 1 depicts the location of the proposed AOI on a United States Geological Survey (USGS) topographic background. Land cover types within the AOI consist primarily of deciduous forest and open pasture. The forested community is dominated by American beech (*Fagus grandifolia*), eastern white pine (*Pinus strobus*), shagbark hickory (*Carya ovata*), red oak (*Quercus rubra*), sugar maple (*Acer saccharum*), and white oak (*Quercus alba*). Elevations throughout the AOI range from approximately 800 feet to 1,260 feet above mean sea level. No roads are crossed by the proposed Project, however County Route 4 does travel within the AOI and will be used for site access.

1.5 Climate/Site Conditions

The Project was visited by Kleinfelder Biologists with weather conditions consisting of the following during each site visit:

- October 30 31, 2013 Temperatures averaging 52 degrees Fahrenheit (°F) with scattered rain events.
- August 19, 2014 Temperatures averaging 76°F with overcast skies.
- February 2, 2015 Temperatures averaging 33°F with light rain in the morning changing over to light snow in afternoon and evening.

2.0 Methods

2.1 Date of Field Work and Personnel

Field work was led by Kleinfelder Biologists Evan McClung, Jaime Zsiros, and John Lewis on October 30 – 31, 2013, August 19, 2014, and February 2, 2015, respectively. Evan McClung is a Senior Environmental Scientist with 15 years of experience conducting stream assessments, wetland delineations, habitat assessments with 13 years of experience conducting stream assessments, wetland delineations, habitat assessments and operating professional grade GPS units. John Lewis is an Environmental Scientist with five (5) years of experience conducting stream assessments, wetland delineations habitat assessments, and operating professional grade GPS units.

2.2 Scope of Work

At the request of EQT, Kleinfelder Biologists delineated aquatic features within the 110-acre AOI according to procedures outlined in the 1987 United States Army Corps of Engineers (ACOE) Wetland Delineation Manual and the AGOE Eastern Mountains and Piedmont Regional Supplement Version 2.0 (ACOE, 2012). Aquatic features including springs, seeps, culverts, ditches, ponds and areas of standing water were evaluated and are illustrated on Figure 2.

Kleinfelder utilized a three-parameter approach, involving the examination of vegetation, soils, and hydrology to identify indicators of wetlands. Representative photographs were taken of each feature (Appendix B) Data points were collected with a sub-meter accuracy Global Positioning System (GPS) unit in order to record the boundary of each aquatic feature within the AOI. The GPS data points were verified and validated by the field and engineering teams and combined into shapefiles, which were used to create the mapping (Figure 2).

Jurisdictional determinations were made in accordance with the "Routine Wetland Determination" procedures outlined in the 1987 ACOE Wetland Delineation Manual and the ACOE Eastern Mountains and Piedmont Regional Supplement to the Wetland Delineation Manual, Version 2.0 (ACOE, 2012) and based on instruction and guidance given by ACOE personnel during site walks in March 2015. The routine method was selected because it resulted in adequate qualitative data for making determinations. Occasionally the comprehensive method may be used in highly complex systems, but for this Project the routine method was sufficient to obtain the necessary data.

Wetlands determined to be jurisdictional exhibited hydric soils, hydrophytic vegetation and indicators of hydrology. Jurisdictional streams exhibited ordinary high water marks (OHWM), a defined bed and bank and a sorted substrate.

2.3 Desktop Analysis

Kleinfelder conducted a desktop analysis to examine known stream and wetland data from the NWI and NHD. NWI data were obtained from the United States Fish and Wildlife Service (USFWS) (http://www.fws.gov/wetlands/Data/State-Downloads.html). NHD data were obtained from the ESRI online map service. These datasets were superimposed upon USGS topographic data to identify areas likely to contain hydrologic features. Hydric soils data from the United States Department of Agriculture – Natural Resources Conservation Service (USDA – NRCS) was also reviewed to determine areas likely to contain aquatic features (Figure 3).

After delineation, a desktop review was conducted to determine stream classifications (Table 2). Designated trout streams were evaluated through consultation with the West Virginia Department of Environmental Protection (WVDEP). High Quality (HQ) waters were evaluated by reviewing Water Quality Standard Data available through the WVDEP website (http://www.dep.wv.gov/WWE/Programs/wqs/Pages/default.aspx), which indicates that no HQ waters exist in the Project AOI.

Additionally, a preliminary review of the National Register of Historic Places (NRHP) and the West Virginia State Historic Preservation Office (WVSHPO) online databases was conducted to determine if any known registered sites are located in the vicinity of the proposed Project. The results of this review identified no archeological areas within the Project AOI. The closest archeological area occurs approximately 1.75 miles southeast of the AOI.

2.4 ACOE Jurisdictional Statement

This report reflects the professional opinion of Kleinfelder. Formal determination of jurisdiction regarding wetlands and waters of the United States (WoUS) can only be determined by the ACOE with the submittal of a jurisdictional determination request by the Project Applicant.

3.0 Jurisdictional Findings

Seven (7) potentially jurisdictional features were observed within the AOI and included five (5) ephemeral streams, one (1) intermittent stream and one (1) palustrine emergent (PEM) wetland. The jurisdictional streams and wetland in the AOI are described below and depicted in Figure 2. Table 2 provides a list of the potential jurisdictional features and characteristics. Data sheets and photographs are included as Appendix A and Appendix B, respectively.

Description of Potentially Jurisdictional Findings:

<u>Stream 1</u> is an ephemeral stream (Unnamed Tributary (UNT) to Broad Run) located in the southwest portion of the Project AOI. At the time of the field investigation, the stream exhibited an OHWM of two (2) inches deep and four and one-half (4.5) feet wide. The stream substrate was primarily composed of gravel and cobble. This stream maintains surface connectivity to a relatively permanent waterway (RPW) and meets the definition of a jurisdictional WoUS.

Stream 2 is an ephemeral stream (UNT to Broad Run) located in the southwest portion of the Project AOI. At the time of the field investigation, the stream exhibited an OHWM of one (1) inch deep and four and one-half (4.5) feet wide. The stream substrate was primarily composed of

gravel and cobble. This stream maintains surface connectivity to a RPW and meets the definition of a jurisdictional WoUS.

<u>Stream 3</u> is an ephemeral stream (UNT to Broad Run) located in the southwest portion of the Project AOI. At the time of the field investigation, the stream exhibited an OHWM of two (2) inches deep and five (5) feet wide. The stream substrate was primarily composed of gravel and cobble. This stream maintains surface connectivity to a RPW and meets the definition of a jurisdictional WoUS.

Stream 4 is an ephemeral stream (UNT to Broad Run) located in the southwest portion of the Project AOI. At the time of the field investigation, the stream exhibited an OHWM of two (2) inches deep and four and one-half (4.5) feet wide. The stream substrate was primarily composed of gravel and cobble. This stream maintains surface connectivity to a RPW and meets the definition of a jurisdictional WoUS.

Stream 5 is an ephemeral stream (UNT to Broad Run) located in the southeast portion of the Project AOI. At the time of the field investigation, the stream exhibited an OHWM of one (1) inch deep and eight tenths (0.8) of a foot wide. The stream substrate was primarily composed of gravel. This stream maintains surface connectivity to a RPW and meets the definition of a jurisdictional WoUS.

Stream 6 is an intermittent stream (UNT to Broad Run) located in the southeast portion of the Project AOI. At the time of the field investigation, the stream exhibited an OHWM of two (2) inches deep and four (4) feet wide. The stream substrate was primarily composed of gravel. The stream is an RPW and meets the definition of a jurisdictional WoUS.

Wetland 1 is a PEM located in the southeast portion of the AOI. Wetland 1 occurs in the floodplain of Stream 6 and is located inside a residential yard. Hydric soils, hydrophytic vegetation, and indicators of hydrology were observed. This wetlands maintains a hydrologic connection to a RPW and is anticipated to be jurisdictional to the ACOE.

Table 2. Potentially Jurisdictional Features Identified in the AOI

Name ¹	Cowardin Code ²	HGM Code?	Measurement Type	Amount	Units	Waters Type ²	Latitude ³	Longitude*	Local Waterway	Wild Trout ⁴	Stocked Trout ^s	High Quality Water
Streams											. No. 1	Nia -
Stream 1	R6	N/A	Linear	758	Feet	NRPW	39.412334	-80.667085	UNT to Broad Run	No	No	No
Stream 2	R6	N/A	Linear	160	Feet	NRPW	39.412211	-80.665987	UNT to Broad Run	No	No	No
Stream 3	R6	N/A	Linear	190	Feet	NRPW	39.410339	-80.669389	UNT to Broad Run	No	No	No
Stream 4	R6	N/A	Linear	217	Feet	NRPW	39.409936	-80.669373	UNT to Broad Run	No	No	No
Stream 5	R6	N/A	Linear	18	Feet	NRPW	39.413567	-80.658559	UNT to Broad Run	No	No	No
Stream 6	R4SB3	N/A	Linear	408	Feet	RPW	39.411703	-80.661819	UNT to Broad Run	No	No	No
Wetlands												
Wetland 1	PEM	Riverine	Area	818	Square Feet	DELINEATE	39.411194	-80.66213	N/A	N/A	N/A	N/A

Notes:

Kleinfelder naming convention.
 As determined by the ACOE's Waters Upload Sheet
 North American Datum 1983
 Sustains wild trout populations with no annual stocking, WV Division of Natural Resources (WVDNR) communication states there are no trout streams in Doddridge County.
 WVDNR Interactive Trout Stream Map. http://map.wv.gov/lrout/
 WHigh Quality (WVHQ) Streams, Sixth Edition. WVDNR (2001)

4.0 Impacts

The location of the proposed Project was developed to avoid and minimize impacts to stream and wetlands. Field data collected during stream and wetland delineations provided the basis for adjusting the Project location in a manner that minimized and avoided impacts to aquatic habitats and biological features.

The proposed Project will permanently impact one (1) intermittent stream (Stream 6). This impact will be associated with placement of rip-rap for a drainage ditch along County Route 4. Temporary disturbances related to construction (non-fill) will occur to one (1) intermittent stream (Stream 6). Table 3 summarizes the proposed fill related impacts to potential jurisdictional features. Table 4 summarizes the proposed non-fill related construction disturbances to potentially jurisdictional features and the associated avoidance and minimization measures.




Table 3. Impacts to Potentially Jurisdictional Waters in the Project LOD (Fill Only)

	HWM epth ches)	Nature of limpact	Length of Disturbance (feet)	Area of Disturbance (acres)	Fill Quantity (cubic yards)	Temporary (T) or Permanent (P) Impacts	Type of Fill
Stream 6 4	2	Open-Cut	31	0.002	3	Р	Rip-Rap

Table 4. Temporary Disturbance Related to Construction in the Project LOD (No Fill)

Feature Label	Length of Non-Fill Disturbance (feet)	Area of Disturbance (acres)	Nature of Disturbance Avoidance and Minimization
Stream 6	18	0.010	The boundaries of the LOD have been reduced at this crossing to minimize impacts to this feature. Matting and pallets will be in place during construction to protect stream banks from construction related traffic.

5.0 Permitting Requirements

- <u>ACOE</u> This project meets the terms and conditions of a non-reporting NWP-14 for impacts to streams under 100 linear feet. No further consultation with the ACOE is required.
- <u>USFWS</u> A rare, threatened and endangered (RTE) species consultation letter was submitted to the USFWS on July 24, 2015 (Appendix D). The project will result in greater than 17 acres of forest clearing. A conservation plan was submitted with the Section 7 consultation letter to the USFWS. Final concurrence from USFWS is currently pending.
- WVDNR-Office of Land and Streams (OLS) Stream Activity Application for coverage under a Right-of-Entry Permit is required for the proposed stream crossing and will be submitted by EQT.
- WVSHPO Environment and Archaeology, LLC (E&A) conducted a literature review on July 9, 2015 and submitted a desktop analysis for the proposed CPT-10 Well Pad Project. Based on the results of the desktop analysis (Appendix D), the proposed project will have no effect on any recorded archeological sites, architectural resources or cemeteries listed on or determined eligible for the National Register of Historic Places. A response from the WVSHPO is currently pending.
- <u>Doddridge County Floodplain Coordinator</u> The proposed Project does not cross any Federal Emergency Management Agency (FEMA) floodplains. However, Project notification is still required to the Doddridge County Floodplain Coordinator and will be submitted by Kleinfelder.
- <u>WV Division of Highways (WVDOH)</u> Permits are required from District 4 for the proposed well pad access road and will be submitted by EQT.

FIGURES

Figure 1 Project Location Map

Figure 2 Delineation Map

Figure 3 Soils Map



FIGURE 1 PROJECT LOCATION MAP






FIGURE 2 DELINEATION MAP









FIGURE 3 SOILS MAP





APPENDIX ADelineation Data Sheets





Stream Datasheet 6

	Stream	evaluation	s should be perfo	rmed while facing	upstrear	n			
Date: _10/31/2013	EC	T Production	Company		Site	: CPT-10 \	Vell Pad		
County/State: Doddridge Co., WV	Investigators: McClung, Eva								
GPS Coordinates: LAT: 39.41233377				Data E	ntered by:	·	McClung, Ev	ran	<u> </u>
Stream Name:	UNT to Broad Run				Field ID	:	Stream 1		
Type of Stream	Epheme	rat		Predominant weather in past	24hrs	☐ 48hrs [72hrs Sho	wers (interm	ittent rain)
1. a) Approximate depth of water in stream	·		xN/A	f) Approximate hei	ght of ban	ks (chann	el depth):	Flow:	
b) Approximate width of water flow:			x_N/A	left	12 in	right	12 in		
c) Approximate width of stream: (from to	p of bank to	top of bank)	5 ft	g) OHWM Depth		2 in		N/A	
d) Approximate width of stream: (from to	e of bank to	toe of bank)	4 ft	h) OHWM Width		4.5 ft		N/A	
e) Approximate depth of pool(s):	<u>2 in</u>		N/A						
2. Is there a significant nexus to another water source? Yes a) If so, is the water source: delineated									
b) if delineated, ils	t connected (eatures:		Stream 2					
3. Plant Species Adjacent to stream (scient	ific name):								
Trees: Fagus grandifolia			Acer re	ubrum			Acer sacchar	rum	
Shrubs: Carpinus carolinian	a				_				
Understory: Polystichum acrosticho	ides				_				
4. Stream habitats present: Pools R	ıns Riffles	□ N/A	5. Aquatic Fau	ına Present? No	If Yes -	Describe:			
6. Nature of the particles in the stream bott	om:			7. Presence of:	·				
silt/clay/mudSome	cobbles	(2-10" diam.)	Most	a) naturally o	ccuring or	ganic mat	erial in stream	Occa	sional
sand <u>Little</u>	boulders	(> 10" diam.)	Some	b) logs or larg	je woody (debris in s	tream	Occa	sional
gravel Most		bedrock	Some					<u> </u>	
8. a) What is the extent of forest cover out	to 50 ft, of the	stream?	left side 50 ft.	right side 50 ft					
And what is the % of that cover?	left side	70 %	right side 70	%					
b) What is the extent of shrub cover out to 50 ft. of the stream? left side 50 ft. right side 50 ft.									
And what is the % of that cover?	left side	<u>15</u> %	right side 15	%					
9. Water Appearance: clear	If other,	explain:		10. V	Vater Odo	r non	e If other, ex	plain:	
11. Pick the description that best fits the stream bank and the channel Left Gradual/No slope (<30°) Right Gradual/No slope (<30°)									pe (<30°)
12. Describe the streamside cover. Select Present or Common 13. In the vicinity of the stream, select Present or Common									
Streamside Habitat and Land Uses									
,	Left	Right	,					Left	Right
Trees	Common	Common			Natural Str	eamside pl	ant cover degraded		
Bushes, Shrubs	Common	Common				Bank	s collapsed/eroded	Present	Present
Tall grasses, ferns	Present	Present			Garba	ge/junk adj	acent to the stream		
Lawn						Foai	n or sheen on bank		
Boulders/Rocks	Present	Present		N	lud, silt, or	sand In or	entering the stream		
Gravel/Sand						Garbage	/junk in the stream		ļ
Bare Soil	Present	Present		Ya	ard waste o	n bank (cilj	pings, leaves, etc.)	· · · · · ·	
Pavement Structures					Livestock	in or with	unrestricted access		<u> </u>
Agriculture						Activel	discharging pipes		
Other if other, explain:		.					Other pipes		
n other, explain:			J			Ditci	es entering stream		<u> </u>
Additional Comments		 .					·		
Additional Comments									



Stream Datasheet 6 Stream evaluations should be performed while facing upstream. Date: 10/31/2013 Client: EQT Production Company Site: CPT-10 Well Pad County/State: Doddridge Co., WV Investigators: McClung, Evan & Renaudin, Nathan **GPS Coordinates:** LAT: 39.41221072 LONG: -80.66598735 Data Entered by: ___ McClung, Evan Stream Name: UNT to Broad Run Field ID: Stream 2 Predominant ☐ 24hrs ☐ 48hrs ☑ 72hrs Type of Stream **Ephemeral** Showers (intermittent rain) weather in past 1. a) Approximate depth of water in stream: x N/A f) Approximate height of banks (channel depth): Flow: x_N/A b) Approximate width of water flow: 12 in right 12 in c) Approximate width of stream: (from top of bank to top of bank) g) OHWM Depth 1 in N/A d) Approximate width of stream: (from toe of bank to toe of bank) 4 ft h) OHWM Width 4.5 ft N/A e) Approximate depth of pool(s): x N/A 2. Is there a significant nexus to another water source? Yes a) If so, is the water source: delineated b) If delineated, list connected features: 3. Plant Species Adjacent to stream (scientific name): Trees: Fagus grandifolia Acer rubrum Acer saccharum Shrubs: Carpinus caroliniana Understory: Polystichum acrostichoides 4. Stream habitats present: Pools Runs Riffles ✓ N/A 5. Aquatic Fauna Present? If Yes - Describe: 6. Nature of the particles in the stream bottom: 7. Presence of: silt/clay/mud Some cobbles (2-10" diam.) Most a) naturally occuring organic material in stream Occasional Little____ sand boulders (> 10" dlam.) Some b) logs or large woody debris in stream Occasional gravel Most bedrock Some 8. a) What is the extent of forest cover out to 50 ft. of the stream? left side 50 ft. right side 50 ft. And what is the % of that cover? left side 70 % right side 70 % b) What is the extent of shrub cover out to 50 ft. of the stream? left side 50 ft. right side 50 ft. And what is the % of that cover? left side 15 % right side 15 % 9. Water Appearance: clear If other, explain: 10. Water Odor If other, explain: none 11. Pick the description that best fits the stream bank and the channel Left Gradual/No slope (<30°) Right Gradual/No slope (<30°) 12. Describe the streamside cover. Select Present or Common 13. In the vicinity of the stream, select Present or Common Streamside Habitat and Land Uses Left Right Left Right Common Common Natural Streamside plant cover degraded **Bushes, Shrubs** Common Common Banks collapsed/eroded Present <u>Pre</u>sent Tall grasses, ferns Present Present Garbage/junk adjacent to the stream Lawn Foam or sheen on bank Boulders/Rocks Present Present Mud, silt, or sand in or entering the stream Gravel/Sand Garbage/junk in the stream Bare Soll Present Present Yard waste on bank (clippings, leaves, etc.) **Pavement Structures** Livestock in or with unrestricted access Agriculture Actively discharging pipes Other Other pipes if other, explain: Ditches entering stream Additional Comments





Stream Datasheet 6

	Stream	evaluations	s should be perfo	rmed while facing upstro	eam.				
Date: 10/31/2013 Client: EQT Production Company				s	ite: <u>CPT-</u>	-1 <u>0 Well I</u>	Pad		
County/State: Doddridge Co., WV	Investigators: McClung, Evan			<u>n</u>	Rena	Renaudin, Nathan			
GPS Coordinates: LAT: 39.41033857	LONG: -80.66938896			Data Entered	by:	McClung, Evan			
ream Name: UNT to Broad Run			Field	ID:		Stream 3			
Type of Stream	Epheme	ral		Predominant 24hr	rs 🗌 48hr	s 🗸 72h	rs Shov	vers (intermi	ttent rain)
1. a) Approximate depth of water in stream:			xN/A	f) Approximate height of I	oanks (ch	annel de	epth):	Flow:	
b) Approximate width of water flow:			xN/A	left 16 in	riç	ght1	6 in		
c) Approximate width of stream: (from to		•	6 ft	g) OHWM Depth	2 ii	<u>n</u>		N/A	
d) Approximate width of stream: (from to	e of bank to t	oe of bank)	4 ft	h) OHWM Width	<u>5 f</u>	<u>ft</u>		N/A	
e) Approximate depth of pool(s):		•	xN/A	Sir.					
2. Is there a significant nexus to another w			Yes	a) If so, is the water sour	ce: <u>del</u>	lineated	_		
b) If delineated, lis	t connected f	eatures:	- ·	Stream 4			_		
3. Plant Species Adjacent to stream (scient	ific name):								
Trees: Fagus grandifolia			Acer sac	charum					
Shrubs: Carpinus carolinian									
Understory: Polystichum acrosticho	ides		<u> </u>						
4. Stream habitats present: Pools Ru	ns 🔲 Riffles	☑ N/A	5. Aquatic Fau	na Present? No If Yo	es - Descri	be:			
6. Nature of the particles in the stream bott	om:			7. Presence of:					
silt/clay/mudSome	cobbles	(2-10" diam.)	Most	a) naturally occuring	organic	material	in stream	Occa	sional
sandLittle	boulders	(> 10" diam.)	Some	b) logs or large wood	dy debris	in strea	m _	Occas	sional
gravel Most		bedrock	Some						
8. a) What is the extent of forest cover out	to 50 ft. of the	stream?	left side 50 ft.	right side 50 ft.					
And what is the % of that cover?	left side	70 %	right side 70	%					
b) What is the extent of shrub cover out	to 50 ft, of the	stream?	left side 50 ft.	right side 50 ft.					
And what is the % of that cover?	left side	15 %	right side 15	%					
9. Water Appearance: If other, explain: 10. Water Odor If other, explain: no water							o water		
11. Pick the description that best fits the st	Left Steeply sloping (>30°) Right Steeply sloping (>30°)								
12. Describe the streamside cover. Select Prese	13. In the vicinity of the	stream, s	elect Pre	sent or Commo	n				
Streamside Hab									
- [Left	Right	1					Left	Right
Trees	Common	Common		Natural		•	over degraded		
Bushes, Shrubs Tall grasses, ferns	Common Present	Common Present					llapsed/eroded	Present	Present
Lawn	Fresent	Present	1	Ga		-	t to the stream		
Boulders/Rocks	Present	Present	1	Mud eilt			sheen on bank ing the stream		·····
Gravel/Sand	riesen	7 Teserit		muu, siit			k in the stream		
Bare Soil	Present	Present	1	Yard was			s, leaves, etc.)		
Pavement Structures			1				stricted access		1
Agriculture			1				charging pipes		
Other					,	,	Other pipes		
if other, explain:					ı	Ditches e	ntering stream	" .	
· L			1			_	- ····[·
Additional Comments					*	·			
-									



Stream Datasheet 6 Stream evaluations should be performed while facing upstream. Date: 10/31/2013 Cilent: EQT Production Company Site: CPT-10 Well Pad County/State: Doddridge Co., WV Investigators: McClung, Evan & Renaudin, Nathan **GPS Coordinates:** LAT: 39.40993606 LONG: -80.66937319 Data Entered by: McClung, Evan Stream Name: UNT to Broad Run Field ID: Stream 4 Predominant ☐ 24hrs ☐ 48hrs ☑ 72hrs Type of Stream **Ephemeral** Showers (intermittent rain) weather in past 1. a) Approximate depth of water in stream: x N/A f) Approximate height of banks (channel depth): Flow: b) Approximate width of water flow: x N/A 16 in right 16 in c) Approximate width of stream: (from top of bank to top of bank) g) OHWM Depth 2 in N/A d) Approximate width of stream: (from toe of bank to toe of bank) 4 ft h) OHWM Width 4.5 ft N/A e) Approximate depth of pool(s): x N/A 2. is there a significant nexus to another water source? Yes a) If so, is the water source: delineated b) If delineated, list connected features: 3. Plant Species Adjacent to stream (scientific name): Fagus grandifolia Acer saccharum Carpinus caroliniana Shrubs: Polystichum acrostichoides 4. Stream habitats present: Pools Runs Riffles ☑ N/A 5. Aquatic Fauna Present? No If Yes - Describe: 6. Nature of the particles in the stream bottom: 7. Presence of: silt/clay/mud Some cobbles (2-10" diam.) Most a) naturally occuring organic material in stream Occasional sand Little boulders (> 10" dlam.) Some b) logs or large woody debris in stream Occasional gravel Most bedrock Some 8. a) What is the extent of forest cover out to 50 ft. of the stream? left side 50 ft. right side 50 ft. And what is the % of that cover? left side ____70 % right side __70_ % b) What is the extent of shrub cover out to 50 ft. of the stream? left side 50 ft. right side 50 ft. And what is the % of that cover? left side 15 % right side __15_ % 9. Water Appearance: If other, explain: 10. Water Odor If other, explain: no water 11. Pick the description that best fits the stream bank and the channel Left Steeply sloping (>30°) Right Steeply sloping (>30°) 12. Describe the streamside cover. Select Present or Common 13. In the vicinity of the stream, select Present or Common Streamside Habitat and Land Uses Left Right Left Right Trees Common Common Natural Streamside plant cover degraded Bushes, Shrubs Common Common Banks collapsed/eroded Present Present Present Tall grasses, ferns Present Garbage/junk adjacent to the stream Lawn Foam or sheen on bank Boulders/Rocks Present Present Mud, silt, or sand in or entering the stream Gravel/Sand Garbage/junk in the stream Bare Soil Present Present Yard waste on bank (clippings, leaves, etc.) **Pavement Structures** Livestock in or with unrestricted access Agriculture Actively discharging pipes Other pipes if other, explain: Ditches entering stream **Additional Comments**





WETLAND DETERMINATION DATA FORM - Eastern Mountains and Piedmont Region

Project/Site: CPT-10 Well Pad	City/County: Doddridge Sampling Date: 08-Jun-15					
Applicant/Owner: EQT Production Company	State: WV Sampling Point: SP 1					
Investigator(s): John Lewis	Section, Township, Range: S N/A T N/A R N/A					
Landform (hillslope, terrace, etc.): Floodplain	Local relief (concave, convex, none): concave Slope: 3.0% / 1.7 °					
	39.411098 Long.: -80.662141 Datum: NAD83					
Soil Map Unit Name: SeB - Sensabaugh silt loam, 3 to 8 percent slop						
Are climatic/hydrologic conditions on the site typical for this time of ye	V 0 N- 0					
Are Vegetation 📋 , Soil 🔲 , or Hydrology 🔲 significant	ly disturbed? Are "Normal Circumstances" present? Yes 🔾 No 🖲					
Are Vegetation 🔲 , Soil 🗌 , or Hydrology 🔲 naturally p	problematic? (If needed, explain any answers in Remarks.)					
Summary of Findings - Attach site map showing s	sampling point locations, transects, important features, etc.					
Hydrophytic Vegetation Present? Yes No						
Hydric Soil Present? Yes No	Is the Sampled Area Yes ● No ○					
Wetland Hydrology Present? Yes No	within a Wetland?					
Remarks:						
WETLAND 1 (PEM) is located on the floodplain of STREAM 6. Normal circumstances are not present due to the location of the wetland inside a residential yard. The wetland vegetation appears to have been cut possibly weeks ago as some of the vegetation is starting to recover.						
Hydrology						
Wetland Hydrology Indicators:	Secondary Indicators (minimum of two required)					
Primary Indicators (minimum of one required; check all that apply)	Surface Soil Cracks (B6)					
Surface Water (A1)	_ ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '					
High Water Table (A2)						
	neres along Living Roots (C3) Moss Trim Lines (B16)					
Water Marks (B1) Presence of Reduc	ced Iron (C4) Dry Season Water Table (C2)					
Sediment Deposits (B2) Recent Iron Reduction in Tilled Soils (C6) Crayfish Burrows (C8)						
Drift deposits (B3)						
Algal Mat or Crust (B4) Other (Explain in Remarks) Stunted or Stressed Plants (D1)						
Iron Deposits (B5)	✓ Geomorphic Position (D2)					
Inundation Visible on Aerial Imagery (B7)	Shallow Aquitard (D3)					
Water-Stained Leaves (B9)	Microtopographic Relief (D4)					
Aquatic Fauna (B13)	FAC-neutral Test (D5)					
Field Observations: Surface Water Present? Yes No Depth (inches):						
	- William Control Cont					
Water Table Present? Yes No Depth (inches):	Wetland Hydrology Present? Yes ◉ No ○					
Saturation Present? (includes capillary fringe) Yes No Depth (inches):	Treating Hydrology Presents 120 100 0					
Describe Recorded Data (stream gauge, monitoring well, aerial photo	os, previous inspections), if available:					
Remarks:						
	events, this area receives flood waters from STREAM 6. This area is also a					
concave depression in a valley bottom that would retain run-off from						
, , , , , , , , , , , , , , , , , , , ,	3					

VEGETATION (Five/Four Strata)- Use scientific names of plants. Dominant


	Dominant ———————————————————————————————————				Sampling Point: SP 1		
Tree Stratum (Plot size: 30')	Absolute % Cover	Re	ecies? ~ el.Strat. over	Indicator Status	Dominance Test worksheet:		
1			0.0%		Number of Dominant Species That are OBL, FACW, or FAC:2 (A)		
2	0		0.0%				
3			0.0%		Total Number of Dominant Species Across All Strata: 2 (B)		
4.			0.0%		(b)		
5			0.0%		Percent of dominant Species		
6	0		0.0%		That Are OBL, FACW, or FAC: 100.0% (A/B)		
7			0.0%		Prevalence Index worksheet:		
8			0.0%		Total % Cover of: Multiply by:		
Sapling-Sapling/Shrub Stratum (Plot size: 15'	Λ .	= To	otal Cover	•	OBL species <u>20</u> x 1 = <u>20</u>		
1.	. 0	\Box	0.0%		FACW species $50 \times 2 = 100$		
2		$\overline{\Box}$	0.0%		FAC species $33 \times 3 = 99$		
	~	$\overline{\Box}$	0.0%		FACU species $15 \times 4 = 60$		
3	-	$\overline{\Box}$	0.0%		UPL species $\frac{0}{x}$ x 5 = $\frac{0}{x}$		
4		$\overline{\Box}$	0.0%		Column Totals: 118 (A) 279 (B)		
6	- —	\Box	0.0%				
7	- —	\Box	0.0%				
8			0.0%		Hydrophytic Vegetation Indicators:		
9		\Box	0.0%		Rapid Test for Hydrophytic Vegetation		
10		$\overline{\Box}$	0.0% /	57	Dominance Test is > 50%		
		= T	otal Cove	/	Prevalence Index is ≤3.0 ¹		
Shrub Stratum (Plot size: 15')			1,		Morphological Adaptations ¹ (Provide supporting data in Remarks or on a separate sheet)		
1 2		\Box	0.0%		Problematic Hydrophytic Vegetation 1 (Explain)		
3	(0.0%	100	¹ Indicators of hydric soil and wetland hydrology must		
4.			0.0%	5	be present, unless disturbed or problematic.		
5	0		V0.0%		Definition of Vegetation Strata:		
6	Ò		0.0%		Four Vegetation Strata:		
7.	/ o'		\0.0%		Tree stratum – Consists of woody plants, excluding vines, 3 in.		
Herb Stratum (Plot size: 5')	19	= T(otal Cove	-	(7.6 cm) or more in diameter at breast height (DBH), regardless of height.		
1. Lysimachia nummularia	40_	V	33.9%	FACW	Sapling/shrub stratum – Consists of woody plants, excluding vines, less than 3 in. DBH and greater than 3.28 ft (1 m) tall.		
2. Arthraxon hispidus	25	\checkmark	21.2%	FAC	Herb stratum – Consists of all herbaceous (non-woody) plants,		
3. Glechoma hederacea	15		12.7%	FACU	regardless of size, and all other plants less than 3.28 ft tall.		
4. Carex lurida	15		12.7%	OBL	Woody vines – Consists of all woody vines greater than 3.28 ft		
5. Rumex crispus	8		6.8%	FAC	in height.		
6. Bidens tripartita	5		4.2%	FACW	Five Vegetation Strata:		
7. Scirpus atrovirens	5		4.2%	OBL	Tree - Woody plants, excluding woody vines, approximately 20		
8. Mentha spicata	5		4.2%	FACW	ft (6 m) or more in height and 3 in. (7.6 cm) or larger in		
9			0.0%		diameter at breast height (DBH). Sapling stratum – Consists of woody plants, excluding woody		
10			0.0%		vines, approximately 20 ft (6 m) or more in height and less		
11.	0		0.0%		than 3 in. (7.6 cm) DBH,		
12		Ш	0.0%		Shrub stratum – Consists of woody plants, excluding woody vines, approximately 3 to 20 ft (1 to 6 m) in height.		
Woody Vine Stratum (Plot size: 30')	118	= T	otal Cove	r	Herb stratum – Consists of all herbaceous (non-woody) plants,		
1	0		0.0%		Including herbaceous vines, regardless of size, and woody species, except woody vines, less than approximately 3 ft (1		
2			0.0%	-	m) in height.		
3			0.0%		Woody vines – Consists of all woody vines, regardless of		
4			0.0%		height.		
5	0_		0.0%		Hydronhytic		
6	0		0.0%		Hydrophytic Vegetation		
	0	= T	otal Cove	r	Present? Yes No		
Remarks: (Include photo numbers here or on a separate she	et.)						
Vegetation is dominated by hydrophytes and meets the dominance t	est.						
I							

^{*}Indicator suffix = National status or professional decision assigned because Regional status not defined by FWS.

Depth -		<u>Matrix</u>				<u>edox Feat</u> ı	ires		_		
(inches)	Color (%		moist)	%	Type 1	Loc2	<u>Texture</u>	Rem	arks
0-8	7.5YR	4/2	95	7.5YR	4/6	5	C	PL	Silt Loam		
8-20	7.5YR	5/2	60	7.5YR	4/6	40	С	PL	Silt Loam		
										,	
				· · · · · · · · · · · · · · · · · · ·				** *********			
										. <u></u>	
										,	
ype: C=Conc	entration. [)=Depletic	on. RM=Red	luced Matrix,	CS=Cove	red or Coat	ed Sand Gra	ins ² Loca	ation: PL=Pore Lining, M=N	latrix	
ydric Soil I		•		· · · · · ·							- C-11-3.
Histosol (A				☐ Dar	k Surface	(S7)			Indicators for Prob	-	c 30115";
Histic Epip	•					` '	(S8) (MLRA	147,148)	2 cm Muck (A10		
Black Histi	` '						MLRA 147, 1		Coast Prairie Rec	ox (A16)	
_	Sulfide (A4))				d Matrix (F2		```, ¢	(MLRA 147,148)		
	Layers (A5)				leted Mat	-	•		⊡ [√] Piedmont Floodp (MLRA 136, 147	ilain Soils (F19))
2 cm Muck						Surface (F6)	1	S)	☐ Very Shallow Da		121
_	Below Dark		A11)	☐ Dep	leted Dar	k Surface (F	₇₎		Other (Explain in		,
-	k Surface (A	•	,	Red	ox Depre	ssions (F8)	1		Outer (Explain ii	i Remarks)	
_	ck Mineral (-	N.	☐ Iron	n-Mangan	ese Masses	(F12) (LRR	N,			
MLRA 147		/ (•••		X A 136)	tom	-				
Sandy Gle	yed Matrix	(S4)		L Um	bric Surfa	ice (F13) (M	LRA 136, 1	(2)	<i>}</i>		
				Piec	dmont Flo	odplain Soil	s (F19) (ML	RA 148)	Indicators of wetland hy	hydrophytic v drology must t	egetation and ne present.
Sandy Rec	dox (S5)				£		1) (MI DA 12	7. 147)			
				Rec	Parent N	1aterial (F2)	I) (MLION 12	., ,	uniess c	isturbed or pro	Dicitiauc.
Sandy Rec	Matrix (S6)	conrod)		Rec	Parent N	faterial (F2)	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		unless c	isturbed or pro	Joiernade.
Sandy Reconstructive La	Matrix (S6)	served):		Rec	l Parent N	laterial (F21	TI THE TE		unless c	isturbed or pro	mientauc.
Sandy Rec Stripped M Stripped La Type: _N	Matrix (S6) ayer (if ob	served):		Rec	l Parent N	faterial (F21	TO CHECK 12				
Sandy Recommend Stripped Mestrictive Later Type: Name of the Name	Matrix (S6) ayer (if ob	served):	10.7	Rec	l Parent N	laterial (F21	i) (MENA 12		Hydric Soil Present?	Yes •	No O
Sandy Recommend Stripped Mestrictive Later Type: No Depth (inches)	Matrix (S6) ayer (if oboth /A hes): N/A		<u> </u>		l Parent N	faterial (F21	The second secon				
Sandy Recommend Stripped Mestrictive Lating Type: No Depth (inchese lating)	Matrix (S6) ayer (if oboth /A hes): N/A		<u> </u>		I Parent N	Material (F2)					
Sandy Recommend Stripped Mestrictive Lating Type: No Depth (inchese lating)	Matrix (S6) ayer (if oboth /A hes): N/A		<u> </u>		I Parent N	Vaterial (F2)					
Sandy Recommend Stripped Mestrictive Lating Type: No Depth (inchese lating)	Matrix (S6) ayer (if oboth /A hes): N/A		<u> </u>		I Parent N	laterial (F2)					
Sandy Reconstructive Later Type: No Depth (inches)	Matrix (S6) ayer (if oboth /A hes): N/A		<u> </u>		d Parent N	faterial (F2)					
Sandy Reconstructive Lating Type: No Depth (inches)	Matrix (S6) ayer (if oboth /A hes): N/A		<u> </u>		d Parent N	faterial (F2)					
Sandy Reconstructive Lating Type: No Depth (inches)	Matrix (S6) ayer (if observed) A hes): N/A		<u> </u>		d Parent N	faterial (F2)					
Sandy Reconstructive Lating Type: No Depth (inches)	Matrix (S6) ayer (if observed) A hes): N/A		<u> </u>		1 Parent N	laterial (F2)					
Sandy Reconstructive Lating Type: No Depth (inches)	Matrix (S6) ayer (if observed) A hes): N/A		<u> </u>		1 Parent N	faterial (F2)					
Sandy Recommend Stripped Mestrictive Later Type: _N/O Depth (inche)	Matrix (S6) ayer (if observed) A hes): N/A		<u> </u>		1 Parent N	laterial (F2)					
Sandy Recommend Stripped Mestrictive Lating Type: No Depth (inchese lating)	Matrix (S6) ayer (if observed) A hes): N/A		<u> </u>		1 Parent N	1aterial (F2)					
Sandy Recommend Stripped Mestrictive Later Type: _N/O Depth (inche)	Matrix (S6) ayer (if observed) A hes): N/A		<u> </u>		1 Parent N	1aterial (F2)					
Sandy Recommend Stripped Mestrictive Later Type: No Depth (inches)	Matrix (S6) ayer (if observed) A hes): N/A		<u> </u>		1 Parent N	laterial (F2)					
Sandy Recommend Stripped Mestrictive Lating Type: No Depth (inchese Remarks:	Matrix (S6) ayer (if observed) A hes): N/A		<u> </u>		1 Parent N	laterial (F2)					
Sandy Rec Stripped M Restrictive La Type: _N Depth (inch	Matrix (S6) ayer (if observed) A hes): N/A		<u> </u>		1 Parent N	laterial (F2)					
Sandy Rec Stripped M Restrictive La Type: _N Depth (inch	Matrix (S6) ayer (if observed) A hes): N/A		<u> </u>		1 Parent N	laterial (F2)					
Sandy Rec Stripped M Restrictive La Type: N	Matrix (S6) ayer (if oboth /A hes): N/A		<u> </u>		1 Parent N	laterial (F2)					
Sandy Recommend Stripped Mestrictive La Type: No Depth (inch	Matrix (S6) ayer (if oboth /A hes): N/A		<u> </u>		1 Parent N	laterial (F2)					
Sandy Recommend Stripped Mestrictive Lating Type: No Depth (inchese Remarks:	Matrix (S6) ayer (if oboth /A hes): N/A		<u> </u>		1 Parent N	laterial (F2)					
Sandy Rec Stripped M Restrictive La Type: _N Depth (inch	Matrix (S6) ayer (if oboth /A hes): N/A		<u> </u>		1 Parent N	laterial (F2)					

APPENDIX B

Photos of Jurisdictional Features








Photo #2: View west (downstream) of Stream 2





Photo #4: View south (downstream) of Stream 4



Photo #5: View southeast (downstream) of Stream 5






Photo #6: View northeast (upstream) of Stream 6



Photo #7: View northeast of Wetland 1



APPENDIX C Design Drawings





CPT-10 WELL PAD SITE DESIGN & CONSTRUCTION PLAN, **EROSION & SEDIMENT CONTROL PLANS**

EQT PRODUCTION COMPANY

PROPOSED TOPSOIL STOCKPILE

STOCKPILE I

CENTER POINT OUAD

PLAN REPRODUCTION WARNING THE PLANS HAVE BEEN CREATED ON ANSI D (22" x 34") SHEETS FOR REDUCTIONS, REFER TO GRAPHIC SCALE.

THE PLANS HAVE BEEN CREATED FOR FULL COLOR PLOTTING. ANY SET OF THE FLANS THAT IS NOT PLOTTED IN FULL COLOR SHALL NOT BE CONSIDERED ADEQUATE FOR CONSTRUCTION PURPOSES.

"WARRING": INFORMATION MAY BE LOST IN COPYING AND/OF CRAY SCALE PLOTTING

NAD 83 (DEGREES)

LATITUDE (N) LONGITUDE (W)

80.660625° W

80.660572° W

80,660519° W

80.660466° W

80.660413° W

80.660359° W

80 660306° W

39,413529° N

39.413530° N

39.413530° N

39.413531* N

39.413531° N

39.413532° N

39.413532° N

WELL HEAD LAYOUT

EASTING 1640597.50

1640612.50

1640627.50

1640642.50

1640657.50

1640672.50

1640687.50

WV STATE PLANE NAD 83 (FT)

NORTHING

334850 57

334850.57

334850.57

334850.57

H3-513515 334850.57

H6-513518 334850.57

H7-514143 334850.57

WELL

HEAD

H1-513513

H2-513514

H4-513516

H5-513517






Squad By: JOSHUA II. FARLEY, W.V. P.E. 8 20711

7	_	REVISIONS			
ł	REV	DESCRIPTION	DSN	CHK APP	DATE
1			F		
1					
\mathbf{I}					
1					
\mathbf{I}					
7	П	-		H	
1					
]	Н				
4	_		\vdash	\vdash	

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION





COVER PAGE & LOCATION MAP

CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA



Where energy meets innovation.

PERMITTING

PROJECT NO.	137355
ISSUE DATE	07/01/201S
CURRENT REVISIO	ж .
DESIGNED BY	AER
DRAWN BY	AER
CHECKED BY	AF
APPROVED DY	ДAF

SHEET

POSED TOPSON STOCKPILE

SOME ENGINEERS

PROPOSED SPOIL STOCKPILE 3

NORTH MERIDIAN REFERENCED TO NAD83

Commence

C 25 / 18

PROJECT CONTACTS

PROJECT OWNER

EQT PRODUCTION COMPANY CONTACT: CHRIS METZGAR 115 PROFESSIONAL PLACE BRIDGEPORT, WV 26330 304,848,0075 OFFICE

LOCATION SURVEYOR

ENCOMPASS ENERGY SERVICES, LLC CONTACT: TYLER HASTINGS 1370 WASHINGTON PIKE, SUITE 308 BRIDGEVILLE, PA 15017 412:564.5215 OFFICE

ENVIRONMENTAL/ DELINEATION BOUNDARY

KLEINFELDER CONTACT: MATTHEW ALBRIGHT 230 EXECUTIVE DRIVE. SUITE 122 CRANBERRY TOWNSHIP. PA 16066 724,772,7072 OFFICE 724,772,7079 FAX

ENGINEER OF RECORD

KLEINFELDER CONTACT: JOSH FARLEY, PE WY PE 8020711 230 EXECUTIVE DRIVE, SUITE 122 CRANBERRY TOWNSHIP, PA 16066 724.772.7072 OFFICE 724.772.7079 FAX

TOPO SURVEYOR

BLUE MOUNTAIN AERIAL MAPPING CONTACT: CRAIG FRY 11023 MASON DIXON HIGHWAY BURTON, WY 26562 304,662,2626 OFFICE 304,815,4890 CELL

	SIT	E LOCATION				
	NAD 83	(DEGREES)	UTM ZONE 17N NAD 83 (M)			
DESCRIPTION	LATITUDE (N)	LONGITUDE (W)	NORTHING	EASTING		
CENTER OF WELL PAD	39.413493° N	80.660501° W	4362718.95	529225.97		
CENTER OF COMPLETION PIT	39,417796° N	80.664784° W	4363195.12	528855.49		
CENTER OF FLOWBACK PIT	39.415813° N	80.660713° W	4362976.36	529206.76		
MAIN ACCESS ROAD ENTRANCE	39.411547° N	80.661251° W	4362502.75	529162.22		
WELL PAD ACCESS ROAD ENTRANCE	39.413638° N	80.659453° W	4362735.39	529316.13		

FLOOD CONDITIONS	
DO SITE CONSTRUCTION ACTIVITIES TAKE PLACE IN FLOODPLAIN	HO.
PERMIT NEEDED FROM COUNTY FLOODPLAIN COURDINATOR:	NO
HEC-RAS STUDY COMPLETED:	N/A
FLOODPLAIN SHOWN ON DRAWINGS:	HO
	54017C0045C
ALKEAGE OF CONSTRUCTION IN FLUCIOPLAIN:	N'A

ACCESS ROAD LENGTH (FEET)	
DESCRIPTION	FEET
MAIN ACCESS ROAD	3,100
PAD ACCESS ROAD	24
TOTAL	3,124

DESIGN CERTIFICATION
THE DRAWINGS, CONSTRUCTION NOTES, AND REFERENCE DIAGRAMS ATTACHED HERETO HAVE BEEN PREPARED IN ACCORDANCE WITH THE WEST VIRGINIA CODE OF STATE RULES, DEPARTMENT OF ENVIRONMENTAL PROTECTION, OFFICE OF OIL AND GAS \$35-4-21 AND \$35-8.

MM-103 PERMIT
EOT PRODUCTION COMPANY WILL OBTAIN AN ENCROACHMENT
PERMIT (MM-109) FROM THE WEST VIRGIMA DEPARTMENT OF
TRANSPORTATION, DIVISION OF HIGHWAYS, PRIOR TO THE
COMMENCEMENT OF CONSTRUCTION ACTIVITIES.

- 100 FROM EDGE OF DISTURBANCE TO WETLANDS, PERENNIAL STREAMS, NATURAL OR ARTIFICIAL LAKE, POND OR RESERVOIR
- 300 FROM EDGE OF DISTURBANCE TO NATURALLY REPRODUCING TROUT STREAMS 1000 FROM EDGE OF DISTURBANCE TO ANY SURFACE OR GROUND WATER INTAKE TO A PUBLIC WATER SUPPLY

WELL LOCATION RESTRICTIONS
WELL PAD IS TO COMPLY WITH WELL LOCATION RESTRICTIONS OF WY CODE 22/4A-12. THE PADS COMPLY WITH THE FOLLOWING RESTRICTIONS:
250 FROM AN EXISTING WELL OR DEVELOPED SPRING USED FOR HUMAN OR DOMESTIC ANNALS TO WELL BEING DRILLED
825 FROM AN OCCUPIED DWELLING OR BARN GREATER THAN 2500 SF USED FOR POULTRY OR DAIRY MEASURED FROM THE CENTER OF

		WELL HEAD LA	YOUT	
WELL	WV STATE PL	ANE NAD 27 (FT)	UTM ZONE 1	7N NAD 83 (N
HEAD	NORTHING	EASTING	NORTHING	EASTING
H1-513513	334814.30	1672038.29	4362723.13	529215.2
H2-513514	334814.30	1672053.29	4362723.15	529219.8
H3-513515	334814.30	1672068.29	4362723.17	529224.4
H4-513516	334814.30	1672083.29	4362723.18	529229.0
H5-513517	334814.30	1672098.29	4362723.20	529233.5
H6-513518	334814.30	1672113.29	4362723.22	529238.14
H7-514143	334814.30	1672128.29	4362723.46	529242.7
H8-514144	334814.30	1672143.29	4362723.47	529247.2

PLANE NORTH ZONE	SEE SHEET 2	
PROPOSED COMPLETION PTT		PROPOSED TOPSOL STOOGPILE 3
PROPOSED SPOIL STOCKPILE 2 PROPOSED SPOIL STOCKPILE 2 PROPOSED SPOIL STOCKPILE 3 PROPOSED SPOIL STOCKPILE 3 PROPOSED TOPSOIL STOCKPILE 3 PROPOSED TOPSOIL STOCKPILE 3 PROPOSED WELL PAD	Action	PROPOSED SPOIL STOCKPILE 1 PROPOSED TOPSOIL STOCKPILE 1 PROPOSED MAIN ACCESS ROAD 25 Taffaige Taffaige Conter Point

AFFECTED TAX PARCELS:

PAGE NO.	DESCRIPTION
1	COVER PAGE & LOCATION MAP
2	SCHEDULE OF QUANTITIES
3	NOTES
4	EXISTING CONDITIONS
5	OVERALL PLAN
6-8	SITE PLAN
9	WELL PAD CROSS SECTIONS AND PROFILE
10	FLOWBACK PIT CROSS SECTIONS AND PROFILE
11-12	COMPLETION PIT CROSS SECTIONS AND PROFILE
13-15	MAIN ACCESS ROAD CROSS SECTIONS AND PROFILE
16	CULVERT PROFILES
17-22	DETAILS

SHEET INDEX

23-25 RECLAMATION PLAN SCALE: N.T.S.

Call Interpret CALL PA ONE CALL SYSTEM TOULFREE B11

1-800-242-1776

CPT-10 WELL PAD		
ITEM DESCRIPTION	QUANTITY	UNIT
1.1 - MOBILIZATION	1	LS
2.1 - CLEARING		
2.1.A - CLEAR & GRUB (TREES, STUMPS, BRUSH)	41	AC.
2.1.B - CLEAR FELLED TIMBER & GRUB	31	AC_
3.1 - EROSION & SEDIMENT CONTROL	1.006	LF.
3.1.A - 12" COMPOST FILTER SOCK	1,205	뱌
3.1.6 - 18" COMPOST FILTER SOCK 3.1.C - 24" COMPOST FILTER SOCK	575	냰
3.1.D - 32" COMPOST FILTER SOCK	615	UF.
3.1.0 - SUPER SILT FENCE	3,780	UF.
3.1.E - ROCK CONSTRUCTION ENTRANCE	1	EA
3.1.F - R-3 RIP RAP (ROCK FILTER OUTLETS)	10	TONS
3.1.G - AASHTO #57 STONE (ROCK FILTER OUTLETS)	5	TONS
3.1.H - R-3 RIP RAP (ROCK CHECK DAMS)	27	TONS
3.1.L - EROSION CONTROL MATTING - NAG C125BN	30,781	SY
3.1.L -EROSION CONTROL MATTING -NAG C350	30,875	SY
A.1 - DITCH LINING		
4.1.A - NORTH AMERICAN GREEN C125BN	1,589	SY
4,1A · R-3	1,787	SY
4.1.A - R-4	676	SY
5.1 - AGGREGATE SURFACING		man -
5.1.A.1 - WELL PAD I/3 - #6 LIMESTONE (8" THICK)	6,485	TONS
5.1.A.2 - WELL PAD 0.75" OR 1.5" CRUSHER RUN LIMESTON (2" THICK)	2,671	TONS
5.1.A.3 - WELL PAD GEOTEXTILE FABRIC (US 200)	25,431	SY
5.1.8.1 - ACCESS ROADS #3 - #6 LIMESTONE (6" THICK)	5,424	TONS
5.1.B.2 - ACCESS ROADS 0.75" OR 1.5" CRUSHER RUN LIMESTON (2" THICK)	2,234	TONS
5.1.B.3 - ACCESS ROADS GEOTEXTILE FABRIC (US 200)	21,269	SY
5.1.C.1 - TRUCK QUEUES #3 - #6 LIMESTONE (8" THICK)	627	TONS
5.1,C.2 - TRUCK QUEUES 0.75" OR 1.5" CRUSHER RUN LIMESTON (2" THCK)	259	TONS
5.1.C.3 - TRUCK QUEUES GEOTEXTILE FABRIC (US 200)	2,458	SY_
8.1 - SEED & MULCH	30.2	AC
6.1.A - SITE SEEDING (LIME, FERTILIZER, SEEDING, AND HYDRO-MULCH WTACK (HYC-2 OR EQUAL))		AC.
6.1.B - RECLAMATION SEEDING (UME, FERTILIZER, SEEDING, AND HYDRO-MULCH w/TACK (HYC-2 OF	(EGGPL)) 1 1.5	~
7.1.4 - TOPSOIL (ESTIMATED AT 1' DEEP)	30,402	CY
7.1.B -WELL PAD EXCAVATION (CUT TO FILL)	32,642	CY
7.1.C -WELL PAD EXCAVATION (EXPORT TO SPOIL AREA)	41,490	CY
7.1.D - COMPLETION PIT & TRUCK QUEUE EXCAVATION (CUT TO FILL)	67,537	CY
7.1.E - COMPLETION PIT & TRUCK QUEUE EXCAVATION (IMPORT FROM SPOIL AREA)	18,337	CY
7.1.F - FLOWBACK PIT & TRUCK QUEUE EXCAVATION (CUT TO FILL)	1,023	CY
7.1.G - FLOWBACK PIT & TRUCK QUEUE EXCAVATION (EXPORT TO SPOIL AREA)	36,779	CY
7.1.H - ACCESS ROADS EXCAVATION (CUT TO FILL)	17,240	CY
7.1.1 - ACCESS ROADS EXCAVATION (IMPORT FROM SPOIL AREA)	2,742	CY
8.1 - PAD		
8.1.A - CONTAINMENT BERM	7,060	CY
8.1.B - SUMPS - (SEE "SUMP SYSTEM DETAIL")	8	EA
8.1.C - 4" PVC SUMP DRAIN PIPE - (SEE "SUMP SYSTEM DETAIL")	100	UF
8.1.D - PVC PIPE OUTLET PROTECTION - R-3 RIP RAP	68	TONS
R1 - CROSS DRAIN CULVERTS		
9,1.A - 18" HDPE	370	LF
9.1.8 · FLARED END SECTION	5	EA
9.1.C - R-3 RIP RAP (INLETS/OUTLETS)	20	TONS
9.1.E · R-4 RIP RAP (INLETS/OUTLETS)	41	TONS
9.1.G - R-6 RIP RAP (INLETS/OUTLETS)	51	TONS
9.1.D - AASHTO #57 STONE (INLETS)	91	TONS
0.1 - PIT	T 0400 1	SY
10.1.A - PRIMARY LINER (60 ML)	9,122	
10.1.8 - NON-WOVEN GEOTEXTILE FABRIC CUSHION (1602 FELT)	9,122	SY
1.1 FRENCH DRAIN	1,248	LF
11.1.A - F PERFORATED PIPE 11.1.B - GEOTEXTILE FABRIC	7,488	SY
11.1.8 - GEOTEXTILE FABRIC 11.1.C - #57 STONE	114	TONS

DESCRIPTION							
DESCRIPTION IACRES PARCELS	LIMITS OF DISTURBANCE						
MORRES PARCES COMPLETION PIT 2.14 COSTAL FOREST COSTAL FOREST RESOURCES MINH ACCESS ROAD 7.75 FLOWBACK PIT & TURN AROUND 2.31 COMPLETION PIT & TURN AROUND 4.51 SPOIL STOCKPILE 2.67 SPOIL STOCKPILE 2.67 SPOIL STOCKPILE 2.67 SPOIL STOCKPILE 2.27 SPOIL STOCKPILE 2.27 JAMES & MA STOCKPILE 3.22 SPOIL STOCKPILE 3.22 S	DESCRIPTION						
COMPLETION PT 2.14 MAN ACCESS ROAD 7.75 F.WELL PAD 7.47 FLOWBACK PT & TURN AROUND 2.51 COMPLETION PT & TURN AROUND 4.51 SPOLL STOCKPILE 1 3.54 SPOLL STOCKPILE 2 2.67 SPOLL STOCKPILE 2 2.67 SPOLL STOCKPILE 3 0.22 SPOLL STOCKPILE 4 0.11	DEDGRAFIRON	(ACRES)					
WELL PAD 7.47	COMPLETION PIT	2.14					
FLOWBACK PT & TURN AROUND 2.51	MAIN ACCESS ROAD	7.75					
COMPLETION PT & TURN AROUND 4.51 SPOIL, STOCKPILE 3.84 SPOIL STOCKPILE 2.67 SPOIL STOCKPILE 0.22 SPOIL STOCKPILE 0.11 STOCKP	WELL PAD	7.47					
SPOIL STOCKPILE 1							
SPOIL STOCKPILE 2 2.67 HAYES SHRLEY	COMPLETION PIT & TURN AROUND	4.51					
SPOIL STOCKPILE 2 2.67 SPOIL STOCKPILE 3 0.22 SPOIL STOCKPILE 4 0.11	SPOIL STOCKPILE 1	3.84	HAVES SHIPLEY				
SPOIL STOCKPILE 3 0.22 SPOIL STOCKPILE 4 0.11	SPOIL STOCKPILE 2	2.67					
	SPOIL STOCKPILE 3	0.22	JAMES & RIA				
TODGOU STOCKBUE 1 3.51	SPOIL STOCKPILE 4	0.11					
	TOPSOIL STOCKPILE 1	3.51					
TOPSOIL STOCKPILE 2 1.56	TOPSOIL STOCKPILE 2	1.56					
TOPSOIL STOCKPILE 3 0.71	TOPSOIL STOCKPILE 3	0.71					
COMPLETION PIT 3.66 ASH SAMUEL G ET	COMPLETION PIT	3.66	ASH SAMUEL G ET UX				
TOTAL 40.46		40.46					
TOTAL WOODED ACRES DISTURBED 30.88	TOTAL WOODED ACRES DISTURBED	30.88					
TOTAL LINEAR FOOTAGE OF MAIN 3.100	TOTAL LINEAR FOOTAGE OF MAIN	3 100					
ACCESS ROAD		3.100					
TOTAL LINEAR FOOTAGE OF WELL PAD 24	TOTAL LINEAR FOOTAGE OF WELL PAD	24					
ACCESS ROAD 24	ACCESS ROAD	24					

GRADING		
CUT SLOPE	2:1	
FILL SLOPE	2:1	
SPOIL SWELL FACTOR	20	6
WELL PAD ELEVATION	969	7
FLOWBACK PIT BERM ELEVATION	109	9"
COMPLETION PIT BERM ELEVATION	117	9"
UNLESS OTHERWISE NOTE)	
PAD/ROAD CUT/ FILL SLOPES		Z:1
EQUIPMENT PAD & ACCESS ROADS		2
COMPLETION & FLOWBACK PIT INTERIOR SLO	OPES	3
COMPLETION & FLOWBACK PIT EXTERIOR SLI	OPES	2
SPOIL STOCKPILES		2
TOPSOIL STOCKPILES		3

FL	FLOWBACK PIT VOLUMES							
Bevation	Barrels	Gallons	Acre-Ft	Unincised Acre-Ft	Incised Acre-Ft			
1081 (Bottom)	0	0	0.000	0,000	0.000			
1082	903	37,908	0.116	0.000	0.116			
1083	1,983	83,277	0.256	0.000	0.256			
1084	3,254	138,650	0.419	0.000	0.419			
1085	4,728	198,570	0.609	0.000	0.609			
1086	6,419	269,579	0.827	0.000	0.827			
1087	8,339	350,219	1.075	0.000	1.075			
1088	10,501	441,036	1.353	0.000	1.353			
1089	12,918	542,573	1.665	0.000	1.665			
1090	15,604	655,368	2.011	0.000	2.011			
1091	18,571	779,968	2.394	0.000	2.394			
1092	21,831	918,917	2.814	0.000	2.814			
1093	25,399	1,066,756	3.274	0.000	3.274			
1094	29,286	1,230,026	3.775	0.000	3,775			
1095	33,506	1,407,273	4.319	0.000	4.319			
1096	38,072	1,599,040	4.907	0.000	4.907			
1097 (Pit Capacity)	42,997	1,805,869	5.542	0.635	4.907			
1098	48,293	2,028,302	6.225	1.317	4,907			
1099 (Top Berm)	53,978	2,268,882	6,957	2.050	4,907			
* 1 Barre	I JUS Petro	deum) = 42	gallons (L	IS (iquid)				

col	APLETION I	COMPLETION PIT VOLUMES								
Devation	Barrets	Gallons	Acre-Ft	Unincised Acre-Ft	Acre-Ft					
1160 (Bottom)	0	o	0.000	0.000	0.000					
1161	3,136	131,717	0.404	0.000	0.404					
1162	6,769	284,290	0.872	0.000	0.872					
1163	10,910	458,230	1.406	0.000	1.406					
1164	15.573	654,048	2.007	0.000	2.007					
1165	20,768	872,251	2,677	0.000	2.677					
1168	26,508	1,113,362	3.417	0.000	3.417					
1167	32,806	1,377,863	4.229	0.000	4,229					
1168	39,674	1,686,293	5,114	0.000	5.114					
1169	47,123	1,979,151	6.074	0.000	6.074					
1170	55,165	2,316,949	7.110	1.037	6.074					
1171	63,814	2,680,199	8.225	2.151	6.074					
1172	73,081	3,069,411	9.420	3.346	6.074					
1173	82,978	3,485,092	10.695	4.622	6.074					
1174	93,518	3,927,759	12.054	5.980	6.074					
1175	104,712	4,397,921	13.497	7.423	6.074					
1176	118,573	4,896,086	15.026	8.952	6.074					
1177 (Pit Capacity)	129,114	5,422,767	16.642	10.568	6.074					
1178	142,345	5,978,473	18.347	12.273	6.074					
1179 (Top Berm)	156,279	6,583,715	20.143	14.069	6.074					

				QUANTITIES				
DESCRIPTION	CUTICN	FILL (CY)	BASE (CY)	TOPSOIL (CY)	SPOIL (CY)	BORROW (CY)	MAX. SLOPE	LENGTH OF SLOPE
WELL PAD	74132	32642	4021	8477	37034	NA	N/A	N/A
FLOWBACK PIT	36802	1023	716	2819	33675	N/A	N/A	N/A
COMPLETION PIT	67537	85874	1429	6949	N/A	23858	NA	WA
PRIMARY ACCESS ROAD	13410	19962	1908	7079	N/A	11745	16.99%	1520*
WELL PAD ACCESS ROAD	3870	0	15	1 11	3874	N/A	N/A	N/A
TOPSOIL STOCKPILE 1	0	21589	0	0	N/A	21689	N/A	N/A
TOPSOIL STOCKPILE 2	0	2926	0	0	N/A	2928	N/A	N/A
TOPSOIL STOCKPILE 3	0	1103	0	. 0	N/A	1103	N/A	N/A
SPOIL STOCKPILE 1	Ó	31093	0	0	NYA	31093	N/A	N/A
SPOIL STOCKPILE 2	1 0	1738	0	1 0	N'A	1738	N/A	N'A
SPOIL STOCKPILE 3"	0	3570	0		N/A	3570	N/A	NA
SPOIL STOCKPILE 4"	0	1560	0	0	N/A	1560	H/A	WA
TOTALS	195751	203200	8087	25335	74584	99281	N/A	N/A
	TOT	AL EXPOR	TICY	63	,			

TOTAL EXPORT (CY) 637

SPOIL STOCKPILES 3 & 4 WILL SE BUILT PRIOR TO CONSTRUCTION OF TOPSOIL STOCKPILE 1.
CONSTRUCTION SEQUENCING MUST SE EVALUATED

KLEINFELDER
Bright People. Right Solutions.



8	grand By: JOSHUA HL FARLEY, W.V.	P.E. 8	20711	
	REVISIONS			
æ	DESCRIPTION		CHK	DATE
į	-		APP	
١,	REVISED SCHEDULE OF		.NF	7721/2015
·	QUANTITIES (11.1.C)	MOV	AF	
		_	L	Į .
		_	_	
		L	<u> </u>	ļ
				<u> </u>
		Т		
•		厂		ŀ
		1		
		$\overline{}$		
		T		
		\Box		
		т	_	
		г		
$\overline{}$		Т		
l		\vdash		
$\overline{}$			_	
ı	l	_	i	

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

SCALE VERIFICATION LINCH

OROGNAL ORAWING SIZE IS 22 # 34

SCHEDULE OF QUANTITIES

CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA



Where energy meets innovation.

PERMITTING

PROJECT NO. 137355
ISSUE DATE 07/01/2015
CURRENT REVISION .
DESIGNED BY AER
DRAWN BY AER
CHECKED BY AF
APPROVED BY ,AF

WEST VIRGINIA 811 UTILITY RESPONSE STATUS	
TICKET #1421253047 THRU SEPTEMBER 4, 2014	

	taility Owner	Utility Contact/Responder Information			Utility	Utility Type	Utility Specifications	Notes
Utility Code	usiny Owner	Name	Number	E-Mail	Response	O(MIT) 19De	(diameter, pole number(s), etc.)	11023
AC.	Frontier Communications (Farmerly Verizon)	÷			Clear	Phone		•
CCS	Columbia Gas Transmission - Clarksburg		1-800-835-7191	inthretaop@nisource.com	Clear	ä		
EQW560	EQT Gathering	-			No Response	ä		•
MPC	Firstenergy Corp		-		Clear	Electric		

GENERAL NOTES

- EGT PRODUCTION COMPANY WILL OBTAIN AN ENCROACHMENT PERMIT (FORM MIN-199) FROM THE WEST YIRGINIA DEPARTMENT OF TRANSPORTATION DYNGON OF INGRIVANS, PROR TO COMMENCEMENT OF CONSTRUCTION ACTIVITIES.
- IN DECEMBER FOUND BETWEEN THE GOWINGS AND DESCRIPTIONES AND DITE CONDITIONS ON ANY RECOGNITIONS ON ANY RECOGNITIONS CAN RECOURTE AN EXPONENCE OF SPECIAL OTHERS CHAIL BE RECOGNITION FOR EXPONENCE IN THE PROPERTY OF RECOGNITIONS OF ARRESTITIES SHALL BE ONE AT THE CONTRACTION AFTER THE DECOMPTION OF SUCH DESCRIPTIONES.
- WORK ON THIS PROJECT SHALL CONFORM TO THE LATEST EDITIONS OF THE WEST VIRGIMA DEPARTMENT OF EMPROMENTAL PROTECTION (WINDER) EROSION AND SEZIMENT CONTROL SEST MANAGEMENT PRACTICE HANDROOK, IN THE EVENT OF CONFLICT SERVICE HANDROOK IN THE EVENT OF CONFLICT SERVICENT HIS LOOKERY.
- THE CONTRACTOR IS RESPONSIBLE FOR LOCATION AS ALL PUBLIC OR PRIVATE TRUTHERS WHO HE IN OR ADMICIST TO THE CONTRACTOR IS RESPONSIBLE FOR LOCATION ATTE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE REPRIVAT AT HIS ON HER EXPENSE OF ALL EXISTING UTILITIES DAMACED DURING CONSTRUCTION SHALL FOR THE PUBLIC FOR THE REPRIVAT AT HIS ON HER EXPENSES. OF ALL EXISTING UTILITIES DAMACED DURING CONSTRUCTION SHALL DALL MESS UTILITY AT 1400-144-1448.
- INSTALLATION OF STORM RIPE SHALL BE IN CONFORMANCE WITH THESE DRAWINGS,
- ALL MITERIALS USED FOR RILL OR BACK RILL SHALL BE FREE OF WOOD, ROOTS, ROCKS, BOULDERS OR ANY OTHER NON-COMPACTABLE SOL, TIME IMPERIALS, UNSAITISFACTORY MATERIALS ALSO INQUIDE MAN IMPOERILLS AND REPUSE DEBYS DERIVED FROM ANY SOURCE.
- MITTERES (SEE) TO THE LANGARD DEVANUES STREAMED HELTER TESONED THE ANY CORE DEPOSITION FOR LINE AND ADMINISTRATION OF ANY CORE DEPOSITION FOR LINE AND ADMINISTRATION OF ANY CORE DEPOSITION FOR ANY C
- FILL SHALL BE PLACED IN LIFTS AT A MAXIMUM UNCOMPACTED DEPTH OF 12" WITH SQL FREE FROM AGGREGATES EXCEEDING 6".
- ALL TEST RESULTS SHALL BE SUBMITTED TO THE ENGINEER FAILURE TO CONDUCT DENSITY TESTS SHALL BE CAUSE FOR NON-ACCEPTANCE OF THE FACILITY. TESTS SHALL BE CONDUCTED AT THE SOLE COST OF THE CONTRACTOR OR HIS ACENT.
- A PRE-CONSTRUCTION CONFERENCE SHALL BE HELD PRIOR TO THE START OF CONSTRUCTION.
- SATISFACTORY MATERIALS FOR USE AS PELL FOR PAD AREAS INCLUDE IMPERIALS CLASSIFIED HASTIM D-HEF AS GW, GP, GM, GC, SW, SP, SM, SC, ML, AND CO. GROUPS. THE MOSTURE CONTINENT SIMIL SE CONTINUED WITHIN FLUS ON HIMES M, GP THE CHTIGAN TO ACREDITE TO COMPAND, GENERALLY, MASTIM-STACTORY METROL SHOULD MEMBER ALL ASSESSED HAS MADE PAIR JAP JC, ML, ML, QL, OH AND ANY SIGN. TO WET TO FAIRLY RECONSTRUCTION, CH AND MH SIGN, SW SE (SES) SHARED'T TO APPRICAVE, GF THE MEMORIES SCALES SHALL WHICH AMBRIAND FOR STRETS OF SERVICE PRE ATTAIN COME AND MAD HALL HAVE A PASSIONT MOST LISTS THAN THE STATE OF THE STAT
- CONTRACTOR SHALL DEVELOP A GENERIC GROUNDWATER PROTECTION PLAN (GPP), SUBLITTAL TO WYDEP IS NOT REQUIRED, THE GROUNDWATER PROTECTION PLAN SHALL BE ADNERED TO DURING CONSTRUCTION.
- 1. NO ROCK FILL LIFTS SHALL BE GREATER THAN 36".

EROSION & SEDIMENT CONTROL NARRATIVE

- . PROJECT DESCRIPTION: THE PURPOSE OF THE PROJECT IS TO GRADE HAD RETAIL BEFORDOW AND RETRIEBENT CONTROL MEASURES, IN PREPARATION FOR THE CONSTITUTION OF A MITHAU LAW WELL AND COUNT FOURT ALL DOCUMENTS COUNTY, WEST WISCOBLE, THE CONSTITUCTION INCLUDES THIS ACCESS PROJEC, ONE WELL PAUL ONE FLOWEACK PIT, ONE COMPLETION PIT, STORM WATER CONTROLS AND PROJECTIVITY OF THE PROJECTION PIT, STORM WATER CONTROLS AND PROJECTIVITY OF THE PROJECTION PIT, STORM WATER CONTROLS AND PROJECTIVITY OF THE PROJECTIVITY OF
- EXISTING SITE CONDITIONS: THE EXISTING SITE IS PREDOMINATELY WOODS, NO EROSION IS NOTICED ON SITE, OR IN ANY NATURAL
- ADJACENT PROPERTY: THE SITE IS BORDERED BY WOODS.
- SOLS: NO SOL STUDIES OR SUBSURFACE INVESTIGATIONS WERE PERFORMED FOR THIS PROJECT,
- OFF SITE AREAS: THERE SHALL BE NO BORROW AREA OUTSIDE OF THE PROPOSED GRADING AND CONSTRUCTION AREA.
- CLEARING OF VEGETATION SHOULD BE KEPT TO THE MINIMAN NECESSARY FOR CONSTRUCTION PLUS THE INSTALLATION OF SEDMENT
- CESTION, BEDGEN ARREA MENTIONANCE, ALL Y TE ACMS AND RESEARCH, DETOCKS AND DETENT CONTROLS SHALL BE COVERED FORTICLE RESIDENT ARREAS A THESE, AREAS ONLY, SEE MICHIGINED EMERITARIES OF ANY AND AFFEE FOR AMENIFAL OF ASSETTION GREATER, THE LOCAL GOVERNMEN AUTHORIST WILL HAVE THE AUTHORITY TO RESOLUCION THE PLACE SHEET OF ACCORDINAL CONTROL MEASURES OF HEESE AREASY IT RESOLUCIONS EVENDED FOR DEPOSITIONS THAT THE OWNER HALLOS AREA CONTROL MEASURES OF HEESE AREASY IT RESOLUCIONS TOWARD CORRESTORIES THAT THE OWNER AND ASSETTION OF THE OWNER HALLOS AREA THE OWNER AND ASSETTION OF THE OWNER AND ASSETTION OF THE OWNER ASSETTION OF THE OWNER AND ASSETTION OF THE OWNER ASSETTION OWNER ASSETTION OF THE OWNER ASSETTION OWNER ASSETTION OF THE OWNER ASSETTION OWNER ASSETTION OWNER ASSETTION OWNER ASSETTION OWNER ASSETTION OWNE
- BROSON WAS DEBOOK OF CONTROL MANAGES, HELES CHEEKS CHECKNES WOOLTD, MA VICETATIVE AND STRUCTUM, DROSON HIGH SECREPT CHAMPION PROFINEDS BANK IS CONSTRUCTION MONTHARPO ACCORDING TO MANAGE ATTEMBOOKS AND SECREPTATIONS OF THE CURRENT WEST VIRSION BROSON AND SECREPT CONTROL BEST MANAGEMENT PRACTICE MANAGE. FOR CONTRACTION SHALL CHAMPION OF THE MANAGE, FOR THE WHOOP PRESSET MAY CONSTRUCT ALL OWERS BANKS ON THE STANDARDS OF THE MANAGE AND ALL SEA ARRESTED TO MAKE SO THE PROVISE WAYNED OR APPROVED BY A VARANCE, EXE PLANS FOR ALL PROVIDED BOSON AND SECREPT CONTROL MANAGES.
- STRUCTURAL PRACTICES:

 DYNERSON DITCHES WILL BE CONSTRUCTED AS SHOWN ON THE PLANS.

 DUTLET ROTOECTORE WILL BE CONSTRUCTED AS SHOWN ON THE PLANS.

 FLIER SOCIOSUPER SILT FENCE: WILL BE CONSTRUCTED AS SHOWN ON THE PLANS.
- VEGETATIVE PRACTICE TO PSOLUMO: TO PSOLUMO: REPORD A RESIDENCE DIAS SHOWN ON THE PLANS, LPON
 THE COMMERTION OF THE PROJECT, LOYDOX WILL BE STREPPED FROM THE SITE AND STOCKPUS AT A MEMBRAN DEFIT OF INDOCE.

 THE SITE AND STREPPED FROM THE STREPPED FROM THE PROJECT OF THE SITE AND - NAMESIEST STRATEGIS: CONSTRUCTION MILL SE SCRUENCES DE THAT GRADNIC OPERATIONS MILL SEGRI AND DER AS SCONLAS POSSELE. THE DIS REPRIMITISMENT ONLE SE ESPONICIEUR DE RIFE HER THATALATION AND MAINTHAMPHANCE OF ALL ESTEDIAM HID SEDMENT CONTROL ME-CURES AFTER ACHIEVERA ACECULATE STRAIGATION THE TEMPORATY FORSION AND SEDMENT CONTROLS SMULL SE ROUNDED AND ANY AREAS DESTRIPED CURES THE PROPERCES SMULL SE STRAIGUED.
- ERMANENT STABILIZATION; ALL AREAS LEFT UNCOVERED BY EITHER BUILDINGS OR PAVEMENT SHALL BE STABILIZED WITH FRAMMENT SEEDING BANEDIATIELY FOLLOWING FRICH GRADING AND WITHIN 7 DAYS, AT NO TIME SHALL LAND LAY DORWANT FOR
- WATERWARE AND THER COMBIDERATIONS AND CRICIAD WATER PROTECTION ALL EROSION AND SEDERAT CONTROL MEASURES WILL BE COCKED ONLY AND ATTER MACH RANGE (OF COMMON THE WATER MACH RANGE). OR SHOWN OF HOME THE CONTROL WAS READ WATER MACH RANGE OF THE WATER WATER MACH RANGE OF THE WATER
GENERAL EROSION & SEDIMENT CONTROL NOTES

- THE CONTRACTOR SHALL ARRANGE FOR A PRE-CONSTRUCTION CONFERENCE WITH THE APPROPRIATE EROSION AND SECURENT CONTROL INSPECTOR ALMOURS PROR TO BEGINNING WORK
- ALL EROSION CONTROL DEVICES AS SHOWN OR AS REQUIRED, ARE TO BE CONSTRUCTED TO THE CURRENT STANDARDS AND SPECIFICATIONS OF THE WEST VIRGINIA EROSION AND SEDIMENT CONTROL BEST MANAGEMENT PRACTICE MANUAL AND ARE TO BE
- EROSION AND SEDIMENT CONTROL WEASURES SHALL BE WANTAINED CONTINUIOUSLY, RELOCATED WHEN AND AS NECESSARY AND SHALL BE OVECKED AFTER EVERY RAWRALL SEDIED AREAS SHALL BE OVECKED REGULARLY AND SHALL BE WATERED, FERTILIZED, RESEEDED AND MULTONED AS RECESSARY TO OUTLAND ADDRESS TATION OF GRASS.
- ALL DRAIN INLETS SHALL BE PROTECTED FROM SILTATION, INSPFECTIVE PROTECTION DEVICES SHALL BE IMMEDIATELY REPLACED AND THE INLET CLEANED, FLUSHING IS NOT AN ACCEPTABLE METHOD OF CLEANING.
 - PERSONNENT OF TEXTOCAL FOR STORE LANDON DALL SE APPLIED TO CORRECT AREA LATTICE STATE OUT A LYTE AT THE OWN DALES. SECORD DO NAM PROTICE OF THE STATE LINEAGONEY DES STREAL AT THE APPLIED THE STATE OF THE OWN TO THE STATE OWN TO THE STATE OWN TO THE STATE OWN TO THE APPLIED THAT THE STATE OWN TO THE AT THAT CONTROL BUT THE SERVICE OF THE APPLIED TO APPLIED THAT SECOND THE OWN THAT IS ANY S. PERMANENT AT A REAL BUT AND A STREAM THAT THE APPLIED THAT THE APPLIED THAT THE APPLIED THAT THE APPLIED THAT THE AT THE APPLIED THAT THE AT THE AT THE APPLIED THAT THE AT THE AT THE APPLIED THAT THE AT THE ATTENT AND THE ATTENT AT THE ATT
- DURING CONSTRUCTION OF THE PROJECT, SOIL STOCKPILES SHALL SE STABILIZED OR PROTECTED WITH SEI DEWICES,
- SECURENT GASINS AND TRAPS, PERSISTER DIKES, SECURENT BARGERS AND OTHER MEASURES INTENDED TO TRAP SECURENT SHALL BE CONSTRUCTED AS A FIRST STEP IN ANY LAND DISTURBING ACTIVITY AND SHALL BE MADE FUNCTIONAL BEFORE UPSLOPE LAND DISTURBINGE THAS PLACE.
- STABILIZATION MEASURES SHALL BE APPLIED TO EARTHEN STRUCTURES SUCH AS IMPOUNDMENTS, DIKES AND DIVERSIONS MADIED THE RISTALLATION.
- ALL TEMPORATY EXCOUNT AND SECOND IT CONTING, MEASURES DAYL BE REMOVED WITHIN 30 MAY AFTER THE TEMPORARY MEASURES ARE NO LOWER MEETER, DAIS SO INFÉRINCE ANTINOSEME OF THE REMOVED TEMPORATION TO SECOND TO SECOND THE CENTRED SCAL AREAS RESALTION FROM THE DESPOSITION OF TEMPORARY MEASURES SHALL BE PERMAMENTLY STABILIZED TO PREVENT REFINED FROM SECOND TEMPORARY MEASURES SHALL BE PERMAMENTLY STABILIZED TO PREVENT ARRIVED TO THE SECOND TEMPORARY MEASURES SHALL BE PERMAMENTLY STABILIZED TO PREVENT ARRIVED TO THE SECOND TEMPORARY MEASURES SHALL BE PERMAMENTLY STABILIZED TO PREVENT ARRIVED TO THE SECOND TEMPORARY MEASURES SHALL BE PERMAMENTLY STABILIZED TO PREVENT ARRIVED TO THE SECOND TEMPORARY MEASURES SHALL BE PERMAMENTLY STABILIZED TO PREVENT ARRIVED TO THE SECOND TEMPORARY MEASURES SHALL BE REMAMENTLY STABILIZED TO PREVENT ARRIVED TO THE SECOND TEMPORARY MEASURES SHALL BE REMAMENT.
- NO SERVICH TRACKING ON THE ROLDWAY IS ALLOWED, IN THE EVENT THAT SEDMENT IS INMOVERTEATLY TRACKED ONTO THE ROAD THE ROAD SHALL BE CLEAVED TROUGHOUT IN THE END OF EACH HAVE SEALURE THALL BE REMOVED FROM ROAD SEY SOUTHING OR ROAD PROVED AND SHALL BE REMOVED FROM ROAD SEY SOUTHING OR ROAD PROVED AND SHALL BE REMOVED THE ROAD OF SEALURE THAT TO THE STORM COMMENT OF THE ROAD OF SEALURE AND ALLOWED OF STREET WASHING OF SEALURE AND ALLOWED AND ALLOWED OF STREET WASHING OF SEALURE AND ALLOWED OF STREET WASHING OF STR
- ALL DISTURBED AREAS NOT PAVED OR BUILT UPON SHALL BE HYDRO-SEEDED AND FERTULZED, PERFORM PERMANENT TOP SORLING. SEEDEND AND FERTULZING AS SOON AFTER FINSH GRADING AS POSSIBLE. SEEDING SHALL COMPLY WITH THE FOLLOWING:
- TOPSOIL 4 INCH MINIMUM FOR PERMANENT TURF.
- FERTILIZER 500 LBS. PER ACKE OF 10-20-20 FERTILIZER OR EQUIVALENT POUNDAGE OF DIFFERENT ANALYSIS. WORK INTO SOIL, PRIOR TO SERENGE.
- LIME (PERMANENT SEEDING) AGRICULTURAL LIME SPREAD AT RATE OF 4 TONS PER ACRE, WORK INTO SOIL PRIOR TO SEEDING.
- MULCH OR EROSION CONTROL BLANKET (ECB) WOOD FIBER OR CHOPPED STRAW AT RATE OF 2 TONS PER ACRE, HYDRO-ARUCH AT RATE OF 20 BALES PER ACRE, ECB SHALL BE PER PLANS.

SEQUENCE OF 8MP INSTALLATION AND REMOVAL

CONSTRUCTION MUST BE IN ACCOMMENCE WITH THE FOLLOWING SECURING. THIS SECURING B DESIGNED TO MINIMATE SELL EFFICION DEVALUATION FROM THE RELATIVE ORDER OF EFFICIENT AND RESTMENTING DIVINION WHICH THE RELATIVE ORDER OF EFFICIENT AND RESTMENTING DIVINION WHILE ALL LOWER.

THE STREAM OF AUTHORISM ACTIVITIES FOR THE PROJECT OF A COMMENT OF THE WORK REQUIRED. ALL WORK ONLL GO COMMENTED IN ACCORDANCE WITH COMMENT STREAMS OF MEST RESTAURCH DESTRUCTION OF THE WORK REQUIRED. ALL WORK ONLL GO COMMENTED IN A COMMENT STREAMS OF THE WEST RESTAURCH DESTRUCTION OF EMPLOYMENT AND PROTECTION REGULATIONS AND ALL DIVERS AND PLANE FEDERAL, STATE OR LOCAL PROJECTIONS OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PLANE FEDERAL STATE OR LOCAL PROJECTION OF THE WORK REPORTED AND PL

THE AMPROVED EROSON AND SEQUENTATION CONTROL, PLANFOCULODIS THE SQLE EROSION CONTROL DRAWINGS SHALL BE AVAILABLE ON SITE AT ALL THES DURNING ENTH DISTURBANCE. THE APPROVED DISCRIPTION OF STREAMINE

(I) ON STEAT ALL THE DURING BERTHOUS TURBANCE

(II) ON STEAT ALL THE DURING BERTHOUS TURBANCE

(III) ON STEAT ALL THE DURING BERTHOUS TURBANCE RUNN'ALL RUND'S EVENT. ANY NECESSARY REPARS MIST BE MADE

ALL BURY SWALL BE INSPECTED AFTER EACH MEASURANCE RUNN'ALL RUND'S EVENT. ANY NECESSARY REPARS MIST BE MADE

ALL BURY SWALL BE INSPECTED AFTER AND EFFICIENT OPENITION.

(II) ON THE PROVINCE OF THE CONTRACT OF THE PROVINCE O

- A PRE-CONSTRUCTION CONFERENCE WILL BE HELD ON SITE WITH CONTRACTOR TO REVIEW THE CONSTRUCTION DRAWINGS AND PROVIDE ANY REQUESTED QUIDANCE. WEFALAG DISTURBED WORK AREA, CLEARLY IDENTIFYING WETLAND AND STREAM EDGES AND BUFFERS, INSTALL SIGNS TO SIGNATE THE AREA AND ORANGE SAFETY FENCE TO IDENTIFY INFORTRAIT PROJECT ATTRIBUTES SUCH AS APPROVED ACCE AGS, NO REPUBLING ZONES, WETLANGSTREAM BOUNDS, ETC.
- 1 CONSTRUCT THE CONSTRUCTION ENTRANCE.
- CONSTRUCT ALL PROPOSED SEDIMENT CONTROL DEVICES AS SOON AS CLEARING AND GRUSSING OPERATIONS ALLOW
- 5. PRIOR TO GRADING OR OTHER EARTH DISTURBANCE ON THE PARCEL, PERMANENT DOWN SLOPE BMPs ARE TO BE INSTALLED,
- 6. CLEAR AND GRUB, REMOVE TOPSOL AND PLACE AS SHOWN ON THE PLANS, TOPSOL STOCKPILE TO BE SEEDED AND MILLCHED, EAS BURY SHALL BE CONSTRUCTED ANOUND TOPSOL STOCKPILES AS SHOWN.
- GRADING OPERATIONS AS REQUIRED, CUT SLOPES AND ALL SLOPES SHALL BE TOPSOLED AS NEEDED, DITCH LINES SHALL BE CLEANED, ALL DITCHES WILL HAVE AT LEAST GRASS LINNO PROTECTION OR AS SPECIFIED IN DETAIL ON SHEET IS.
- A THE ACCESS ROAD SHALL BE CONSTRUCTED UP TO THE PROPOSED PADS. THE ACCESS ROAD SHALL RECEIVE A STONE SURFACE.
- 9, INSTALL PROPOSED EQUIPMENT PAD AND EQUIPMENT PAD BERMS.
- 10. CULVERT INJET AND OUTLET PROTECTION SHALL BE CONSTRUCTED DIAGEDATELY UPON PLACEMENT OF INJETS AND CULVERTS. INSTALLATION OF MATTING AND/OR RIP RAP TO OCCUR ONCE DITCHES ARE CONSTRUCTED.
- 11. SIDE SLOPE STABILIZATION MATTING AND STABILIZATION SHALL OCCUR AS SOON AS POSSIBLE.
- 12. AT THE DID OF EACH WORK DAY, WHERE THE PARCEL HAS BEEN GRADED, INCLIDING ANY STREPPING, ETRUPING, LEVELING, 21 ON SIDE OLDES, ETC. DIDN AND TO BE RESTAULD. IN INC CASE IS THE CONTRACTOR TO LEVEL THE LOB STEFA TIME FIND OF THE WORD DIVENTION THE WORK DAY VILLESS THE CONFIDENCIAL DISCOVERATION. THE WORK DAY VILLES THE CONFIDENCIAL DISCOVERATION FOR THE WORK DAY VILLES THE CONFIDENCIAL DISCOVERATION. THE WORK DAY VILLES THE CONFIDENCIAL DISCOVERATION.
- 13. PRINCHINAL GRANE SEA MENTEN. TOPOCA. TO SE PLACED ON ALL GESTARGED ARGEA NOT LINES, SEED ALL DESTARGED ARGEA AS FOCKMEDLA SEA, DEAPER É BOOLGE RADIS AND TESTO DESTERBINE SEGOMENCIDED ARTIS EN DE DOCE SEMBLE I SANCIA RE FOLLOWING BATES SHOULD SEA MPUEDLA SEA MERGANE LINES ET A DATE D' 4 TODA FER ADOS, FERTULES, AT A BATE D' FOO LESS, OF LOZA-DEPER ADDE. ESED MINH ALL SER PRINCIPE OF THE FEODER AND DUES FOR ADDE OF THE ADDER ANT GUESSA.
- 14. LIME, FERTILIZER, AND SEED WILL BE APPLIED. HYDRO-MULCH PRODUCTS SHALL BE MIXED AND INSTALLED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS, OR EROSION CONTROL BLANKET SHALL BE INSTALLED PER PLANS & SPECIFICATIONS.
- 15. FINAL SEEDING MUST OCCUR WITHIN 7 DAYS OF FINAL GRADING.
- 18. WHEN SITE IS STABILIZED, ALL EROSION AND SEDIMENT CONTROL MEASURES CAN BE REMOVED AND REPAIR/STABILIZE THOSE AREAS OF ACCORDANCE WITH STATE STANDARDS.
- 17. FINAL SITE DISPECTION, A NOTICE OF TERMINATION SHOULD BE FILED WITH DEP UPON FINAL STABBLIZATION

GENERAL CONSTRUCTION NOTES

- THE WELL PAD AND FRESHWATER IMPOLIDMENTS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE CONSTRUCTION DOCUMENTS AND THE SCOPE OF WORK AND SHALL CONFORM GENERALLY WITH THE GRADES, BERILS, AND DIMENSIONS SHOWN.
- THE CONSTRUCTION DOCUMENTS SHOW THE EXISTING AND PROPOSED GRADES AND BERMS, ETC, THAT ALL CUT AND PILL ESTBATES ARE BASED UPON THE ENGINEER'S ESTBATES OF THE QUANTITIES ARE ONLY ESTBATES AND MAY CHANGE BASED ON ACTUAL PIELD
- THE GRADES, BERMS, DEPTHS, AND CINENSIONS MAY CHANGE BASED ON ACTUAL FIELD CONDITIONS. THE ENCINEER RESERVES THE RIGHT TO CHANGE GRADES, BERMS, DEPTHS AND CINENSIONS AS NECESSARY TO MEET RIELD CONDITIONS.
- THE CONTRACTOR SHALL PROVIDE THE ENCONEER ALL REASONABLE FACILITIES AND PROVIDE INFORMATION AND SAMPLES AS REQUIRED BY THE ENCONEER FOR PROPER MONITORING AND TESTING OF MATERIAL WORKMANISHP.
- THE CONTRACTOR SHALL HAVE ON SITE AT ALL TIMES WHEN CONSTRUCTION IS IN PROGRESS A COMPETENT SUPERINTEN THORQUIDALY FAMILIAR WITH THE CONSTRUCTION OF EARTH BERMS AND EMBANGMENTS, THE COMPACTION OF SOUS AND
- THE CONTRICTION IN HILL HESTALL RUISE SCOTE AND SUPER BLI FEMOLE PRIOR TO CLEARING AND OWNERSHOURS SHOWN ON THE DRIVINGS HE ACCOPRIANCE WITH WHOTE BEST HANGLOCKERST PRICATIONS ANKIALL OWNERS A SUPERIOR SHOULD BE OVER ANY FROM ALL EXCANATIONS AND THE FACE OF ALL FILLS TO PREVENT FLOODING AND SOFTENING OF THE SUBGRADE OR COMPACTED WITH TERMAL.
- CLEARED AND CRUSSING SMALL REMOVE ALL BRISN. TREES, ROOTS, STRAPS, FEXCES, SONS OR ANY OTHER MATERAL THAT IS NOT TO BE ROOSED FOR HE CONTINUED AND SMALL PROBLEM. TO COLUMN DESIGN TO THE CONTINUED AND SMALL PROBLEM. TO COLUMN DESIGN SMALL PROBLEM. TO COLUMN DESIGN SMALL PROBLEM. TO COLUMN DESIGN SMALL PROBLEM. THE CONTINUED AND PROSPECT OF SMALL PLANT AND SMALL PROBLEM. THE CONTINUED AND PROSPECT OF SMALL PLANT AND SMALL PROBLEM. THE SMALL PROBLEM SMALL PROBLEM. THE SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM. THE SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM. THE SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM. THE SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM. THE SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM. THE SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM SMALL PROBLEM. THE SMALL PROBLEM SMALL
- a. TOP SOIL SHALL BE STREPPED AND STOCKPILED WITH APPROPRIATE STABILIZATION TO PREVENT EROSION, THE TOP SOIL SHALL BE REUSED DURING THE RECLAMATION PROCESS AS MEEDED.
- PRIOR TO PLACING ANY RILL, THE EXPOSED SUBGRADE SHALL BE COMPACTED AND PROOF ROLLED TO PRODUCE A STABLE AND UNIVELDING SITE.
- 10, RPRAP USED AS OUTLET PROTECTION MAST BE MARD, ANGULAR AND OF A CAPALITY RESISTANT TO WEATHERING AND DISINTEGRATION, RPRAP SHOULD BE GROUTED ON STEEP OR LENGTHY FALL SLOPES WITH A MONDAIN THICKNESS TWO TIMES THE MAXIMUM STONE DIMARTER BUT NOT LESS THAN SEX KINGLES.
- THE PROPERTY OF THE LAGORITHOUSE UPTO OF UP TO 12" AND SHALL SE COMPACTED TO AT LEAST 89% OF THE LAGORITORY WASHAM ON DOISITY AS DETERMINED BY THE STANDARD PROCEDOR TEST METHOD (SATIO 1985). IT IS MOST STANDARD WASHAM ON DOISITY AS DETERMINED BY THE STANDARD PROCEDOR TO THE OWNER OF THE STANDARD STANDARD WASHAM TO STANDARD PROCEDORS OF THE LAGORITHOUSE OF THE STANDARD PROCEDUR. SEE THE CONTRACTOR SHALL DO SHALL DESIGNED THESE SEVENT HERDEL OFF STANDARD CONSTRUCTIONS OF THE EMPOREMENT RESIDENCE OF THE OWNER OF THE STANDARD OF THE STA
- 12. ON-SITE FILL SHALL BE USED TO THE MADMAN EXTENT POSSBUE, ANY IMPORTED FILL SHALL BE CERTIFIED BY THE CONTRACTOR TO BE CLEAR OF ALL HAZAPOLOUS SUSSTANCES OR INVERVALLS F MATERIAL IS ENCOUNTERED THAT CAMOUT BE REPRED BY A CAY ON MIT A SHALL TOWN IMPORED, TROIT THE CONTRACTION SHALL CONTRACT THE SHEEP WITH SHALL SHALL THE SIZE AND OFFICEMAME F THE MATERIAL MAY BE USED AS SO ON MIST BE RESOLVED BY OTHER MEANS, IF MICHARD SOLIS AN THE SUBSPACE ARE FOUND THE SHALL BE REMOVED AND REPRACED WITH APPROPRIATE FILL AT THE CONTRACTORS SERVICES FOR THE PERMITSET DIRECTION.
- 13. IF SPRINGS OR SEEPS ARE ENCOUNTERED, SUBSURFACE DRADAGE FEATURES SHALL BE INSTALLED PRIOR TO FILL PLACEARDIT, CONTACT ENGINEER FOR EVALUATION AND RECONMENDATION OF CORRECTIVE MEASURES. THE FILL TOE FOR ALL EMBARKMENTS SHALL BE BENCHED OR KEYED INTO THE NATURAL SCIL. ALL FILL TOES SHALL BE SUPPORTED BY COMPETENT BEDROOK OR SCIL MATERIAL.
- 15, FILL PLACED AGAINST EXISTING SLOPES SHALL BE BENCHED INTO THE EXISTING MATERIAL DURING ALL PLACEMENT TO REDUCE THE POTENTIAL FOR DEVELOPMENT OF A SMOOTH INTERFACE BETWEEN THE FILL AND EXISTING SLOPE.
- 16, ANY SOFT AREAS SHALL BE OVER-EXCAVATED TO A FIRM MATERIAL AND BACKFILLED WITH A WELL COMPACTED STRUCTURAL FILL.
- FILL REQUIRED TO OBTAIN DESIGN GRADES SHALL BE FRACED AS CONTROLLED, COMPACTED, ALL THE FILL SHALL BE FREE OF TRASH, WOOD, TOPSON, DRIANCS, COM, COAL MINE REPUSE, FROZEN MATERIAL AND PIECES OF ROCK GREATER THAN 6" IN ANY DIMENSION
- DURNO PLACEMENT OF INITIDAL LIGISTICS OF AERATE FACH LAYER OF FLL, AS RECESSARY, TO OFFINA THE REGULARD COMMUNITOR, TALL BOOLD NOT BE PLACED OF SURFACES THAT THE RECOVER OF PRODUCT OF PRODUCT OF THE PLACE OF THE P
- 19. SOB, WATERIAL WHICH IS REMOVED BECAUSE IT IS TOO WET TO PERMIT PROPER COMPACTION MAY BE SPREAD AND ALLOWED TO DRY DRYMO CAN BE FACILITATED BY DISCHOOL OR HARROWING UNTE, THE WOSTUNE CONTENT IS REDUCED TO AN ACCEPTABLE LEVEL. WHICH HE SOL, IS TOO DRY, WATER MAY BE UNFORMLY APPLIED TO THE LUTHER TO BE COMPACTED.
- 20. THE FILL OUTSLOPES SHALL BE OVERBUILT AND TRIMMED BACK TO DESIGN CONFIGURATIONS TO VERIFY PROPER COMPACTION.
- 21, GRANULAR MATERIALS, SUCH AS AASHTO NO, 57 STONE SHALL BE COMPACTED TO 65% OF ITS RELATIVE DENSITY, AS DETERMINED BY ASTMID 4253 AND 0.4254 TEST METHODS.
- 22. PHOTOGRAPHIC DOCLMENTATION SHALL BE TAKEN BY THE CONTRACTOR AND PROMDED TO THE ENGINEER OF THE POLLOWING ACTIVATION.

 - SITE AFTER CLEARING AND GRUSSING;
 THE SITE AFTER TOPSOL REMOVAL;
 TOE KEY AND INSPECTION TRENCH CONSTRUK
 DULLY PROTOS OF CUT AND FILL OPERATIONS;
 PROOF-POLLING TESTS.
- THE CONTRACTOR SHALL PROVIDE THE ENGINEER WITH A COMPLETE BINDER THAT INCLUDES ALL PHOTO DOCUMENTATION, ALL
 COMPACTION TEST REPORTS, RESULTS AND MAPS, AND A REPORT OF ALL CUT AND RILL VOLUMES IN CURIC YARDS.



230 Executive Orive, Suite 127 Crandwity Township, PA 15006 Phone: 734-773-7072



Signed By: JOSHUA M. FARLEY, W.V. P.E. 8 20711

	REVISIONS				
REV	DESCRIPTION	DSN	CHK APP	CATE	
HEV	DESCRIPTION	DWN	APP	- CAIE	
		1			
		$\overline{}$			
		Ţ			
		T T			
		Ĺ.			
		\vdash			
_		L.			
	!	L			

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

> SCALE VERIFICATION IF DISTANCE BELOW PLOTS DIFFERENTLY, SCALE ACCORDINGLY L_INCH_J

ORIGINAL DRAWING SIZE IS 22 x 34

NOTES

CPT-10 WFLL PAD DODDRIDGE COUNTY WEST VIRGINIA





Where energy meets innovation.


PERMITTING


PROJECT NO.	137355
ISSUE DATE	07/01/2015
CURRENT REVIS	ю .
DESIGNED BY	AER
ORAWN BY	AER
CHECKED BY	ДF
APPROVED BY	JAF


3
















KLEINFELDER









































30 NORTH AMERICAN GREEN C350 TURE REINFORCEMENT MATTING (OR EQUIVALENT).
22 Arts





Signed By: JOSHUA IA, FARLEY, W.V. P.E. # 20711

REVISIONS						
REV	DESCRIPTION	DSN	CHK APP	QATE		
-						
		\vdash	Н			
-+			Н			
		- ⊢-	ш			
			ш			
			ш			
		Г				
		\neg				
			П			
		_	-			
		-	Н			
			Н			
1		_	ш			
			ш			
- 1			ш			
			П			
- 1						
-		\neg	1			
- 1		-	Н			
		_	Н			

ISSUED FOR PERMITTING NOT RELEASED FOR CONSTRUCTION

> SCALE VERIFICATION IF DISTANCE BELOW PLOT DIFFERENTLY, SCALE ACCORDINGLY I DICH

ORIGINAL DRAWING SIZE IS 22 x 34

DETAILS

CPT-10 WELL PAD DODDRIDGE COUNTY WEST VIRGINIA




Where energy meets innovation.


PERMITTING


PROJECT NO.	137358
ISSUE DATE	07/01/2015
CURRENT REVISION	ж
DESIGNED BY	AEF
DRAWN BY	AER
CHECKED BY	2,65
ADDROVED DV	nes.

22









APPENDIX D

Agency Correspondence Letters

- USFWS
- WVSHPO





July 24, 2015

Mr. John Schmidt
Endangered Species Biologist
United States Fish and Wildlife Service
West Virginia Field Office
694 Beverly Pike
Elkins, West Virginia 26241

Re: Threatened and Endangered Species Consultation

CPT-10 Well Pad Project
Doddridge County, West Virginia
EQT Production Company

Dear Mr. Schmidt:

Kleinfelder, Inc. (Kleinfelder) is submitting this consultation on behalf of EQT Production Company (EQT) for the CPT-10 Well Pad Project (Project).

1.0 PROJECT DESCRIPTION

EQT is proposing to construct a well pad completion pit, flowback pit, and associated access roads in Doddridge County, West Virginia (WVV) (Figure 1). Site location maps are provided as Figure 1 (Project Location Map) and Figure 2 (Aerial Imagery Map). A review of the United States Fish and Wildlife Service (USFWS) Terrestrial and Aquatic buffer shapefiles, provided to Kleinfelder by the USFWS on June 25, 2015 and July 1, 2015, respectively, indicates no buffers occur within the 110.0-acre area of interest (AOI) (Figures 1 and 2). No National Wetland Inventory wetlands or National Hydrography Dataset streams occur in the AOI. Additionally, the AOI is not located within any known Federal Emergency Management Agency (FEMA) 100-year flood zones. The entire AOI is within the Middle Ohio North watershed, HUC-05030201. In order to protect on-site water quality, EQT will implement erosion and sediment controls within the limit of disturbance (LOD).

2.0 DELINEATION FINDINGS

Kleinfelder biologists conducted stream and wetland investigations and habitat assessments on October 30 – 31, 2013, August 19, 2014, February 2, 2015, and June 8, 2015 within the 110.0-acre AOI surrounding the Project. Seven (7) aquatic features were identified which consisted of one (1) intermittent stream, five (5) ephemeral streams and one (1) palustrine emergent (PEM) wetland (Figure 2).

3.0 SITE DESCRIPTION

Land cover types within the AOI consist primarily of deciduous forest and open pasture. The forested community is dominated by American beech (*Fagus grandifolia*), eastern white pine (*Pinus strobus*), shagbark hickory (*Carya ovata*), red oak (*Quercus rubra*), sugar maple (*Acer saccharum*), and white oak (*Quercus alba*).

4.0 THREATENED AND ENDANGERED SPECIES IN DODDRIDGE COUNTY, WEST VIRGINIA

The USFWS lists 18 animal species occurring within WV as either endangered or threatened. The table below summarizes the species that are known to occur within Doddridge County or are not defined at a county level.

Table 2: Threatened and Endangered Species Potentially Occurring or Known to Occur in Doddridge County

Common Name Scientific Name Status		
gray bat	Myotis grisescens	Endangered
Indiana bat	Myotis sodalis	Endangered
northern long-eared bat	Myotis septentrionalis	Threatened
clubshell	Pleurobema clava	Endangered
sheepnose mussel	Plethobasus cyphyus	Endangered
snuffbox mussel	Epioblasma triquetra	Endangered
spectaclecase (mussel)	Cumberlandia monodonta	Endangered
diamond darter	Crystallaria cincotta	Endangered
rufa red knot	Calidris canutus rufa	Threatened

5.0 POTENTIAL THREATENED AND ENDANGERED SPECIES HABITAT IN PROJECT AOI

Gray Bat

The gray bat roosts in caves year-round. A desktop review was conducted within a 2-mile radius of the proposed Project using topographic and aerial maps, historic mine data, and posted surface and underground mining permits within WV. The desktop review concluded there are no active surface or underground mining permits occurring within the AOI or 2-mile buffer of the Project. In addition, Kleinfelder staff biologists did not identify any caves or mine portals within the Project AOI during the site reviews. As a result, no impacts are proposed to caves or mine portals. Project-related activities will be confined to the permitted LOD.

Indiana Bat

During the site reviews, Kleinfelder assessed the on-site bat habitat and collected three (3) bat habitat sample points (Figure 2). The majority of the Project AOI contains mature upland forest with tree sizes ranging from approximately 10 to 30 inches diameter at breast height. Fourteen (14) potentially suitable secondary roost trees were observed within the AOI and two (2) of these potentially suitable secondary roosts were found within the LOD. No potentially suitable primary roost trees were identified within the AOI or proposed LOD. Kleinfelder Biologists referenced the *USFWS 2007 Indiana Bat (Myotis sodalis) Draft Recovery Plan* and USFWS WV Field Office's *Guidance on Developing and Implementing a Myotid Bat Conservation Plan* for guidance on distinguishing primary roost trees from secondary roost trees (Attachment A). Open access roads, county roads, and tree-lined pastures were observed and could potentially serve as flight corridors and foraging habitat. In addition, a large perennial stream, Broad Run, occurs adjacent to the AOI and could serve as a potentially suitable flight corridor and foraging habitat. Due to the presence of potentially suitable roost trees, migratory habitat, and foraging habitat, the proposed Project AOI contains good habitat for the Indiana bat.

The Indiana bat roosts in caves during the winter. A desktop review was conducted within a 2-mile radius of the proposed Project using topographic and aerial maps, historic mine data, and posted underground and surface mining permits within WV. The desktop review concluded there are no active surface or underground mining permits occurring within the AOI or 2-mile buffer of the Project. In addition, Kleinfelder staff biologists

did not identify any caves or mine portals within the Project AOI during the site reviews. As a result, no impacts are proposed to caves or mine portals. Project-related activities will be confined to the permitted LOD.

The proposed Project LOD will be 40.4 acres, of which approximately 32.1 acres are forested (based on GIS reviews of aerial photography). There are 8,042 pre-construction acres of land within a 2-mile radial buffer surrounding the proposed center point of the Project, of which 7,357 acres are forested. The post-construction forested land would be 7,324.9 acres within the 2-mile radial buffer. In Kleinfelder's professional opinion, sufficient forested habitat will remain on the post-construction landscape and the Project will not have an adverse effect on the Indiana bat or its habitat. Additionally, EQT proposes to conduct winter clearing between November 15, 2015 and March 31, 2016 while the Indiana bat is in hibernation.

Northern Long-Eared Bat

Since the time of the initial bat assessment, the northern long-eared bat (NLEB) was listed as threatened with an interim 4(d) rule under the Endangered Species Act. The final listing and interim rule became effective on May 4, 2015. The NLEB shares similar ecological needs to the Indiana bat and the assessment of the Project's potential effects on Indiana bats provided above are also applicable to the NLEB. However, the NLEB prefers to forage on forested hillsides and ridge-tops.

The Project AOI provides the NLEB with forested hillsides that could potentially serve as suitable foraging habitat. Due to the presence of potentially suitable migratory habitat, potentially suitable foraging habitat, and the presence of potential roost trees within the AOI, the proposed Project AOI contains good habitat for the NLEB. As such, EQT proposes to conduct winter clearing between November 15, 2015 and March 31, 2016 while the NLEB is in hibernation. The post-construction forested and would be 7,324.9 acres of the 7,357 acres of pre-construction forested land within the 2-mile radial buffer.

Mussels

There are no federal or state listed mussel streams within the Project AOI; therefore, impacts to mussel species are not anticipated by the proposed Project. The closest USFWS aquatic buffer is approximately 0.35 mile southwest of the proposed LOD and is associated with McElroy Creek. EQT will implement erosion and sediment control plans within the LQD in order to protect on-site water quality.

Diamond Darter

The diamond darter prefers sand and gravel dominated riverbeds. There are 122.5 miles of river that is considered critical habitat for this species. The only known population in WV exists in the lower Elk River of Clay and Kanawha Counties. The proposed Project is approximately 58.8 miles northeast of this critical habitat. The streams within the AOI do not have a direct hydrologic connection to Elk River; therefore impacts to the diamond darter resulting from the proposed Project are not anticipated.

Rufa Red Knot

The range of the rufa red knot includes coastal and inland habitats located in several regions within the western hemisphere. This species migrates between its breeding grounds in the Canadian Artic to several wintering regions annually. These wintering regions include the southeast United States, the northwest Gulf of Mexico, northern Brazil and Tierra del Fuego at the southern tip of South America. The proposed Project is located within the range for this species, but is not located within known breeding or wintering habitat. The nearest known habitat for the rufa red knot is Delaware Bay and is located approximately 282.1 miles east of the Project. Currently no critical habitat has been designated for this species. Impacts to the rufa red knot resulting from the proposed Project are not anticipated.

6.0 PROPOSED IMPACTS

The Project proposes impacts to potentially suitable foraging, migratory, and roosting habitat for the Indiana bat and NLEB. The Conservation Plan provided in Appendix A describes the proposed impacts as well as proposed avoidance and minimization measures. EQT proposes to conduct winter clearing of 32.1 forested acres between November 15, 2015 and March 31, 2016 while the Indiana bat and NLEB are in hibernation. Forested habitat remaining within a 2-mile buffer of the proposed Project would be approximately 7,324.9 acres (99.6% of forest remaining within a 2-mile buffer). Based on the proposed compensation measures (Appendix A) and the lack of state or federally listed mussel streams within the AOI, the Project is not anticipated to adversely affect the Indiana bat, NLEB, or other state or federally listed species.

7.0 AVOIDANCE & MINIMIZATION

To the extent practicable, the location of the proposed Project was developed to avoid and minimize aquatic feature, foraging, and migratory impacts as well as minimize forest clearing. Field data collected during stream and wetland delineations provided the basis for adjusting the Project location in a manner that minimized and avoided impacts to aquatic habitats and biological features. As result, project overlap with Broad Run and a USFWS aquatic buffer was avoided. However, EQT plans to implement erosion and sediment controls plans to protect on-site water quality within the LOD. Two (2) potentially suitable secondary roost trees identified within the LOD will be impacted by the proposed Project; therefore, minimal impacts to the potential roosting habitat of the Indiana bat and NLEB are anticipated (Figure 2). Additionally, forested clearing will be conducted between November 15, 2015 and March 31, 2016, to avoid any potential impacts to the Indiana bat and NLEB.

8.0 CONCLUSION

Kleinfelder requests any additional information concerning the potential occurrence of threatened and endangered species and their critical habitat within a 0.5-mile radius of the proposed Project and concurrence that the CPT-10 Well Pad Project will not adversely affect endangered species.

We appreciate your timely review of this request. Please contact Matthew Albright (724-831-5101) of Kleinfelder or Lacoa Corder (304-848-0066) of EQT with any questions.

Respectfully submitted,

matthing cought

Matthew Albright Project Manager

Enclosures (3)

Figure 1 –Project Location Map Figure 2 – Aerial Imagery Map Appendix A – Myotid Conservation Plan

FOR THE CPT-10 WELL PAD PROJECT

DODDRIDGE COUNTY, WEST VIRGINIA



Where energy meets innovation.

EQT PRODUCTION COMPANY 120 PROFESSIONAL PLACE BRIDGEPORT, WV 26330

PREPARED BY:

KLEINFELDER
Bright People. Right Solutions.

KLEINFELDER, INC. 230 EXECUTIVE DRIVE, SUITE 122 CRANBERRY TOWNSHIP, PA 16066

JULY 24, 2015

Indiana Bat/Northern Long-Eared Bat Summary Sheet for Option 1: Assumption of Presence

Project Name: CP1-10 Well Pad Project		
Project Location: 39.411532°, -80.6612	58°	
County: Doddridge County		
Project type: non-linear (2-mile buffer from centerpoint for	non-linear; ¼-mile buffer around center	line for linear)
# acres within Limits-of-Disturbance (I	LOD): 40.4	·
# acres forest in LOD prior to project c	onstruction: 32.1	in the second
# acres forest in LOD following to proje	ect construction:0.0	
Total # acres in buffer area: 8,042 (2-mile buffer from centerpoint for non-linear; 1/4-mile (2-mile buffer area is always 8,042 acres for non-linear # forested acres in buffer area prior to # forested acres in buffer area after pro Caves/mine portal presence? No If yes, suitable habitat? N/A	project construction: 7,357	
# Potential Indiana Bat Primary Roost	Trees within clearing limits:	0
# Potential Indiana Bat Primary Roost	Trees to be avoided: 0	
# Potential Indiana Bat Secondary Roo	st Trees within clearing limits	s: <u>2</u>
# Potential Indiana Bat Secondary Roo	st Trees to be avoided: 12	
#Potential NLEB Primary Roost Tree	within clearing limits: 2 (same	trees identified for Indiana Bat)
#Potential NLEB Primary Roost Trees	to be avoided: _12 (same trees	s identified for Indiana Bat)
CRA15L23399	Page 1 of 7	July 24, 2015

Avoidance and Minimization Measures to be Applied on Project

X	Seasonal tree clearing (all trees greater than 3" DBH) REQUIRED					
X	Avoid cutting potential roost trees					
	Avoid high quality foraging areas					
X	Minimize limits of disturbance (narrowed LOD or ROW)					
X	Minimize impacts (clearing) around suitable swarming and summer habitat and wetland/riparian zones					
	50-foot or greater forested buffer left along both sides of streams					
X	Collocate project features with previously disturbed or cleared areas					
	Phase tree clearing over multiple years					
	Reforest disturbed areas					
	Restore or enhanced riparian/wetland areas					
X	Strong erosion and sedimentation best management practices					
X	Pollution control plan in place					
	Suitable habitat acreage permanently preserved within or adjacent to the project site					
	Other:					
	Other:					
	Other:					
	Other:					
Conse	rvation Measures to be Applied on Project					
Х	Girdling trees on a 1:1 ratio for each potential roost tree that is lost during project development					
	Erecting artificial roosting structures on a 1:1 ratio for each potential primary roost tree that is					
_	lost during project development (a 2-year minimum monitoring plan of artificial structures)					
	Erecting artificial bark, bat boxes, or other artificial roosting structures (a 2-year minimum					
	monitoring plan of artificial structures)					
	Preservation of suitable Indiana bat and/or NLEB habitat off-site					
	Creation of watering areas; wetlands, or ponds					
	Other:					
	Other:					
	Other:					

1.0 PROJECT DESCRIPTION

EQT is proposing to construct a well pad, completion pit, flowback pit, and associated access roads in Doddridge County, West Virginia (WV) (Figure 1). Site location maps are provided as Figure 1 (Project Location Map) and Figure 2 (Aerial Imagery Map). A review of the United States Fish and Wildlife Service (USFWS) Terrestrial and Aquatic buffer shapefiles, provided to Kleinfelder by the USFWS on June 25, 2015 and July 1, 2015, respectively, indicates no buffers occur within the 110.0-acre area of interest (AOI) (Figures 1 and 2). No National Wetland Inventory wetlands or National Hydrography Dataset streams occur in the AOI. Additionally, the AOI is not located within any known Federal Emergency Management Agency (FEMA) 100-year flood zones. The entire AOI is within the Middle Ohio North watershed, HUC-05030201. In order to protect on-site water quality, EQT will implement erosion and sediment controls within the limit of disturbance (LOD).

2.0 DELINEATION FINDINGS

Kleinfelder biologists conducted stream and wetland investigations and habitat assessments on October 30 – 31, 2013, August 19, 2014, February 2, 2015, and June 8, 2015 within the 110.0-acre AOI surrounding the Project. Seven (7) aquatic features were identified which consisted of one (1) intermittent stream, five (5) ephemeral streams and one (1) palustrine emergent (PEM) wetland (Figure 2).

Table 1: Aquatic Features Identified in the Project AOI

Feature Name	Classification	Local Waterway	OHWM¹ Width (feet)	Location within AOI
Streams			· •	
Stream 1	Ephemeral	Unnamed Tributary (UNT) to Broad Run	4.5	Southwest
Stream 2	Ephemeral	UNT to Broad Run	4.5	Southwest
Stream 3	Ephemeral	UNT to Broad Run	5	Southwest
Stream 4	Ephemeral	UNT to Broad Run	4.5	Southwest
Stream 5	Ephemeral	UNT to Broad Run	0.7	East
Stream 6	Intermittent	UNT to Broad Run	4	Southeast
Wetlands	Marine San		•	
Wetland 1	PEM	// N/A	N/A	Southeast

Notes:

3.0 SITE DESCRIPTION

Land cover types within the AOI consist primarily of deciduous forest and open pasture. The forested community is dominated by American beech (*Fagus grandifolia*), eastern white pine (*Pinus strobus*), shagbark hickory (*Carya ovata*), red oak (*Quercus rubra*), sugar maple (*Acer saccharum*), and white oak (*Quercus alba*).

4.0 PROPOSED IMPACTS

The proposed Project LOD will impact approximately 40.4 acres, of which 32.1 acres are forested (based on GIS reviews of aerial photography). There are 8,042 acres of land within a 2-mile radial buffer surrounding the proposed center point of the Project. The wooded acreage of this buffer area is 7,357 acres. Post-construction wooded acreage would be 7,324.9 acres, which would amount to 99.6% forested land remaining

^{1.} Ordinary High Water Mark

within a 2-mile buffer. To avoid impacts to the Indiana bat and northern long-eared bat (NLEB), EQT proposes to complete winter tree clearing between November 15, 2015 and March 31, 2016 while these species are in hibernation. It is Kleinfelder's professional opinion that sufficient forested habitat will remain on the post-construction landscape to support the Indiana bat and NLEB.

5.0 POTENTIAL HABITAT IN PROJECT AOI

Caves and Mine Portals

The Indiana bat and NLEB roosts in caves during the winter. A desktop review was conducted within a 2-mile radius of the proposed Project using topographic and aerial maps, historic mine data, and posted surface and underground mining permits within WV. The desktop review concluded there are no active surface or underground mining permits occurring within the AOI or 2-mile buffer of the Project. In addition, Kleinfelder staff biologists did not identify any caves or mine portals within the Project AOI during the site reviews. As a result, no impacts are proposed to caves or mine portals. Project-related activities will be confined to the permitted LOD.

Forested Habitat

During the stream and wetland delineation activities performed on October 30-31, 2013, August 19, 2014, February 2, 2015, and June 8, 2015, Kleinfelder assessed the on-site bat habitat. Vegetative cover was evaluated for potentially suitable summer habitat. The 2015 Range-Wide Indiana Bat Summer Survey Guidelines along with habitat specifications outlined in the USRWS 2007 Indiana Bat (Myotis sodalis) Draft Recovery Plan and USFWS WV Field Office's Guidance on Developing and Implementing a Myotid Bat Conservation Plan were used as a reference to determine potential summer and winter habitats. Kleinfelder Biologists assessed potentially suitable roost trees within the AOI and characterized roost trees and/or snags as either primary or secondary. Primary roost trees, also known as maternity roost trees, typically have an average diameter at breast height (DBH) of 18 inches, direct sunlight for more than half the day, are in the early-to-mid stages of decay, and contain large, thick slabs of exfoliating bark. In addition to these conditions, primary roost trees suitable for the NLEB may also contain cavities underneath the bark, crevices, or hollows of both live and dead trees and/or snags. Secondary roost trees do not meet the primary specifications listed above; however have the potential to support roosting habitat for the Indiana bat and NLEB. The NLEB shares similar ecological needs with the Indiana bat and the assessment of the Project's potential effects on the summer roosting, migratory habitats and winter hibernacula of the Indiana bat provided in this plan are also applicable to the NLEB. In addition to riparian areas, the NLEB utilizes forested hillsides and ridge-tops as foraging habitat. Therefore, the foraging habitat of the NLEB is discussed separately in this conservation plan.

Fourteen (14) potentially suitable secondary roost trees were identified within the AOI (Figure 2, Table 2). No potentially suitable primary roost trees were identified within the AOI. Of the 14 potentially suitable secondary roost trees, two (2) potentially suitable secondary roost trees were located within the proposed LOD and 12 potentially suitable secondary roost trees were located outside of the LOD, in areas not proposed for tree clearing. Potentially suitable secondary roost trees proposed for cutting (inside LOD) are located within a forested landscape on relatively steep hillsides, which provide potentially suitable foraging habitat for the NLEB. However, most of the potentially suitable secondary roost trees have limited exposure to sun and wind and are located in areas where the overall usable habitat is low. Most of these trees are located near travel corridors and the potentially suitable foraging and migratory habitat provided by Broad Run, a large perennial stream adjacent to the Project.

Open access roads, county roads, and tree-lined pastures were observed and could potentially serve as flight corridors and foraging habitat. In addition, a large perennial stream, Broad Run, runs along the south border of the AOI and could serve as a potentially suitable flight corridor and foraging habitat. Due to the presence of potentially suitable roost trees, migratory and foraging habitat, the proposed Project AOI contained good habitat for the Indiana bat and NLEB. The table below summarizes the results of the habitat assessment including the average DBH of tree species.

Table 2: Potential Roost Tree (PRT) Information

Tree			DBH		Coordinates		Trees Cut in
Location ID#	Species	Classification	(in)	Live/Dead	Latitude	Longitude	LOD/ Trees Avoided ¹
PRT-01	Carya ovata	Secondary	30	Live	39.411657	-80.660318	Avoid
PRT-02	Carya ovata	Secondary	18	Live	39.411885	-80.660116	Avoid
PRT-03	Carya ovata	Secondary	18	Live	39.41281 <u>6</u>	-80.659052	Avoid
PRT-04	Carya ovata	Secondary	10	Live	39.412888	-80.659051	Avoid
PRT-05	Carya ovata	Secondary	14	Live	39.412960	-80.659018	Avoid
PRT-06	Carya ovata	Secondary	12	Live	39.413124	-80.659281	Cut
PRT-07	Carya ovata	Secondary	10	Live 🛵	×39.413260	<u>-</u> 80.658964	Avoid
PRT-08	Carya ovata	Secondary	12	Live	39.413318	-80.658654	Avoid
PRT-09	Carya ovata	Secondary	12	Live	39.414434	-80.659229	Avoid
PRT-10	Carya ovata	Secondary	10 (Live	39.414691	-80.659287	Avoid
PRT-11	Carya ovata	Secondary	10	Live	39,414473	-80.659467	Avoid
PRT-12	N/A	Secondary	12	Dead	39.416599	-80.663275	Avoid
PRT-13	N/A	Secondary /	30	Dead	39.416700	-80.662464	Cut
PRT-14	Carya ovata	Secondary	12	Live	39.413075	-80.658861	Avoid

Notes:

Habitat Impacts

Roosting

Fourteen (14) potentially suitable secondary roost trees were observed within the AOI. Of the 14 potentially suitable secondary roost trees, two (2) are located within the LOD. The remaining 12 potentially suitable secondary roost trees are found outside of the LOD and are not proposed for cutting. No potentially suitable primary roost trees were observed within the AOI.

Foraging

No suitable streams or open-water resources were found within the AOI. However, Broad Run, a large perennial stream, is located directly adjacent to the south border of the AOI and provides potentially suitable foraging and migratory habitat for the Indiana bat and NLEB. No impacts are proposed to Broad Run; however, EQT plans to implement erosion and sediment controls plans to protect on-site water quality within the LOD. The two (2) potentially suitable secondary roost trees located within the LOD occur on forested hillsides which provide potentially suitable foraging habitat for the NLEB. One (1) of these potentially suitable secondary roost

Trees listed as Avoid are located within the AOI, but outside the LOD. Trees identified outside of the AOI are not included.

tree is in close proximity to open-water, which provides potentially suitable foraging habitat. The other potentially suitable roost tree is in proximity to Broad Run, which serves as potentially suitable foraging habitat outside of the AOI.

Migratory

Observed access roads, county roads, and tree-lined pastures within the AOI offer numerous potentially suitable flight corridors for the Indiana bat and NLEB, in addition to providing potential foraging habitat.

In summary, most of the observed potentially suitable roost trees were located near, but not directly adjacent to potentially suitable open-water foraging habitat. Additionally, they were located on forested hillsides that are optimal NLEB foraging habitat. Most of the potentially suitable roost trees were located near or adjacent to travel corridors. As a result of the observed conditions above, the potential on-site summer habitat for the Indiana bat and NLEB was qualified as good. Based on the proposed conservation measures, limited impacts are proposed to the potential roosting and migratory habitats for the Indiana bat and NLEB within the LOD and 2-mile buffer established for the proposed Project. However, a majority of the 40.4 acre LOD is potentially suitable NLEB foraging habitat that will be impacted by the proposed Project. Broad Run, a large perennial stream, is located outside of the AOI; therefore no impacts are proposed to open-water. However, since Broad Run is directly adjacent to the Project, potentially suitable foraging habitat exists for both the Indiana bat and NLEB.

6.0 CUMULATIVE PROJECT CLEARING SUMMARY

Table 3: EQT Project(s) Occurring within the 2-mile Buffer of the Proposed Project

Project Title	Type of Project	Year of Concurrence	Year of Project Completion/To Be Completed	Coordinates	Tentative Amount of Tree Clearing
CPT-10 Well Line	Pipeline	N/A	To be completed in the next 5 years	N/A	<10 acres

No EQT projects have occurred within the 2-mile buffer surrounding the proposed Project in the past five (5) years. However, EQT plans to install a well line to the proposed CPT-10 Well Pad, currently known as the CPT-10 Well Line, within the 2-mile buffer in the next five (5) years. It is estimated that the CPT-10 Well Line will clear less than ten (10) acres of trees.

7.0 PROPOSED AVOIDANCE AND MINIMIZATION


EQT proposes to complete winter tree clearing of 32.1 forested acres between November 15, 2015 and March 31, 2016 while the Indiana bat and NLEB are in hibernation. During the on-site habitat analysis two (2) potentially suitable secondary roost trees were observed within the proposed LOD. The LOD was designed to minimize roost tree impacts; therefore, minimizing impacts to potentially suitable roosting habitat of the Indiana bat and NLEB. In order to further reduce potentially suitable habitat impacts for both bat species, erosion and sediment controls throughout the site will be enhanced per the EQT internal guidance for the purpose of protecting on-site water quality.


8.0 COMPENSATION MEASURES


EQT proposes to provide additional roosting habitat at a 1:1 ratio by girdling two (2) replacement trees at a USFWS-approved conservation parcel in Ritchie County, WV (Figure 3). This conservation parcel is approximately 16.5 miles southwest of the Project AOI. Girdling, in regards to Indiana bat or NLEB habitat mitigation, is defined as the cutting of the bark and a portion of the underlying cambium layer to create a ring-like groove encircling the base of the trunk. The trees proposed for girdling will be field located and their suitability determined by a qualified biological consultant or forester. In addition, no caves or mine portals were observed in the vicinity of the Project; therefore, the proposed Project will not result in adverse impacts to these features that require mitigation. Due to the amount of forested habitat left within a 2-mile buffer (7,324.9 acres) surrounding the proposed center point, coupled with the implementation of the proposed compensation measures, it is unlikely that the proposed impact to two (2) potentially suitable secondary roost trees will result in adverse impacts to Indiana bat or NLEB habitat.


9.0 SUMMARY

EQT proposes to conduct winter clearing of 32.1 forested acres between November 15, 2015 and March 31, 2016 while the Indiana bat and NLEB are in hibernation. Forested habitat remaining within a 2-mile buffer of the proposed site is approximately 7,324.9 acres (99.6% of total forested land remaining within a 2-mile buffer). Kleinfelder is requesting concurrence with the implementation of the proposed compensation measures that sufficient forested habitat will remain on the post-construction landscape; therefore, the Project will not adversely affect the Indiana bat or NLEB.



















Photograph 1 - KLF-BH01 - Facing North



Photograph 2 - KLF-BH01 - Facing South



Photograph 3 - KLE-BH02 - Facing North



Photograph 4 - KLF-BH02 - Facing South




Photograph 5 - KLF-BH03 - Facing East



Photograph 6 - KLF-BH03 - Facing West



Photograph 7 – PRT-06 – Facing West



Photograph 8 – PRT-13 – Facing North

INDIANA BAT FIELD HABITAT ASSESSMENT DATASHEET

Project Client/Name:	EQT Production Compa	ny/CPT-10 Well Pad		Date: 2/2/2015	
Sample site number(s):	BH-01				
Latitude, Longitude:	39.411765, -80.660755	5	Surveyor:	John Lewis/Mitch Fleming	
Include a map depicting locations of san	nple sites if assessing discrete habitats	at multiple sites in a proj	iect area.		
Brief Project Description					
Stream and wetland deline	ations conducted in an ap	pproximately 56.	1-acre area of int	erest proposed for an access	
road and well pad.					
	t-				
Land Use/Vegetation Assemblag Project AOI	ges in	Landscape within 1	-mile radius		
Describe the Site.		Flight corridors to oth	er forested areas?		
Land use inside the AOI co	nsists of two large	Within a 1-mile	radius there are	several county roads that	
agriculture fields, a recove	ring selective-cut forest,	could facilitate	bat movement.		
and a small portion of mat	ure secondary growth	Describe Adjacent Pro	perties (e.g. forested, g	grassland, development, water)	
forest in the northern port	ion of the AOI.	Adjacent proper	rties consist prim	narily of forested ridges and	
			some agricultura	-	
				* · · · · · · · · · · · · · · · · · · ·	
			A 1	:)	
Water Resources at Samp					
Stream Type (# and length)	Ephemeral	\alpha\ntermittent	Perennial	Describe existing condition of water sources:	
	1	0 0	<u></u> 0		
Pools/Ponds (# and size)	0	7.00	essible to bats?	There is a large perennial stream (Broad Run) that runs just outside	
Wetlands	Permanent			the southern border of the AOI. It	
(approx. ac.)	0	0		is accessible to bats.	
Forest Resources at Samp	lociéo	·			
	Canopy (> 50')	Midstory (20-50')	Understory (<20')	1=1-10%, 2=11-20%, 3=21-40%, 4=41-60%,	
Closure/Density	4	4	3	5=61-80%, 6=81-100%	
% Trees w/ Exfoliating Bark	10%	0	0		
Size Composition of	Small (3-8 in DBH)	Med (9-15 in DBH)	Large (>15 in DBH)	1	
Live Trees (%)	20	60	20		
Dominant Species of Mature Trees	Carya ovata , Quer	rcus alba , Pinus s	trobus , Quercus	rubra	
No. of Suitable Snags	2				
Suitable snags are standing dead tre	es with exfoliating bark, cracks, cre	vices or hollows. Snags	without these characte	eristics are not considered suitable.	

AT THE SAMPLE POINT, IS THERE POTENTIAL:

Summer roosting habitat? x
Foraging habitat? x
Travel corridors? x

INDIANA BAT FIELD HABITAT ASSESSMENT DATASHEET

Detailed Habitat Information

Potential Maternal Roost Trees (MRTs) Potential Roost Trees (PRTs) Are there any potential MRTs? Describe (include number, species, and Describe, including live and dead (snag) trees. (PRTs must have DBH > 3 in. PRTs size). Must meet the following criteria: 1) \geq 16 in DBH; significant areas should always be indicated when the trees do not meet all the criteria for MRTs. of peeling bark, crack, or crevices; and 3) must receive significant solar Include number, species, and size of potential PRTs. exposure on southern facing slopes. No potential maternal roost trees were observed. Yes, please reference Table 2 in the Indiana Bat and Northern Long-Eared Bat Conservation Plan. Travel corridors Foraging habitat Describe (Are there tree-lined paths, wooded corridor, riparian Describe (are there open wooded areas, forest edges, riparian areas, e.g.? corridors, e.g.?) The southern portion of the AOI offers strong potential for Broad Run Road could facilitate bat movement and foraging habitat. There are active open pastures that surround Broad Run, a large perennial stream. act as a travel corridor to other foraging habitat and roost trees. Summer roosting habitat Is there suitable summer roosting habitat? Yes No х **Habitat Rating:** Forest/woodlot containing potential roost trees and/or snags ≥5 inches DBH. Good No potential roost trees and/or snags ≥5 inches DBH. Habitat includes other trees > inches DBH and any Marginal combination of emergent wetlands, edge habitat along agricultural fields, fencerows, wooded corridors, and/or riparian forests. None of the features listed above. This category may include ≥20 acres of early successional habitat with Poòr: trees $\frac{3-5}{2}$ inches DBH. This may serve as suitable foraging habitat and require surveys by the USFWS and/or state agencies. None of the features listed above. No suitable trees or other roosting habitat available within the sample Not available point/project area. Winter Hibernacula Are there any portals or mines? Describe and photograph. Are there openings, shafts, crack/crevices? There should be horizontal openings >6 inches with air flow, vertical shafts >1 foot, passages that continue > 50 ft., and/or any other openings that may lead to deeper cavities/fissures. No winter hibernacula was observed.

INDIANA BAT FIELD HABITAT ASSESSMENT DATASHEET

Project Client/Name:	EQT Pro	duction Compa	ny/CPT-10 Well	Pad	Date: 2/2/2015
Sample site number(s):	BH-02				
Latitude, Longitude:	39.412992, -80.658886 Surveyor:				John Lewis/Mitch Fleming
include a map depicting locations of sample	sites if asses	sing discrete habitats at	multiple sites in a projec	ct area.	
Brief Project Description					
Stream and wetland delinea	tions con	ducted in an ap	proximately 56.	1-acre area of in	nterest proposed for an access
road and well pad.					
	. • .	ı .			
Land Use/Vegetation Assemblage Project AOI	s in		Landscape within 1	L-mile radius	
Describe the Site.			Flight corridors to oth		
Land use inside the AOI con	sists of tv	vo large	_		e several county roads that
agriculture fields, a recoveri		_		bat movement.	·
and a small portion of matu	-		Describe Adiacent Pro	operties (e.g. forested.	, grassland, development, water)
forest in the northern portion	on of the	AOI.			marily of forested ridges and
				some agricultur	
			siopes we	Some agricultar	an lands.
					<u>V</u>
		_			
Water Resources at Sample	Site		Or V	200	
Stream Type		Ephemeral	Intermittent	Perennial	Describe existing condition of
(# and length)		1	() 0	> 0	water sources:
Pools/Ponds		0	Open and accessible to bats?		There is a large perennial stream (Broad Run) that runs just outside
(# and size)	1	11 13 13 13 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1	I/A '	the southern border of the AOI. It
Wetlands (approx. ac.)		Permanent 0	Sea	ssonal 0	is accessible to bats.
(upprox. uc.)			<u> </u>	U	
Forest Resources at Sample	Site	19 3			
Closure/Density	C	anopy (> 50')	Midstory (20-50')	Understory (<20')	1=1-10%, 2=11-20%, 3=21-40%, 4=41-60%,
•	13	47	4	3	5=61-80%, 6=81-100%
% Trees w/ Exfoliating Bark		10%	0	0	
Size Composition of	Small (3-8 in DBH)		Med (9-15 in DBH)	Large (>15 in DBH)	
Live Trees (%)		25	50	25	<u> </u>
Dominant Species of Mature Trees	Car	ya ovata , Quero	cus alba , Pinus s	strobus , Quercus	s rubra
No. of Suitable Snags	1	2	I	1	
Suitable snags are standing dead trees	with exfolia	iting bark, cracks, crev	vices or hollows. Snag	■ s without these charac	teristics are not considered suitable.
AT THE SAMPLE POIN	IT, IS THE	ERE POTENTIAL	:	Fora	sting habitat? <u>x</u> ging habitat? <u>x</u> vel corridors? x

KLEINFELDER INDIANA BAT FIELD HABITAT ASSESSMENT DATASHEET

Detailed Habitat Information

Potential Maternal Roost Trees (MRTs) Potential Roost Trees (PRTs) Are there any potential MRTs? Describe (include number, species, and Describe, including live and dead (snag) trees. (PRTs must have DBH ≥ 3 in. PRTs size). Must meet the following criteria: 1) \geq 16 in DBH; significant areas should always be indicated when the trees do not meet all the criteria for MRTs. of peeling bark, crack, or crevices; and 3) must receive significant solar Include number, species, and size of potential PRTs. exposure on southern facing slopes. No potential maternal roost trees were observed. Yes, please reference Table 2 in the Indiana Bat and Northern Long-Eared Bat Conservation Plan. Travel corridors Foraging habitat Describe (Are there tree-lined paths, wooded corridor, riparian Describe (are there open wooded areas, forest edges, riparian areas, e.g.? corridors, e.g.?) The southern portion of the AOI offers strong potential for Broad Run Road could facilitate bat movement and foraging habitat. There are active open pastures that act as a travel corridor to other foraging habitat and surround Broad Run, a large perennial stream. roost trees. Summer roosting habitat Is there suitable summer roosting habitat? Yes No х **Habitat Rating:** Forest/woodlot containing potential roost trees and/or snags ≥5 inches DBH. Good No potential roost trees and/or snags ≥5 inches DBH. Habitat includes other trees > inches DBH and any Marginal combination of emergent wetlands, edge habitat along agricultural fields, fencerows, wooded corridors, and/or riparian forests. None of the features listed above. This category may include ≥20 acres of early successional habitat with **Poor** trees 3-5 inches DBH. This may serve as suitable foraging habitat and require surveys by the USFWS and/or state agencies. None of the features listed above. No suitable trees or other roosting habitat available within the sample Not available point/project area. Winter Hibernacula Are there any portals or mines? Describe and photograph. Are there openings, shafts, crack/crevices? There should be horizontal openings >6 inches with air flow, vertical shafts >1 foot, passages that continue > 50 ft., and/or any other openings that may lead to deeper cavities/fissures. No winter hibernacula was observed.

KLEINFELDER INDIANA BAT FIELD HABITAT ASSESSMENT DATASHEET

Project Client/Name:	EQT Pro	duction Compa	ny/CPT-10 Well Pad		Date:	2/2/2015
Sample site number(s):	BH-03					
Latitude, Longitude:	39.413471, -80.660781 Surveyor:				John Lewi	is/Mitch Fleming
nclude a map depicting locations of sample	sites if asse	ssing discrete habitats a	t multiple sites in a projec	ct area.		
Brief Project Description		_			_	
Stream and wetland delinea	tions co	nducted in an ap	proximately 56.	1-acre area of in	terest pro	posed for an
access road and well pad.						
Land Use/Vegetation Assemblage	s in] 1				
Project AOI			Landscape within 1	-mile radius		
Describe the Site.			Flight corridors to othe	er forested areas?		
Land use inside the AOI cons		_	Within a 1-mile	radius there are	several co	ounty roads that
agriculture fields, a recoveri			could facilitate b	oat movement.		
and a small portion of matur		. –	Describe Adjacent Pro	perties (e.g. forested,	grassland, de	velopment, water)
forest in the northern portion	n of the	AOI.	Adjacent proper	ties consist prin	narily of fo	rested ridges and
		!	hill slopes with	some agricultura	al lands.	
					>	
Water Resources at Sample	Sito	1		, ,		
Stream Type	·	Ephemeral Ephemeral	Intermittent	Perennial	Describe ex	isting condition of
(# and length)		1	11/0/	[*] 0	water sources:	
Pools/Ponds	1		Open and accessible to bats?		There is a la	arge perennial stream
(# and size)	ł		N/A		•) that runs just outside
Wetlands		Permanent	Seasonal		the souther is accessible	rn border of the AOI. It
(approx. ac.)	1 The last	0	0		is decessible to buts.	
Forest Resources at Sample	(Site					
	1	anopy/(>/50')	Midstory (20-50')	Understory (<20')	1=1-10%, 2=11	-20%, 3=21-40%, 4=41-60%,
Closure/Density	13	/3/	3	4	5=61-80%, 6=8	31-100%
% Trees w/	1	10%	0	0		
Exfoliating Bark		1070			1	
Size Composition of	Small (3-8 in DBH)		Med (9-15 in DBH)	Large (>15 in DBH)	4	
Live Trees (%)		50	40	10	<u> </u>	1
Daminant Carrier of						
Dominant Species of Mature Trees	Car	ya ovata , Quero	cus alba , Pinus st	trobus , Quercus	rubra	
No. of Suitable Snags		2				
Suitable snags are standing dead trees	with exfoli	ating bark, cracks, cre	vices or hollows. Snag	s without these chara	cteristics are r	ot considered suitable.

AT THE SAMPLE POINT, IS THERE POTENTIAL:

Summer roosting habitat? x

Foraging habitat? x
Travel corridors? x

INDIANA BAT FIELD HABITAT ASSESSMENT DATASHEET

Detailed Habitat Information

Potential Maternal Roost Trees (MRTs)		Potential Roost Trees (PRTs)	\neg		
Are there any potential MRTs? Describe (include number, species, and		Describe, including live and dead (snag) trees. (PRTs must have DBH ≥ 3 in. PRTs should always be indicated when the trees do not meet all the criteria for MRTs.			
Travel corridors		Foraging habitat			
that run through the middle and sout	m access roads	Describe (are there open wooded areas, forest edg The southern portion of the AOI offe foraging habitat. There are active op surround Broad Run, a large perenni	ers strong potential for pen pastures that		
of the AOI.					
Summer roosting habitat	1				
Habitat Rating: Good x Marginal Poor Not available	No potential roost trees and/or riparian fores Trees 3-5 inches DBH and/or/state agencie	taining potential roost trees and/or snags ≥5 inches rees and/or snags ≥5 inches DBH. Habitat includes o ergent wetlands, edge habitat along agricultural field sts. Is listed above. This category may include ≥20 acres H. This may serve as suitable foraging habitat and re	other trees > inches DBH and any ds, fencerows, wooded corridors, of early successional habitat with equire surveys by the USFWS		
Winter Hibernacula Are there any portals or mines? Describe and photo	ograph. Are there op	penings, shafts, crack/crevices? There should be hori	rizontal openings >6 inches with		
air flow, vertical shafts >1 foot, passages that continued in the continue		any other openings that may lead to deeper cavities,	;/fissures.		

July 17, 2015

Ms. Lora A. Lamarre-DeMott Senior Archaeologist West Virginia Division of Culture and History The Cultural Center - Capitol Complex 1900 Kanawha Blvd., E Charleston, WV 25305-0300 (304) 558-0220

Re: Cultural Resources Desktop Analysis

EQT Production Company CPT-10 Well Pad Project Doddridge County, West Virginia

Dear Ms. Lamarre-DeMott:

EQT Production Company (EQT) is proposing the installation of a drainage ditch along County Route 4 to support oil and gas activities associated with the proposed CPT-10 Well Pad Project (Project) in Doddridge County, West Virginia (Figures 1 and 2). Construction of the road side drainage ditch will result in less than 100 linear feet of impact to one (1) intermittent stream, which meets the terms and conditions of a non-reporting Nationwide Permit 14, therefore, no consultation with the United States Army Corps of Engineers (USACE) is required (Figure 3).

In order to comply with the requirements of Section 106 of the National Historic Preservation Act, on June 30, 2015, Environment & Archaeology, LLC was retained by Kleinfelder, Inc. to provide cultural resource consultation for the proposed Project. This consultation was conducted under the authority of the National Historic Preservation Act of 1966 (PL 89-665), the National Environmental Policy Act of 1969 (PL 91-190), the Archaeological and Historic Preservation Act of 1974 (PL 92-291), the Protection of Historic Cultural Properties (36 CFR 800), and the Guidelines for Phase I Surveys, Phase II Testing, Phase III Mitigation and Cultural Resource Reports (WVDCH 2005). Environment & Archaeology, LLC is providing this cultural resources desktop analysis as part of EQT's Section 106 due diligence for the CPT-10 Well Pad Project.

The Project area is situated within the Western Allegheny Plateau Section of the Appalachian Plateau Physiographic Province and is located on steeply sloped hillslopes containing second growth forested lands above Broad Run with limited level ridgeline areas (Figures 3 and 4). Since the general soil maps for Doddridge County, West Virginia have not been digitized and are not available on the Web Soil Survey website, a discussion of the soil association(s) potentially present within the Project Area is not possible. However, there are approximately three (3) soil types present within the Project limits-of-disturbance (LOD) (Table 1, Figure 5).

Table 1. Soil Types Encountered by the Proposed Project in Doddridge County, West Virginia.

Soil Type	Description	Setting
GsE	Gilpin-Peabody complex, 15 - 35% slopes, very stony fine- loamy clayey residuum from shale and siltstone and interbedded sedimentary rock, well drained	Hillslopes, backslope, side slope
GsF	Gilpin-Peabody complex. 35 - 70% slopes, very stony fine- loamy clayey residuum from shale and siltstone and interbedded sedimentary rock, well drained	Hillslopes, backslope, side slope
SeB	Sensabaugh silt loam, 3 - 8% slopes, rarely flooded, gravelly fine-loamy alluvium from interbedded sedimentary rock, well drained	Flood plains, toeslopes

Historic maps and quadrangles were examined in an attempt to identify the potential for historic structures to be present within the Project LOD. The 1933 Doddridge County, West Virginia Atlas Page from the West Virginia State Atlas published by the Clarksburg Publishing Company failed to turn up structures within the proposed Project LOD (Figure 6). The 1903 (1924 culture revised) USGS 15-minute Northwest Centerpoint, West Virginia, Quadrangle, also failed to turn up structures within the proposed Project LOD (Figure 7).

A Literature Review of the Restricted Data found online at the West Virginia State Historic Preservation Office (WVSHPO) Interactive Map Viewer Page was performed on July 9, 2015 by Environment & Archaeology, LLC Archaeology Project Manager/Principal Investigator Luke W. Erickson, M.A., RPA to determine the presence or lack of, previously inventoried prehistoric or historic sites, structures, features, bridges or Phase I Surveys (cultural resources) within the proposed Project LOD and to help evaluate the potential for the Project LOD to contain cultural deposits. As a result of this Literature Review, no previously inventoried cultural resources were identified within, immediately adjacent to within 1,000-feet of or within a one-mile radius of the proposed Project LOD.

The aquatic feature to be impacted consists of an existing culverted stream located immediately adjacent to and crossing underneath County Route 4 (CR 4) (Photos 1 and 2). This stream is within a previously disturbed roadside ditch therefore any construction activities planned for this aquatic feature will not result in any new impacts to this resource. The Area of Potential Effect (APE) for this proposed Project consists of an area approximately 100-feet by 100-feet leading up to and away from each side of the stream as it enters and exits the culvert running underneath CR 4. However, this APE consists of disturbed soils, therefore it is the recommendation of *Environment & Archaeology, LLC* that a Phase I Cultural Resource Survey is not warranted for this feature.

Lora Lamarre-DeMott Page 3

Please submit a written response of your review of this letter. If you should have any questions, please feel free to contact me.

Sincerely,

Luke W. Erickson, M.A., RPA

Luke W. Trukson

Archaeology Project Manager/Principal Investigator

Cc:

Matt Albright, Project Manager, Kleinfelder Inc. Lacoa Corder, EQT Production Company




Figure 1. State Map of West Virginia Showing the Location of the Proposed EQT CPT-10 Well Pad Project in Doddridge County.




Figure 2. The Proposed EQT CPT-10 Well Pad Project in Doddridge County, West Virginia on the 7.5-minute USGS Center Point, West Virginia, Quadrangle. Quadrangle Courtesy of ESRI Online Mapping Services.




Figure 3. The Proposed EQT CPT-10 Well Pad Project Identifying the area-of-potential-effects (APE) (white circle) that will require the road side drainage ditch. Quadrangle Courtesy of ESRI Online Mapping Services.




Figure 4. The Proposed EQT CPT-10 Well Pad Project. Aerial Imagery Courtesy of ESRI Online Mapping Services.




Figure 5. The Proposed EQT CPT-10 Well Pad Project with USDA Soil Overlay. Aerial Imagery Courtesy of ESRI Online Mapping Services.




Figure 6. The Red Circle Identifies the area that the Proposed EQT CPT-10 Well Pad Project is located within. Background imagery is the 1924 USGS 15-minute Northwest Centerpoint, West Virginia, Quadrangle.




Figure 7. The Red Shape Identifies the area that the Proposed EQT CPT-10 Well Pad Project is located within. Background imagery is the 1933 Doddridge County Atlas Page from the 1933 Clarksburg Publiching Company, West Virginia State Atlas.



Photo 1. Facing South looking at the inlet for the existing, channelized, ditched stream to be upgraded.




Photo 2. Facing North looking at the outlet for the existing, channelized, ditched stream to be upgraded. County Route 4 can be seen in this photo.